

# USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Olympia™ Micro™ Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand Identitee® DXI™ Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light-reflective finish (LR-0.86) reduces light fixtures and energy use.
- USDA Certified Biobased Product.<sup>7</sup>
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

## APPLICATIONS

- Offices
- Classrooms
- Reception/Lobby Areas
- Hotels
- Conference Areas
- Retail Stores

## SUBSTRATE

- Wet-formed Mineral Fiber

Fine-Textured Panel

# USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

## CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE  
USG: usg.com or samplitt@usg.com  
CGC: contact Sales Representative

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com  
usg.ecomedes.com

TECHNICAL SERVICES  
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
ULCOM/GG  
UL 2818































**30** YEAR LIMITED SYSTEM WARRANTY  
• No Visible Sag  
• Mold/Mildew Protection

**10** YEAR AVAILABILITY  
4211, 4221, 4231,  
4411, 4421, 4742,  
4744

**HRC** HIGH RECYCLED CONTENT



UL Classified

Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR <sup>2</sup>	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content <sup>1</sup>	Panel Cost
SQ 	2'x2'x5/8"	Class A 	<b>4210</b>	—	35	0.86	White	A,B,C 	Low 		66% 	<b>\$\$</b> 
	2'x4'x5/8"	Class A	<b>4913</b>	—	35	0.86	White	A,B	Low		66%	<b>\$\$</b>
SQ 	2'x2'x5/8"	Class A	<b>4211</b>	0.50	30	0.86	White	A,B,C	Low		66%	<b>\$\$</b>
	2'x4'x5/8"	Class A	<b>4411</b>	0.50	30	0.86	White	A,B	Low		66%	<b>\$\$</b>
SLT 	2'x2'x5/8"	Class A	<b>4221</b>	0.50	35	0.86	White	D	Low		66%	<b>\$\$</b>
	2'x4'x5/8"	Class A	<b>4421</b>	0.50	35	0.86	White	D	Low		66%	<b>\$\$</b>
FLB 	2'x2'x5/8"	Class A	<b>4231</b>	0.50	35	0.86	White	E,F,G,H	Low		66%	<b>\$\$</b>
	2'x4'x5/8"	Class A	<b>4431</b>	0.50	35	0.86	White	E,F,G,H	Low		66%	<b>\$\$</b>
SQ 	2'x2'x3/4"	Class A	<b>4750</b>	0.60	33	0.86	White	A,B,C	Low		80%	<b>\$\$</b>
	2'x4'x3/4"	Class A	<b>4751</b>	0.60	33	0.86	White	A,B	Low		80%	<b>\$\$</b>
SLT 	2'x2'x3/4"	Class A	<b>4752</b>	0.60	35	0.86	White	D	Low		80%	<b>\$\$</b>
	2'x4'x3/4"	Class A	<b>4753</b>	0.60	35	0.86	White	D	Low		80%	<b>\$\$</b>
FLB 	2'x2'x3/4"	Class A	<b>4754</b>	0.60	35	0.86	White	E,F,G,H	Low		80%	<b>\$\$</b>
	2'x4'x3/4"	Class A	<b>4755</b>	0.60	35	0.86	White	E,F,G,H	Low		80%	<b>\$\$</b>
SLT <sup>4,11</sup> 	2'x4'x3/4"	Class A	<b>4742</b>	0.50	35	0.86	White	D	Low		66%	<b>\$\$</b>
ILT <sup>5,11</sup> 	2'x4'x3/4"	Class A	<b>4744</b>	0.50	35	0.86	White	I	Low		66%	<b>\$\$</b>

USG OLYMPIA™ MICRO™  
PANELS UNPERFORATED<sup>9</sup>

USG OLYMPIA™ MICRO™  
PANELS 50 NRC<sup>6</sup>

USG OLYMPIA™ MICRO™  
PANELS 60 NRC<sup>6,10</sup>

USG OLYMPIA™  
MICRO™ ILLUSION™  
TWO/24 PANELS

### PATTERNS

#### USG Illusion™ Two/24












**Low Emissions (VOC)**  
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.ecomedes.com and at spot.ul.com.

**ClimaPlus™ Warranty Performance<sup>3</sup>**  
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

**High Recycled Content**  
USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of pre-consumer (post-industrial) and post-consumer recycled content per FTC guidelines.

### GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C <sup>8</sup> USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Identitee™ DXI™	G USG Fineline™ DXF™	H USG Fineline™ 1/8 DXFF™	I USG Centricitee™ DXT™
								

### PHYSICAL DATA/ FOOTNOTES

**Product literature**  
Data sheet: SC2180

**ASTM E1264 classification**  
ASTM E1264-22 Type III, Form 2, Pattern C & E  
ASTM E1264-23 Type A, Form A1.2, Pattern C & E

**ASTM E84 and CAN/ULC S102 surface-burning characteristics**  
Class A  
Flame spread: 25 or less  
Smoke developed: 50 or less

**Online tools**  
usgdesignstudio.com, cgcdesignstudio.com  
or usg.ecomedes.com

**Weight**  
0.77-1.00 lb./sq. ft.

**Thermal resistance**  
R-1.4 (5/8" panels)  
R-1.7 (3/4" panels)

**Maximum backloading**  
See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

**Maintenance**  
Can be cleaned easily with a soft brush or vacuum.

- Notes**
- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
  - LR values are shown as averages.
  - For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
  - Panels have 15/16" routing.
  - Panels have 9/16" routing.
  - Mixing 0.50 and 0.60 NRC panels in the same ceiling plane is not recommended.
  - This product has achieved both BioPreferred Initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

- Maximum 2'x2' with SQ edge panels.
- Item numbers 4210 and 4913 are not UL Classified for acoustics.
- It is not recommended to mix panels with varying NRC values in the same ceiling plane.
- SLT & ILT Illusion™ edges have a different reveal depth from SLT or FLB edge details. Please reference the System Interface, located in the SC2000, before installing.

**Notice**  
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2180/rev. 7-24  
© 2024 USG Corporation and/or its affiliates. All rights reserved.  
Printed in USA

Manufactured by USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, FINELINE, IDENTITEE, ILLUSION, MICRO, OLYMPIA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

