

USG PREMIER HI-LITE™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Premier Hi-Lite™ Kapok Panels
with ClimaPlus™ Performance/
USG Donn® Brand DX®
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050



Flat Black
205

FEATURES AND BENEFITS

- Washable vinyl face for easy maintenance.
- Excellent noise reduction with NRC of 0.70 for greater sound control in open-plan spaces.
- Lightweight fiberglass basemat makes installation fast and easy.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

APPLICATIONS

- Discount Stores
- Grocery Stores
- Mass Merchandisers
- Retail Stores

SUBSTRATE

- Fiberglass

Medium-Textured Panel, Kapok Perforated and Unperforated

Medium-Textured Panel, Twill Perforated and Unperforated

USG PREMIER HI-LITE™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
 USG: usg.com or samplitt@usg.com
 CGC: contact Sales Representative

TECHNICAL SERVICES
 800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL
 usgdesignstudio.com
 cgcdesignstudio.com
 usg.ecomedes.com

30 YEAR LIMITED SYSTEM WARRANTY
 • No Visible Sag
 • Mold/Mildew Protection

UL Classified

Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color ⁴	Grid Options	Anti-Mold & Mildew/ Sag Resistance	Recycled Content ¹	Panel Cost
USG PREMIER HI-LITE™ TWILL PANELS 	2'x2'x5/8" Perforated	Class A	7050G	0.70	20	0.76	White	A, B, C, D		42%	\$
	2'x2'x5/8" Unperforated	Class A	7052G	0.50	20	0.76	White	A, B, C, D		42%	\$
	2'x4'x5/8" Perforated	Class A	7051G	0.70	20	0.76	White	A, B, C, D		42%	\$
	2'x4'x5/8" Unperforated	Class A	7053G	0.50	20	0.76	White	A, B, C, D		42%	\$
USG PREMIER HI-LITE™ KAPOK PANELS 	2'x2'x5/8" Perforated	Class A	7054G	0.70	20	0.76	White and Black	A, B, C, D		42%	\$
	2'x2'x5/8" Unperforated	Class A	7056G	0.50	20	0.76	White and Black	A, B, C, D		42%	\$
	2'x4'x5/8" Perforated	Class A	7055G	0.70	20	0.76	White and Black	A, B, C, D		42%	\$
	2'x4'x5/8" Unperforated	Class A	7057G	0.50	20	0.76	White and Black	A, B, C, D		42%	\$

ClimaPlus™ Warranty Performance³
 Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

GRID PROFILE OPTIONS

A USG DX®	B USG DXW™	C USG ZXLA™	D USG AX™

PHYSICAL DATA/ FOOTNOTES

<p>Product literature Data sheet: SC1838</p> <p>ASTM E1264 classification ASTM E1264-22 Type XII, Form 1, Pattern C & E (perforated), Pattern E (unperforated)</p> <p>ASTM E1264-23 Type B, Form B1, Pattern C & E (perforated), Pattern E (unperforated)*</p> <p>ASTM E84 and CAN/ULC S102 surface-burning characteristics Class A Flame spread: 25 or less Smoke developed: 50 or less</p> <p>Online tools usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com</p>	<p>Weight 0.18 lb./sq. ft.</p> <p>Thermal resistance R-2.7</p> <p>Maximum backloading See USG 30-Year Limited System Warranty Commercial Applications (SC2102).</p> <p>Maintenance Can be cleaned easily with a damp sponge.</p> <p>Metric sizes available Contact sales for minimum quantities and lead times.</p>	<p>Notes</p> <ol style="list-style-type: none"> For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com. LR values are shown as averages. Published values are representative for White panels only. For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102). See Colors selector for more information.
---	---	---

Notice
 The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1838/rev. 7-24
 © 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The trademarks USG, CGC, AX, CLIMAPLUS, DONN, DX, DXW, PREMIER HI-LITE, ZXLA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

