

CGC MILLENNIA® HIGH-NRC

CLIMAPLUS™ PERFORMANCE

CGC Millennia High-NRC Panels/
CGC Donn Finline DXF
Suspension System


Flat White
050

FEATURES AND BENEFITS

- High NRC value without mechanical perforations.
- NRC of .75 meets the demanding sound control needs of open-plan offices.
- ClimaPlus™ 30-year lifetime system warranty against visible sag, mould and mildew.

APPLICATIONS

- Libraries
- Open plan offices
- Reception and lobby areas
- Legal
- Financial
- institutions

SUBSTRATE

- Wet-formed mineral fiber

FINE-TEXTURED PANEL











CGC MILLENNIA® HIGH-NRC CLIMAPLUS™ PERFORMANCE

CUSTOMER SERVICE
Ontario/Atlantic Canada : 800.387.2690
Quebec/Eastern Ontario : 800.361.1310
Western Canada : 800.242.4418
COMPANY WEBSITE
cgcinc.com

SEE LEED REPORT TOOL
for detailed sustainability
information, as well as the
MOST UP-TO-DATE
TECHNICAL INFORMATION,
all available at
cgcdesignstudio.com



UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ²	Colour	Grid Options	VOC Emissions	Anti-Mould & Mildew	Recycled Content ¹	Panel Cost
SLT 	2' x 2' x 3/4"	Class A	76201	.75 	30	.85 	White	A	Low		82.3% 	\$\$
FLB 	2' x 2' x 3/4"	Class A	76302	.75 	30	.85 	White	B, C, D, E	Low		82.3% 	\$\$

CGC MILLENNIA HIGH-NRC PANELS

LEGEND

Low Emissions (VOC)


Low-emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on the CHPS database for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com.


ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mould and mildew. Includes sag resistance performance.






High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per U.S. FTC guidelines.

 ≥ .70 NRC

 ≥ .85 LR

GRID PROFILE OPTIONS

A DX [®] /DXL™	B CENTRICITEE™ DXT™	C FINELINE® DXF™	D FINELINE 1/8 DXFF™	E IDENTITEE™ DXI™
				

PHYSICAL DATA/NOTES

Product literature
Data sheet: SC1851E

ASTM E1264 classification
Type III, Form 1, Pattern E & G

**ASTM E84 and CAN/ULC S102 surface
burning characteristics**
Class A

Flame spread: 25
Smoke developed: 50

Weight
1.06-1.09 lbs./sq. ft.

Thermal resistance
R-2.0

Maximum backloading
See Warranty for details.

Maintenance
Can be cleaned easily with a soft brush
or vacuum.

Proprietary technology
This product's unique combination of sag
resistance and sound performance results
from a proprietary technology.

Notes

- For details, see LEED report tool at cgcdesignstudio.com.
- LR values are shown as averages.
- Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial additive that inhibits and retards the growth of mould and mildew. For details, see Ceiling Systems Limited Warranty Commercial Applications (CSC2102) and ClimaPlus Ceilings Certification of Performance (SC2451).