

DESIGNER PATTERNS

ATTRACTIVE MEDIUM-TEXTURED PANELS

USG Alpine™ 1004

TO ORDER SAMPLES, GO TO USG.COM

USG Alpine™

USG Majestic™/USG Olympia™ Micro™

USG Moonscape™

USG Saville Row™


























FEATURES AND BENEFITS

- Good sound absorption.
- High light reflectance minimizes eyestrain and energy costs.
- Surface cleans easily.
- Easy installation.

SUBSTRATE

- Wet-formed mineral fiber

PRODUCT SPECIFICATIONS

Pattern	Item No.	Edge	Panel Size	Pcs./ Carton	Sq. Ft./ Carton	Ctns./ Pallet	Fire Rating	Sound Control		Technical Information							
								NRC	CAC	LR	R-Value	VOC	Mold, Mildew & Sag Resistance	Abuse Resistant	Recycled Content	USG Commercial Equivalent	
USG ALPINE™1,2																	
	1003		2'x4'x5/8"	8	64	18	Class A	0.50	35	0.86	1.85	Low			49%	—	
USG MAJESTIC™	1004		2'x2'x5/8"	16	64	16	Class A	0.50	35	0.86	1.4	Low			49%	—	
	5221		2'x2'x5/8"	16	64	16	Class A	0.50	35	0.86	1.4	Low		—	44%	USG Olympia™ Micro™ 4221	
USG MOONSCAPE™1,2	5411		2'x4'x5/8"	8	64	18	Class A	0.50	30	0.86	1.4	Low		—	44%	USG Olympia™ Micro™ 4411	
	R4800		2'x4'x5/8"	8	64	20	Class A	0.55	35	0.86	1.4	Low		—	44%	USG Pebbled™ 4800	
USG OLYMPIA™ MICRO™	R4805		2'x2'x5/8"	16	64	20	Class A	0.55	35	0.86	1.4	Low		—	44%	USG Pebbled™ 4805	
	4231		2'x2'x5/8"	16	64	20	Class A	0.50	35	0.86	1.4	Low		—	44%	USG Olympia™ Micro™ 4231	
USG SAVILLE ROW™	550		2'x2'x3/4"	12	48	20	Class A	0.55	35	0.87	1.7	Low	—	—	42%	USG Aspen™ 650	

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com

ClimaPlus™ Warranty Performance

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.



This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete list of all USG ceiling panels on biopreferred.gov website.



GREENGUARD Gold Certification offers stricter certification criteria, considers safety factors to account for sensitive individuals (such as children and the elderly), and ensures a product is acceptable for use in environments such as schools and healthcare facilities. It is referenced by both The Collaborative for High Performance Schools (CHPS) and the Leadership in Energy and Environmental Design (LEED) Building Rating System.

FOOTNOTES

ASTM E84 surface-burning characteristics

Class A
Flame Spread: 25 or less
Smoke Developed: 50 or less

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Notes

1. USG Alpine™ and USG Moonscape™ are manufactured at multiple locations resulting in slightly varying surface textures. To make sure that panel textures match an existing ceiling, ensure that panels are ordered to ship from the same manufacturing location.
2. USG Alpine™ and USG Moonscape™ products do not meet BioPreferred Initiatives.