

USG LEVELROCK® BRAND CSD™ PRIMER

DESCRIPTION

High-quality floor underlayment primer

- For use over corrugated galvanized steel decks
- Blue tint ensures uniform application
- Low odor
- Fast-drying
- Resists mold
- Enhances bond between substrate and underlayment

USG Levelrock™ Brand CSD™ Primer is manufactured and designed by USG to improve the adhesion to corrugated galvanized steel deck substrates. USG Levelrock CSD primer is installed by USG Levelrock® authorized applicators prior to installing USG Levelrock® CSD® Early Exposure™ and USG Levelrock® CSD® Early Exposure™ FR Floor Underlayment in all types of commercial, institutional and residential floor applications.

Fast-drying USG Levelrock CSD primer features a high-solids latex base, emits low odor and resists mold. It is available ready-mixed in 53-gallon drums.

LIMITATIONS

1. Do not use in exterior applications.
2. Do not apply at temperatures below 45 °F or above 120 °F.
3. Do not apply on excessively dusty or dirty subfloors.
4. Do not dilute.

APPLICATION

Read and follow all cautions and warnings on USG Levelrock CSD primer product labels. Refer to the Safety Data Sheet (SDS) on usg.com for additional information. The floor to be primed must be sound, clean, free of alkali and dry. Remove dirt, wax, polish, paint and all foreign material that would interfere with a good bond. A minimum building temperature of 45 °F must be maintained for USG Levelrock CSD primer during the drying period. Cooler temperatures and high humidity will prolong drying time.

Apply USG Levelrock CSD primer at full strength by pouring it onto the deck and spreading it out with a push broom at a rate of 300 sq. ft./gal. Do not thin. Primer may also be sprayed onto the deck, but it is imperative to achieve a continuous, uniform coating, especially on the top of the flutes. Allow a minimum of 3 hours for adequate drying to a maximum of 24 hours before pouring USG Levelrock CSD Early Exposure and USG Levelrock CSD Early Exposure FR floor underlayment. If the 24-hour period is exceeded, the area must be reprimed. The primer will take on a translucent quality when dry. Cooler weather and high humidity will lengthen primer drying time. Primer must be dry prior to the installation of USG Levelrock CSD Early Exposure floor underlayments.

CLEANUP

Clean tools with water before primer dries. Flush with large quantities of water. Dry primer can be cleaned with mineral spirits.

STORAGE

Protect from freezing, and do not store above 120 °F. If accidentally frozen, allow it to thaw at room temperature. Stir to a homogenous state before using. Do not use material that is coagulated or has excessive settlement that cannot be readily remixed. Do not use any primer that is of suspect quality. Do not over-stir or use a high-speed mixer, as excessive air entrainment may result.

SUBMITTAL APPROVALS

Job Name	
Contractor	Date

PRODUCT INFORMATION

See usg.com or pourlevelrock.com for the most up-to-date product information.

CAUTION

May cause an allergic skin reaction. Avoid breathing mist or vapor. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear protective gloves/protective clothing/eye protection. If on skin: Wash with plenty of water. If skin irritation or rash occurs, or if swallowed: Get medical attention. If eye contact occurs, flush thoroughly with water for 15 minutes. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Dispose of in accordance with local, state, and federal regulations. Keep containers closed when not in use. For more information call Product Safety: 800-507-8899 or see the SDS at usg.com.

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, CSD, EARLY EXPOSURE, LEVELROCK, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates.

NOTICE

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

800 USG.4YOU
800 (874.4968)
usg.com
pourlevelrock.com
usgdesignstudio.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG1728/rev. 6-15
© 2015 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

