

Warm up to Stronger Than Concrete™ RH floor underlayments

USG Levelrock® Brand Radiant Heat (RH) Floor Underlayments

- Can be used with USG Durock™ Brand Quik-Top™ White & Gray and USG Durock™ Proflo™ self-leveling underlayment for a finished floor effect
- Fast application, fast-setting allows for return of light trade traffic within hours
- Smooth, crack-resistant surface

USG Levelrock® Brand RH & Green · Commercial RH & Green and UltraArmor™ engineered cementitious and FR engineered cementitious underlayments

USG

IT'S YOUR WORLD. BUILD IT.™



The non-shrinking nature of USG Levelrock® Brand Radiant Heat (RH) floor underlayments lock hydronic tubes and electric cables in place, preventing noise and tube chafing, while the special formulations are designed to be used within the elevated operating temperature ranges associated with radiant heat floors.

PRODUCT PERFORMANCE

USG Levelrock RH floor underlayments are fast-applying engineered cementitious underlayments formulated specifically for electrical and hot water radiant heat interior floor installations. USG Levelrock RH and USG Levelrock® RH Green floor underlayments are ideal for use in residential and light-commercial construction, while USG Levelrock® Commercial RH and USG Levelrock® Commercial RH Green floor underlayments are designed for use in commercial construction. USG Levelrock® UltraArmor™ floor underlayment is a unique all-in-one floor underlayment and wear surface product suitable for new and renovation construction in residential and commercial applications.

USG Levelrock RH floor underlayments:

- Accept virtually all types of floor coverings including ceramic tile, carpeting and wood
- Apply at 1 ½ in. min. thicknesses
- Provide approximate compressive strengths of 2500 – 3500 psi (USG Levelrock RH & Green), 3500 – 4500 psi (USG Levelrock Commercial RH & Green) and 3500 – 5000 psi (USG Levelrock UltraArmor)
- Setting/drying time can be shortened with the use of USG Levelrock™ RH Accelerator

For more information on USG Levelrock RH floor underlayments, please contact your USG Levelrock/Alcorp Network representative at 817 329.1808.

PRODUCT INFORMATION

See usg.com or pourlevelrock.com for the most up-to-date product information.

TRADEMARKS

The trademarks USG, DUROCK, LEVELROCK, PROFLOW, QUIK-TOP, ULTRAARMOR, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates.

NOTICE

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

800 USG.4YOU (874.4968)
usg.com
pourlevelrock.com
usgdesignstudio.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661