



Date:  
Project:

Certification Number:  
Address:

To whom it may concern,

This is to certify the Securock® ExoAir® 430 Panel is used as part of a system of products which are compatible and can include Dymonic® 100, Spectrem® 1, ExoAir 230, Tremco® Epoxy Primer, ExoAir LEF, ExoAir Primer, Proglaze ETA Connections and Securock ExoAir Reinforcing Mesh. The Securock ExoAir 430 Panel meets or exceeds the following ASTM and other industry test standards:

### Panel Physical Properties

Membrane Adhesion to Panel, psi min.	ASTM C297	Pass
Flexural Strength	ASTM C473	
Bearing edge perpendicular to board length, lbf. min.		147
Bearing edge parallel to board length, lbf. min.		100
Water Absorption, % max.		10
Nail-Pull Resistance, lbf. min.		90
Weight, psf nominal		2.6
Thermal Resistance, R (°F ft <sup>2</sup> h/BTU)	ASTM C518	0.50
Nail Sealability	ASTM D1970, Section 7.9	Pass
Mold Resistance	ASTM D3273	10
Peel Adhesion, lbf./in. pli ≥1	ASTM D3330	Pass
Membrane Adhesion to Panel, 16 psi min.	ASTM D4541	Pass
Water Vapor Permeance, perms	ASTM E96	
Base Panel, Dry Cup		26
Composite, Wet Cup		8
Air Permeance, 0.004 cfm/ft <sup>2</sup> @ 1.57 lb./ft <sup>2</sup> max.	ASTM E2178	0.0001 cfm/ft <sup>2</sup>
Assembly Air Leakage, 0.04 cfm/ft <sup>2</sup> @ 1.57 lb./ft <sup>2</sup> max.	ASTM E2357	0.002 cfm/ft <sup>2</sup>
Assembly Water Penetration, 15 minutes @ 2.86 lb./ft <sup>2</sup>	ASTM E331	Pass
Bending Radius*, Dry		9'
Coefficient of Thermal Expansion, in./in./°F	ASTM E831	8.5x10 <sup>-6</sup>
Water Resistance, @22 in./5 hrs.	AATCC 127-08	Pass
R-Value R (h·°ft <sup>2</sup> ·F/Btu)		0.50
R-Value R (m <sup>2</sup> ·K/W)		0.088

\* Recommended fastener spacing is 6" o.c. when panels are bent.

### JOINT TREATMENT PHYSICAL PROPERTIES

Cyclic Movement	ASTM C719	
Dymonic 100		+/- 50%
Spectrem 1		+100 / -50%
Crack Bridging	ASTM C1305	
Dymonic 100		Pass
Spectrem 1		Pass
Elongation	ASTM D412	
Dymonic 100		800% Elongation; 350 PSI
Spectrem 1		1000% Elongation; 160 PSI

\* For joint movement capabilities, refer to ASTM C719

USG Corporation 550 West Adams St., Chicago, IL 60661, t 312.436.4000

usg.com

The trademarks USG, SECUROCK, the USG logo, and related marks are trademarks of USG Corporation or its affiliates. The trademarks Dymonic, ExoAir, Spectrem and Tremco are trademarks of Tremco Incorporated.

BE106/08-18  
© 2018 USG Corporation and Tremco Incorporated.



Test data is available upon request. Please feel free to contact the Technical Services group if you have any questions.

Regards,

Rep Name: