

# SHEETROCK™ Brand Metal Trim

## Application

**SHEETROCK Brand 200-A and 200 B Metal Trim, 1/2" and 5/8"** Apply gypsum panels, omitting fasteners at framing member where trim is to be installed. Leave a space 3/8" to 1/2" wide between edge of panel and face of jamb. Slip trim over edge of panel with wide knurled flange on room side and fasten trim and panel to framing using standard panel fasteners. Space fasteners 9" o.c. maximum. Finish with three coats of joint compound; use only two coats with SHEETROCK Brand lightweight compounds.

**SHEETROCK Brand 401 Metal Trim, 1/2", J-Stop, and SHEETROCK Brand 402 Metal Trim, 5/8", J-Stop** Apply trim to wall before gypsum panels go up by nailing through trim flange into framing. Space fasteners 9" o.c. Board is held firmly in place by short leg of trim. No additional edge fastening is necessary.

**SHEETROCK Brand 800 and 900 Corner Bead** For gypsum drywall panels or single-coat veneer finish on gypsum base, use SHEETROCK Brand 800 Corner Beads on all vertical and horizontal exterior corners. Fasten with 9/16" rosin-coated staples on both flanges along entire length of bead, or nails at maximum 9" spacing. Where two-coat veneer plaster will be applied, use SHEETROCK Brand 900 Corner Beads on all vertical and horizontal exterior corners of gypsum base.

**SHEETROCK Brand 801-A and 701-A, 701-B Metal Trim** For gypsum drywall panels or single-coat veneer finish on gypsum base, use SHEETROCK Brand 801-A and 801-B Metal Trim at window and door jambs, and at intersections where panels abut other materials. Fasten with 9/16" rosin-coated staples, or attach to framing or jamb with nails at maximum 9" spacing. Where two-coat veneer plaster will be applied, use SHEETROCK Brand 701-A and 701-B Metal Trim at window and door jambs, and at intersections where panels abut other materials on gypsum panels or base.

### Trademarks

The following trademarks used herein are owned by United States Gypsum Company or a related company: SHEETROCK.

### Note

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

### Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than their intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date it was or reasonably should have been discovered.

### SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

