



USG DUROCK™ BRAND PATCHES AND SKIM COATS

USG DUROCK™ SYSTEM SOLUTIONS

usgperformanceflooring.com

USG DUROCK™ BRAND PATCHES AND SKIM COATS

New construction, major renovation or minor repairs – USG has a solution for every flooring demand. USG Performance Flooring's superior products work seamlessly together to create the only floor you'll ever need.

PRODUCT	APPLICATION	PACKAGE	APPROXIMATE COVERAGE AT 1/8 IN. (3 MM)	THICKNESS RANGE ^(b)	WORKING TIME (MIN.)	INSTALL FLOORING (MIN.) ^(d)
PATCHES AND SKIM COATS						
USG Durock™ Advanced Skim Coat™ Floor Patch ^(a)	Interior concrete, gypsum and approved wood subfloors; most interior flooring, including ceramic and quarry tile, terrazzo, wood, metal and interior concrete; as well as properly prepared residues of cutback and other non-water-soluble adhesives on concrete and epoxy coatings	9 lb. (4.0 kg) bag	38 sq. ft. (3.5 m ²)	FE - 1/2 in. (13 mm); any thickness in small, well-defined areas	10 - 15 ^(d)	15 - 25
USG Durock™ EXG™ Concrete Repair Patch	Exterior concrete area repairs such as sidewalks, driveways, parking garages and pool decks; interior concrete floors prior to installation of high relative humidity (RH) durable floor coverings	50 lb. (22.7 kg) bag	40 sq. ft. (3.7 m ²)	FE - 12 in. ^(e) (305 mm)	15 - 25	45 - 60
USG Durock™ NE Floor Patch ^(a)	Interior concrete, gypsum and approved wood subfloors	25 lb. (11.3 kg) bag	39 sq. ft. (3.6 m ²)	FE - 1/2 in. (13 mm)	10 - 20	60 - 70
USG Durock™ Quik-Ramp™ Floor Patch	Interior concrete, gypsum and approved wood subfloors; terrazzo, ceramic and quarry tile; and other nonporous substrates	50 lb. (22.7 kg) bag	55 sq. ft. (5.1 m ²)	FE - 5 in. ^(c) (127 mm)	15 - 25	60 - 70
USG Durock™ Tuf-Skim™ Floor Patch ^(a)	UL Classified for use in fire-rated assemblies; interior gypsum-based underlayments, concrete and approved wood subfloors	25 lb. (11.3 kg) bag	48 sq. ft. (4.5 m ²)	FE - 1/2 in. (13 mm); any thickness in small, well-defined areas	10 - 25	30 - 60
USG Durock™ X Floor Patch ^(a)	Interior concrete, gypsum and approved wood subfloors	18 lb. (8.1 kg) bag	47 sq. ft. (4.4 m ²)	FE - 1/2 in. (13 mm)	10 - 15	35 - 45
USG Durock™ Crack Repair Compound	Ideal for repairing cracks and voids in concrete; may also be used over wood, fiberglass and asphalt	Carton with 1/2 gal. (US) (1.9 L) jug each of Part A and Part B	460 lf	1/8 in. (3 mm)	Up to 5 minutes	15 - 30

Notes

- a. May be used with USG Durock™ Matrix™ Bond Enhancer.
 b. FE = featheredge
 c. For thicknesses exceeding 2 in. (51 mm), aggregate is required.

- d. May be retempered multiple times without addition of water.
 e. For thicknesses exceeding 3 in. (76 mm), aggregate is required.
 f. Depending on thickness and drying conditions. See submittals for drying requirements when using specialty adhesives and for installation of wood floor coverings.

USG Durock™ Matrix Bond Enhancer is a liquid additive that improves flexibility and adhesion, as well as impact resistance and coverage rates. When mixed with these patching compounds, the material can be applied over most interior floor coverings, including ceramic and quarry tile, terrazzo, wood and interior concrete, as well as properly prepared residues of cutback and other non-water-soluble adhesives on concrete and epoxy coatings.

PRODUCT	MIX DESIGN	USG DUROCK™ MATRIX™ BOND ENHANCER	COVERAGE AT 1/32 IN. (.8 MM)
USG DUROCK™ MATRIX™ BOND ENHANCER - RATIOS			
USG Durock™ Advanced Skim Coat™ Floor Patch	9 lb. (4.0 kg) bag	2.5 qt. (2.3 L)	Up to 180 sq. ft. (16 m ²)
	5 parts by volume	2 parts by volume	
USG Durock™ NE Floor Patch	25 lb. (11.3 kg)	3.5 qt. (3.3 L)	Up to 150 sq. ft. (14 m ²)
	3 parts by volume	1 part by volume	
USG Durock™ Tuf-Skim™ Floor Patch	25 lb. (11.3 kg)	3.25 qt. (3.1 L)	Up to 260 sq. ft. (24.1 m ²)
	3 parts by volume	1 part by volume	
USG Durock™ X Floor Patch	18 lb. (8.1 kg) bag	3 qt. (2.8 L)	Up to 198 sq. ft. (18 m ²)
	3 parts by volume	1 part by volume	

For detailed instructions including application restrictions and how to prepare the subfloor, see the corresponding product submittal sheets and SDSs at usgperformanceflooring.com.

CB5037-USG-ENG/rev. 3-19

© 2019 USG Corporation and/or its affiliates.
 All rights reserved.
 Printed in the USA

Manufactured by or for
 United States Gypsum Company
 550 West Adams Street
 Chicago, IL 60661

800 USG.4YOU
 800 (874-4968)
usgperformanceflooring.com
usgperformanceflooring.com/repair
usg.com

PRODUCT INFORMATION

See usgperformanceflooring.com for the most up-to-date product information.

TRADEMARKS

The trademarks USG, ADVANCED SKIM COAT, DUROCK, EXG, MATRIX, QUIK-RAMP, TUF-SKIM, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates. UL is a registered trademark of UL LLC.

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall

be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

NOTE

The information in this document is subject to change without notice. USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document. Consult your USG Company sales office or representative for information.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.