

USG LEVELROCK™ BRAND

CRACK SUPPRESSION MAT

DESCRIPTION

Polymeric-reinforcement crack suppression mat

- Can be used over a variety of subfloors
- May contribute towards LEED® credits
- Installed by USG Levelrock® authorized applicators

EXTENDED WARRANTY

USG Levelrock™ Brand Crack Suppression Mat (CSM) is a 3/16 in. (5 mm)-thick random filament, non-geometrically-patterned mat used during the renovation of old buildings. Designed for interior use directly over concrete, plywood or OSB subfloors, USG Levelrock CSM is a Class A fire-rated product. It is 3/16 in. thick, 39.5 in. wide and features an adhesive strip on the flap.

An extended warranty may apply when using USG Levelrock® Crack Suppression Mat in a system application. Please contact USG for further details.

LIMITATIONS

1. Do not use in exterior applications.
2. Do not install where continuous exposure to moisture is a possibility.
3. Structure shall be designed so that deflection does not exceed L/240 from combined dead and live loads and L/360 from live loads. Certain floor coverings such as marble, limestone, travertine and wood may have more restrictive deflection limits. Consult the appropriate floor-covering manufacturer.
4. For wood subfloors, do not install on plywood/OSB subfloors lacking tongue and groove edges without back-blocking.

INSTALLATION

USG Levelrock Crack Suppression Mat (CSM) can be used over concrete, plywood or OSB subfloors. For plywood or OSB subfloors, the edges must be tongue and groove or the use of back blocking is required. The subfloor must be clean and free of construction debris and dirt. The building temperature should be maintained at a 50 °F (10 °F) minimum.

Protect USG Levelrock® underlayment floors poured over USG Levelrock Crack Suppression Mat from heavy trade traffic loads (i.e. loaded drywall carts, heavy tool cabinets, etc.) with plywood.

For further details on installation requirements, specifications and the most up-to-date product information, please visit usg.com.

PRODUCT DATA

USG Levelrock™ Brand Crack Suppression Mat	
Thickness (inches)	3/16 (0.187)
Width (inches)	39.5
Roll Length (feet)	100
Coverage Per Roll (ft²)	330
Weight (ounces/yd²)	10.5
Weight Per Roll (lbs)	24
Roll Diameter (inches)	18
Rolls Per Pallet	10

STORAGE

All material shall be delivered and stored on the job in their original unopened packaging. Do not expose material to sunlight. The material must be stored in an enclosed shelter providing protection from damage and exposure to the elements. Remove damaged or deteriorated material from the premises.

SUBMITTAL APPROVALS

Job Name	
Contractor	Date

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

LEED INFORMATION

For the most up-to-date information on LEED rating systems, project certification and the U.S. Green Building Council, please visit usgbc.org.

CAUTION

Dust may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. Remove contact lenses and continue rinsing. If on skin: Wash with plenty of water. If irritation persists, call physician. For more information call Product Safety: 1-800-507-8899 or see the SDS at usg.com

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, LEVELROCK, IT'S YOUR WORLD, BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates. LEED is a registered trademark of the U.S. Green Building Council.

NOTE

The information in this document is subject to change without notice. USG Corp. and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Consult your USG sales office or representative for information.

NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to the replacement of defective goods or a refund of the purchase price, at USG's option, and does not include costs of labor, floor-covering materials, or any other costs associated with material replacement. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.

800 USG.4YOU
800 (874.4968)
usg.com

Manufactured for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG1917-USA-ENG/rev. 11-20
© 2020 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

USG
IT'S YOUR WORLD. BUILD IT.®