

USG PEBBLED™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Pebbled™ Acoustical Panels
with ClimaPlus™ Performance/
USG Donn® Brand DX®
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Economical, medium-textured ceiling panel has upscale appearance.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

APPLICATIONS

- Schools
- Corridors
- General Offices
- Retail Stores

SUBSTRATE

- Wet-formed Mineral Fiber

Medium-Textured Panel

USG PEBBLED™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
 USG: usg.com or samplitt@usg.com
 CGC: contact Sales Representative

TECHNICAL SERVICES
 800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL
 usgdesignstudio.com
 cgcdesignstudio.com
 usg.ecomedes.com



PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS:
 UL/COM/GG
 UL 2818

30 YEAR LIMITED SYSTEM WARRANTY
 • No Visible Sag
 • Mold/Mildew Protection

UL Classified

Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹	Panel Cost
SQ 	2'x2'x5/8"	Class A	4801	0.55	35	0.86	White	A,B,C	Low		60%	\$\$
	2'x4'x5/8"	Class A	4800	0.55	35	0.86	White	A,B	Low		60%	\$\$
SLT 	2'x2'x5/8"	Class A	4805	0.55	35	0.86	White	D	Low		60%	\$\$
FLB 	2'x2'x5/8"	Class A	4867	0.55	35	0.86	White	E,F,G,H	Low		60%	\$\$

USG PEBBLED™ PANELS

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.ecomedes.com and at spot.ul.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C ⁴ USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Fineline* DXF™	G USG Fineline* 1/8 DXFF™	H USG Identitee* DXI™

PHYSICAL DATA/ FOOTNOTES

Product literature
 Data sheet: SC1836

ASTM E1264 classification
 ASTM E1264-22 Type III, Form 2, Pattern C & E
 ASTM E1264-23 Type A, Form A1.2, Pattern C & E

ASTM E84 and CAN/ULC S102 surface-burning characteristics
 Class A
 Flame spread: 25 or less
 Smoke developed: 50 or less

Weight
 0.83 lb./sq. ft.

Online tools
 usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com

Thermal resistance
 R-1.4

Maximum backloading
 See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

Maintenance
 Can be cleaned easily with a soft brush or vacuum.

Metric sizes available
 Contact sales for minimum quantities and lead times.

- Notes**
- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
 - LR values are shown as averages.
 - For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
 - Maximum 2'x2' with SQ edge panels.

Notice
 The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1836/rev. 7-24
 © 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, FINELINE, IDENTITEE, PEBBLED, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

