

Key Word Index

- A**
- abuse resistance, 2, 449
 - abuse-resistant panels, 8–10, 13
 - abuse-resistant systems, 227–228
 - accelerators, 249–250, 269
 - set times, 176
 - acoustical ceiling, 287–315
 - building codes and, 310
 - environmental considerations for, 303–304
 - fire safety, 304–310
 - installation, 303–304
 - lighting and reflectance, 300–302
 - requirements, 297–299
 - specialty panels, 293–297
 - standards for, 310–315
 - structural implications, 302–303
 - suspended ceiling products, 288–293
 - sustainability, 299
 - acoustical plaster finish, 60–61, 197–198
 - acoustical sealant, 34, 117
 - estimating, 103
 - additives, 249–250, 278
 - acrylic, 250
 - adhesives 45, 103, 113–115, 121, 150, 364
 - fastener spacing with, 115
 - lamination, 118–121
 - aggregated textured surfaces, painting, 208
 - aggregates, 198–199, 267–268
 - air barriers, 345
 - air ducts, 83
 - airless spray equipment, 186, 433
 - anchor inserts, 136
 - angle brackets, 285
 - angles, fastening, 75
 - AQUA-TOUGH underlayment, 17
 - AQUA-TOUGH panels, 7–8, 9, 183
 - AQUA-TOUGH sheathing, 14–15
 - arches, 142
 - area separation walls, 14, 28–30, 327–331
 - asbestos, 57
 - ASTM application standards, 499–501
-
- B**
- back-blocking application, 117–118
 - backerboard, 145–159
 - estimating, 150
 - banjo, 427
 - basecoat plaster, 242–244, 264–268
 - limitations, 243–244
 - base-layer erection, 122–123
 - bead
 - accessories, 22–26
 - cracking of, 371
 - filling, 178
 - metal, 24–25
 - bead applicator head, 429
 - Beadex, 22–24, 168
 - beam and column fire protection, 337–340
 - bending stress, 71
 - blister brush, 431
 - board
 - sag of, 371
 - stacking, 406–407
 - bolt channels, 136
 - bolts, toggle, 285
 - braced soffits, 142, 143
 - maximum dimensions, 142
 - bracing, 285
 - brackets, adjustable wall furring, 31, 33
 - breakaway clip, aluminum, 30
 - brick, 260
 - brocade texture pattern, 203
 - browning rod, 430

building codes, 451–452
for suspended acoustical ceilings, 310

building sciences, 441–466
fire resistance, 451–459
structures, 442–451

C

cabinet attachment, 137–138
CAD, 19, 74
cartridge preparation, 114–115
casing bead, 235, 267
caulking, 189–193, 283
guns, 424
cavity walls, components, 29
ceiling board, exterior 8–10, 127–130
ceiling panels, 157–158, 290–299
abuse-resistant, 8
sag-resistant, 8
ceilings, 86, 115, 121, 132, 134, 186,
255, 258
acoustical, 287–315
curved, 79–80
flat, 79
insulation, 74
redecorating, 206–208
resilient channels, 92–93
resurfacing, 228
safety tips, 411–413
sag, 375
spray textured, 74–75, 86
suspended, 17–22, 78–86
cement board, 146–149
construction problems and remedies,
388–389
substrate, 218
certification, of products, 360
chalk line, 418
channel runners, fastening, 75
chase wall framing, 78
circle cutter, 422
circular holes, 109
cladding, 101–143
planning procedures, 102–105
Clean Room *CLIMAPLUS* vinyl panels, 18

CLIMAPLUS, 17–18
coating spray equipment, 433
cold-rolled channels, 31, 32, 239, 240
column, 132, 133, 134
commercial adhesives, 45
COMPASSO, 22, 294
concrete block, 222, 224, 260
concrete finishing compounds, 51
concrete, applying compound over,
187–189
construction joints, 343–344
control joints, 83, 86, 128, 151, 171–174,
191, 214–217, 237–239, 263–264,
282
applying sealant to, 191
fire-rated, 173–174, 215–217
maximum spacing, 173, 216, 238
corner application head, 429
corner bead, 24, 167–170, 212–213,
235, 236
corner finishing box, 429
corner roller, 428
cornerite, 236–237
corners, finishing inside, 179
corridors, 79
countertops, panel application, 157
COVER COAT, 51, 187–188
cracking, 67, 72, 132, 133, 370–371,
386–387, 393–395
of conventional plaster, 393–395
of drywall, 370–371
of joints, 386–387
crack resistance, 52
of SHEETROCK panels, 3
cross bracing, 78

- cross-furring members, maximum spacing, 259
 - crow's foot texture pattern, 203
 - curved ceilings, 79–80
-
- D**
- damage, of drywall, 371–372
 - darby, 430
 - decorating tips, 185
 - decorative interior finish system, 228–230
 - defects, in drywall, 370–384
 - deflection, 26, 70–71, 354
 - delamination
 - of basecoat or mortar, 389
 - of drywall paper, 72
 - of finish coat of veneer, 386
 - of tile and thin brick, 389
 - delivery, or material, 361
 - design
 - area separation fire-walls, 327–331
 - beam and column fire protection, 337–340
 - considerations, 150–151
 - fire tests, 319–326
 - floor/ceiling assemblies, 336–337
 - head-of-wall construction joints, 343–344
 - penetration fire-stop systems, 340–343
 - sound control systems, 326–327
 - steel stud partitions, 326
 - structural criteria, 318–319
 - of systems, 318–316
 - technical data, 318
 - USG shaft walls, 331–336
 - vapor control, 344–346
 - wood stud partitions, 326
 - diamond mesh lath, 233–234
 - DIAMOND plasters, 220, 223–225
 - DIAMOND veneer basecoat, 55–56, 224
 - coverage, 56
 - DIAMOND veneer finish, 56, 223–227, 246–247, 277
 - coverage, 56
 - radiant heat system, 225–227
 - diaphragm pump, 436
 - discoloration, of drywall, 371, 383
 - dolly, for gypsum board, 438
 - DONN grid systems, 289–290
 - door frames, 94–99, 191, 255, 281–282
 - double nailing, 134
 - drills, 424, 425
 - bits, 39
 - drop cloths, 439
 - dry sanding, 179
 - drying time, joint compound, 183–184
 - drying, plaster, 12
 - drywall and plaster ceiling suspension systems, 78–86
 - drywall construction, joint treatment for, 174–185
 - drywall finishing, 105–106, 161–208
 - drywall hammer, 423
 - drywall suspension system, 19–22
 - curved surfaces, 20–21
 - fascia applications, 21–22
 - drywall, inspection, 363–365
 - drywall, problems and remedies, 370–384
 - Dur-A-Bead, 24, 169
 - durability, 349
 - Durabond, 45, 49–50, 51
 - DUROCK cement board, 3, 7, 13, 146–148, 151–159, 227–228
 - accessories, 149–150
 - DUROCK underlayment, 17
 - curved surfaces, 20–21, 138–141
 - advantages, 21
 - components, 21
 - cutting gypsum panels, 108–109

- E**
- Easy Sand, 45, 49–50, 51
 - edges, of gypsum panels, 5, 10, 14, 132
 - efflorescence, 151
 - electric router, 422
 - electrical fixtures, 135
 - caulking, 283
 - embedding tape, 177
 - end joints, 179
 - energy, measuring building, 473
 - environmental conditions, 105, 150, 253–254
 - environmental considerations, for acoustical ceilings, 303–304
 - environmental management, 470–471
 - equipment, 417–440
 - coating, 433
 - hand-texture, 432–433
 - hoses, guns and nozzles, 437–438
 - manufacturers, 440
 - mechanical taping, 428–429
 - mixing, 425–426
 - spray texture, 433–436
 - equipment
 - care of, 174–175
 - selection of, 359–360
 - estimating, 103–104, 150, 252–253
 - for backerboard, 150
 - for gypsum board, 103
 - for gypsum panel joint treatment, 104
 - for plaster, 252–253
 - evaluation, of products, 470
 - expanded flange corner bead, 24
 - expansion joints, 86
 - expansion plugs, 284
 - exterior wall, 132, 133
 - eye protection, 408
-
- F**
- face paper, puncturing of, 377–378
 - face-layer erection, 123
 - fascia, 21–22, 80
 - fastener heads, spotting, 177–178
 - fasteners, 36–44, 72, 111–112, 115, 261–262, 285, 363–364, 370, 377–379
 - failure, 72
 - imperfections, 370
 - spacing, 111–112, 115
 - problems and remedies, 377–379
 - feather edge, 430
 - fiberglass drywall tape, 53
 - FIBEROCK, 9, 10, 13, 148–149, 151–159, 228
 - FIBEROCK AQUA-TOUGH, 3, 7–8, 9, 14–15, 17, 126, 183
 - underlayment, 17
 - tile backerboard, 3, 8
 - sheathing, 14–15, 126
 - fiber-reinforced gypsum panels, 148–149
 - limitations, 149
 - physical properties, 149
 - fill coat, 178, 225–226
 - finish coat, 179, 226, 247–248
 - finish limes, 245–246, 275–276
 - finish plasters, 244, 247, 270–277
 - finishes, prepared, 246–247, 276–277
 - finishing level, definitions, 163–165
 - finishing, problems and remedies, 383–384
 - FIRECODE, 7, 13, 321, 334–335
 - compound, 34–36
 - Core, 5, 8
 - firestop sealant, 36
 - fire endurance tests, 452–453
 - fire-rated control joints, 173–174
 - fire requirements, 74

- fire resistance, 10, 11, 14, 127, 232, 233, 349, 451–459
- fire safety, of acoustical ceilings, 304–310
- fire-stop systems, 34–36, 340–343
- fire walls, 28–30
- First Coat, 186–187
- fissured finish, 226
- fixtures, 128, 135–138
 - attachment, 135, 152–153, 283–285
 - electrical, 283
 - load data, 137, 493
- flat drywall ceilings, 19
- flat finisher box, 429
- float plaster finishes, 271
- floating interior angle application, 134
- floats, 431
- floor scrapers, 439
- floor surfaces, repairing, 205
- floor underlayment, 17
- floor/ceiling assemblies, 336–337
- flue gas desulfurization, 17, 475
- foil-back gypsum panels, 6
- for underlayment, 150
- frame spacing, 71, 73–75, 258–259
- framing, 26–28, 30–33, 69–99, 151–152, 254, 239–241, 361–362, 375–377, 418–421
 - accessories, 30–33
 - chase wall, 78
 - corrections, 72
 - door and window openings, 94–99
 - general requirements, 70–71
 - inspection of, 361–362
 - limiting heights, 76
 - partition corners, 93
 - problems and remedies, 375–377
 - steel, 75–77
 - suspended ceilings, 81–86
 - tools for, 418–421
 - wood, 71–75
- fungicides, 411
- fungus, 410–411
- furred ceilings, 258
- furred framing board application, 124
- furring
 - accessories, 30–33
 - channels, 26, 81–83, 88
 - free-standing, 89
 - wall, 86–91, 255–256

-
- G**
- gauging plasters, 244–245, 273–275
 - technical data, 275
 - glass mat sheathing, 15–16
 - glitter gun, 432
 - Grand Prize finish lime, 246, 276
 - grid systems, 288–290
 - grillage, suspended ceiling, 83–86
 - grillage, suspending, 362
 - grounds, 212, 266–267
 - grouting, door frames, 281
 - gypsum base, 11, 13, 224, 243
 - gypsum board
 - bending radii, 139
 - ceilings, 115, 130
 - erection, 122
 - estimating, 103
 - nails, 43–44
 - paint levels over, 165–166
 - screws, 36–43, 494
 - gypsum ceiling panel application, interior, 126–127
 - gypsum drywall, application, 107–125
 - gypsum fiber base, 218–219
 - gypsum finishing, levels of, 162–163, 165
 - gypsum lath, 262
 - gypsum liner, 14–16
 - gypsum panels, 2–8, 9, 81, 104, 193,

- 148–149
 fiber-reinforced, 148–149
 foil-back, 6
 mold-resistant, 7–8
 sag, 4
-
- H**
- hand mixer, 425
 - hand pump, 428
 - hand texture effects, 203–204
 - hand tool application, of joint compound, 177–180
 - handbook, using the, xiii–xiv
 - hanger wire, 31, 33, 81, 240
 - hangers, 259
 - hawk, 429
 - head-of-wall construction joints, 343–344
 - heavy door framing, 95–96
 - health hazards, of products, 409–411
 - heating, 270
 - holes, repairing, 204–205
 - hopper gun, 433
 - hopper, convertible, 427
 - horizontal bracing, continuous, 136
 - hoses, guns and nozzles, 437–438
 - humidity, 349, 352–353
 - HVAC equipment, 311–312
 - HYDROCAL FGR 95 gypsum cement, 248
 - HYDROCAL white gypsum cement, 248
 - hygrometric coefficients of expansion, 504
 - hygrometric expansion, 355
-
- I**
- impact testing, 450
 - IMPERIAL gypsum base, 12–13
 - IMPERIAL plasters, 220, 221–222
 - IMPERIAL tape, 53–54
 - IMPERIAL veneer basecoat, 55 (two-coat), 221–222
 - IMPERIAL veneer finish, 55, 246–247, 277 (one-coat), 221
 - IMPERIAL, FIRECODE, 12–13
 - indoor air quality, 474
 - indoor environmental quality, 474
 - inspection, 351, 361–367
 - insulation, 33–34, 71, 74, 261
 - interior patch & repair, 67–68
 - interior texture finishes, 57
 - IVORY finish lime, 246, 275
-
- J**
- jamb, 89, 95, 96
 - job conditions, for plaster, 253–254
 - job preparation, 150–151
 - job, planning, 102–103
 - joint compounds, 45, 46–51, 60, 62, 119, 175–176, 183–184, 188–189, 200, 438
 - drying time, 183–184
 - ready-mixed, 45, 62, 200
 - selection, 50–51
 - set times, 176
 - setting-type, 181–183, 188–189
 - spreaders, 438
 - joint tape, 52–53
 - joint treatments, 158, 174–185, 211, 217–219, 364–365
 - inspection of, 364–365

- joints
 cracking of, 370, 386–387
 end, 179
 prefilling, 177
 problems and remedies, 379–383
 joists, wood, 116
-
- K** Keenes cement lime finish, application, 274
 kick lifter, 423
-
- L** ladders, 413
 lamination, strip, 120
 laser alignment, 418
 lather's hatchet, 423
 lather's nippers, 420
 lay-in tiles, 17–18, 130
 leaching, 151
 LEVELROCK underlayment, 17
 LEVELROCK, 485–486
 light orange peel texture pattern, 201
 light reflectance, 300–302, 350
 lighting fixture, 84
 protection, 85–86
 lighting, 300–302
 liner product, specifications, 16
 liquid contact adhesive application, 121
 loader pump, 425
 loads, supporting, 70
 lumber, shrinkage, 357–358
-
- M** magnetic spirit level, 418
 main runner, maximum spacing, 259
 maintenance, 350
 manufactured housing, joint compounds for, 50
 masonry, 124–125
 walls, 260
 material handling, 403–415
 material selection, 348–349
 measurements, 107–108
 mechanical tool application of joint compound, 180–181
 metal angles, 30, 32
 metal beads, 24–25
 paper-faced, 22–24, 178
 metal channel, ROCKLATH, 257–258
 metal furring channel, 31, 33, 82, 239–240
 metal furring members, limiting span, 82
 metal lath, 15, 233–235, 259, 260, 261, 262
 frame spacing, 259
 metal snips, 420
 metal trim, 25–26, 170–171, 213–214
 metric terms and equivalents, 495
 mildew, 206, 410–411
 mildewcides, 411
 mineral wool blanket installation, 130–131
 mineral wool, crushed, 131
 mixers, 426
 mixing paddles, 425
 mixing, 384, 389–390
 moisture, 7–8, 9, 151, 349, 353
 moisture-resistant sheathing, 15–16
 mold, 7–8, 9, 17, 372–373, 410–411

- and drywall, 372–373
 - resistance, 7–8, 9, 17
 - MOLD TOUGH, 7–8, 14
 - mold-resistant gypsum panels, 7–8
 - mold-resistant sheathing, 15–16
 - monolithic concrete, 222–223, 224, 226–227, 260
 - moulding plaster, 248
-
- N**
- nailing, 105, 110–111, 112, 120, 261
 - nail pops, 37, 43, 112
 - nails, 43–44, 103, 150, 378
 - selector guide for, 44
 - problems and remedies, 378
-
- O**
- openings
 - applying sealant to, 191
 - caulking, 283
 - orange peel texture pattern, 202
 - ornamental plasters, 248–249, 278
-
- P**
- pail extruder, 425
 - paint finish, recommended levels over gypsum, 165–166
 - painting veneer plaster, 225
 - paints, texture, 197, 200–201
 - pallets, 408
 - panel lift, 423
 - panel preparation, curved, 140
 - panel products
 - handling of, 405–407
 - loosening of, 370
 - problems and remedies, 372–375
 - panels, fabrication, 153
 - application, 154–158
 - paper-back lath, 234
 - partition, 132, 133
 - partition corners, framing, 93
 - partition layout, 75
 - partition perimeters, 191, 283
 - movement, in structures, 353–358
 - cracking, 356
 - hygrometric expansion, 355
 - relief joints, 355
 - seismic forces, 354
 - slab deflection, 354
 - thermal expansion, 354–355
 - wind, 354
 - mud pan, 427
 - nested channels, 136
 - noise reduction coefficient, 298
 - noise, structurally generated, 356
 - nozzle cuts, 114
 - orange peel texture pattern, 202
 - ornamental plasters, 248–249, 278
 - partitions, resilient channels, 92
 - party walls, 28–30
 - patching, 53, 204–205
 - penetration fire-stop systems, 340–343
 - performance requirements, 349–351
 - perimeter isolation, 131–134
 - peristaltic pump, 434–435
 - perlite, 198
 - permeance, 503
 - picture hooks, 284
 - pigmented finish plaster, 228–230
 - piston pumps, 435
 - plaster base, 107–125, 232–235, 258, 260–261, 365
 - plaster casting, 486
 - plaster finish, 248, 272–273, 279–280
 - plaster, 231–250, 251–285
 - accelerators, 249–250
 - bonder, 13, 250

- compatibility, 265
- drying conditions, 12, 211, 254
- formulation, 241
- ornamental, 278
- replastering old, 280–281
- retarders, 249
- plaster, conventional
 - application, 367
 - cleanup, 367
 - construction, 392–401
 - inspection of, 365–367
 - job conditions, 366
 - problems and remedies, 392–402
- plastering, two- and three-coat, 266
- pliers, 420
- plugs, expansion, 284
- pop rivet tool, 421
- Portland cement, 13, 15, 244
- powder fastening tools, 412
- powder texture, 57–60, 194–197
- power fastener driver, 419
- preventive measures, 369–402
- primers, 57
- priming, 185–187
- pumps, 434–436
- PVA-based primers, 225

Q quality, of products, 360

-
- R**
- radiant heat ceiling, 132, 133
 - radiant heat plaster system, 225–227
 - rasp, 422
 - ready-mixed texture, 61–66, 198–200, 200–201
 - recaptured gypsum, 17, 475
 - recycled content, 7, 9, 14, 16, 17
 - recycling, 475
 - RED TOP finish, 247
 - RED TOP finish plaster, 277
 - RED TOP finish lime, 276
 - RED TOP gauging plasters, 242, 244, 273
 - RED TOP Keenes cement, 245, 272
 - RED TOP wood fiber plaster, 242
 - reinforcing tapes, 52–54
 - application, 54
 - relief joints, 355
 - repairing, interior, 204–205
 - replastering, 280–281
 - resilient board application, 121–122
 - resilient channels, 26, 31, 32, 74, 77–78, 117
 - framing, steel, 77–78
 - resilient flooring, 158–159
 - resilient framing, wood, 91–93
 - resurfacing, 205–206
 - retarders, 249, 268–269
 - REVIT, 19, 74
 - riblath, 234
 - rigid foam insulation, 261
 - ROCKLATH, 262
 - base furring, 256–258, 260
 - plaster base, 258, 260
 - roller, corner, 428
 - rollers and pans, 427, 432
 - roof board, 16
 - rotor-stator pump, 434
 - runners, steel, 27–28

- S**
- safety, 403–415
 - sag, 4, 8, 74, 75, 371, 375
 - sampling, 360
 - sand float plaster finishes, 271, 274
 - sanders, 427–428
 - sanding, 179–180
 - saws, 419, 420, 421
 - scaffolding, 412–413, 439
 - scarifier, 431
 - screw anchors, 136
 - screw gun, 423
 - screws, 36–44, 103, 109–110, 120, 149, 241, 378, 494
 - DUROCK brand, 149
 - selector guide for, 38–40
 - specifications, 41
 - usage, 494
 - problems and remedies, 378
 - scrub brush, 431
 - sealant, 135, 189–193
 - SECUROCK glass mat sheathing, 15–16, 125–126
 - SECUROCK roof board, 16
 - seismic forces, 354, 448
 - setting time, 385
 - setting-type joint compound, application, 181–183
 - shadowing, 384
 - shaft walls, 14, 28–30
 - shear, 71
 - sheathing, 14–16
 - AQUA-TOUGH, 14–15
 - glass mat, 15–16
 - gypsum, 14
 - limitations, 15
 - specifications, 16
 - SHEETROCK acoustical sealant, 34, 189–193
 - SHEETROCK Beadex, 22–24
 - SHEETROCK ceiling spray texture, 57–58
 - ceiling spray texture, (QT), 194–195
 - SHEETROCK drywall repair clips, 68
 - SHEETROCK exterior ceiling board surfaces, 182–183
 - SHEETROCK fiberglass drywall tape, 53
 - SHEETROCK FIBEROCK AQUA-TOUGH panels, 183
 - SHEETROCK First Coat, 57, 186–187
 - SHEETROCK flexible metal corner tape, 168
 - SHEETROCK floor/patch leveler, 67
 - SHEETROCK gypsum liner panels, 14
 - SHEETROCK gypsum sheathing, 14, 125–126
 - SHEETROCK joint tape, 52–53
 - SHEETROCK lay-in ceiling tile, 17–18
 - SHEETROCK MOLD TOUGH, 7–8
 - SHEETROCK panels, 2–6, 8
 - SHEETROCK paper-faced metal corner bead, 167
 - SHEETROCK patching compound, 68
 - SHEETROCK patching plaster, 68
 - SHEETROCK plaster of Paris, 67
 - SHEETROCK powder joint compounds, 48–49, 60
 - SHEETROCK ready-mixed joint compound, 45, 62, 200
 - SHEETROCK ready-mixed wall and ceiling spray texture, 199
 - SHEETROCK ready-mixed wall and ceiling texture, 198–199
 - SHEETROCK setting-type joint compounds, 45, 47, 51, 119–120, 188–189
 - SHEETROCK spackling powder, 67
 - SHEETROCK texture 12, 196–197
 - SHEETROCK wall and ceiling spray texture, 58, 59

- sand finish texture 12, 59
 - unaggregated, 195
- SHEETROCK wall and ceiling texture (multi-purpose), 196
- SHEETROCK wall and ceiling texture (TUF-TEX), 195–196
- SHEETROCK wall and ceiling texture, 61–62, 200–201
 - sand-finish paint, 61
 - ripple-finish paint, 61
 - Texolite paint, 62
- SHEETROCK wallcovering primer, 57
- SHEETROCK, exterior gypsum ceiling board, 8
- SHEETROCK, sag-resistant panels, 8
- shrinkage, 72, 112
- sidewalls, 121, 134
- skim coating, 184
- skip-trowel texture pattern, 202
- slicker, 430
- snow loads, 16
- SNOWDRIFT finish lime, 246, 275
- soffits, 8, 80, 142–143, 152
- solid wall components, 29–30
- sound-absorbing plaster finish, 60–61, 248, 279–280
- sound attenuation, lay-in ceiling tiles, 18
- sound control, 3, 10, 20, 33–34, 326–327, 349
- sound insulation, mineral wool, 131
- sound-rated texture finish, 197–198
- sound-resistance, of plaster base, 232
- spatter texture pattern, 201
- specifications standards, 497
- spray gun, airless, 186
- spray machines, 433
- spray shield, 438
- spray texture equipment, 433–436
- spray texture finish, 74–75, 222, 271
- spring clamps, 420
- standards, of sustainability, 477–478
- staplers, 424
- staples, 110, 150
- steel frame, 122, 123–124
- steel framing, 26, 75–78, 94–95, 127, 377
- steel runners, 239, 240
- steel studs, 239, 240, 262
 - furring, 83
 - partitions, 326
 - ROCKLATH, 256–257
- steel tape rule, 421
- steel, typical thickness, 27
- steel-framed assemblies, 218
- stilts, 439
- stipple texture pattern, 202
- storage, 351–352, 361, 407
- string line, 418
- strip lamination, 120
- striplath, 236–237
- STRUCTO-BASE gypsum plaster, 242
- STRUCTO-GAUGE gauging plasters, 245, 274
- STRUCTO-LITE gypsum plaster, 243
- structural assemblies, specifications, 241
- structural ceiling, 132, 133
- structural strength, 349
- stucco brush, 432
- stucco, 15
- studless metal lath partitions, 282
- stud-metal lath partitions, 282
- studs, 27–28, 76–77, 116
 - steel, 27–28
 - wood, 116
- sun fading, of gypsum base, 386

sunlight, 353
 surface preparation, 185–186, 217–219
 surface-mounted panels, 130
 suspended ceiling, 17–22, 81–86, 130,
 288–293

T

tack claw, 422
 tape holder, 427
 tape, embedding, 177
 tape, tile backer, DUROCK, 150
 taper, 428
 taping knives, 426
 temperature, 349, 352
 testing
 abuse-resistant, 449–451
 of products, 477–478
 texture additives, 197
 texture brush, 432
 texture finish, 187, 193–194, 207, 226,
 389–392
 powder, 194–197
 ready-mixed, 198–200
 sound-rated, 197–198
 texture paints, 200–201
 texture patterns, creating, 201–204
 texture selector, 63–66
 thermal coefficients, linear expansion, 504
 thermal expansion, 354–355
 thermal resistance coefficients, 505
 tie wire, 31, 33, 240
 tile backer tape, DUROCK, 150
 grillage, 83–86
 suspended framing, 258
 sustainability, 468–479
 of acoustical ceiling components, 299
 swirl finish texture pattern, 203

tile backerboard, 8
 tile floors, panel application, 154
 tile, clay, 260
 toggle bolt, 136, 285
 tolerances, 493
 tools, 417–440
 finishing, 426–428
 hand, 177–180
 hand-texture, 432–433
 mechanical, 180–181
 mechanical taping, 428–429
 plaster, 429–431
 safety, 411–143
 trademarks, xii
 travertine texture pattern, 203
 trestle horse, 438
 trim
 accessories, 22–26, 125, 167–174,
 212–217, 235–239
 metal, 25–26
 paper-faced, 22–24, 178
 trowel plaster finishes, 270
 trowels, 429–430
 T-square, 421
 TUR-TEX, 58–59, 195–196

U

U.S. Environmental Protection Agency
 (EPA), 414
 UL designations, 502
 ULTRACODE Core panels, 6
 underlayment, floor, 17, 150
 universal spray machines, 433
 USG acoustical plaster finish, 279–280
 USG Acri-Add, 250
 USG high strength gypsum accelerator,
 249–250

- USG high-strength retarder, 249
- USG manufacturing plants, 3, 506–507
- USG plaster accelerator—alum catalyst, 250, 269–270
- USG plaster bonder, 13, 250
- USG retarder for lime-containing products, 249
- USG shaft walls, 331–336
- USG standard-strength gypsum plaster accelerator, 249
- USG standard-strength retarder, 249
- USG, 481–486
 - building materials, 483–484
 - new products, 484

-
- V**
- vapor control, 344–346, 351
 - vapor retarders, 345
 - vault ceilings, 19
 - veneer finish construction, problems and remedies, 384–388
 - veneer plaster bases, 10–13, 104, 105–106
 - veneer plaster compatibility selector, 219
 - veneer plaster finishes, 54–56, 210–212, 219–225
 - advantages, 54–55
 - abuse-resistant, 54
 - veneer plaster systems, finishing, 209–230
 - veneer plaster, 210, 227–228
 - painting, 225
 - ventilation, 127–128, 270, 353
 - very high impact (VHI) panels, 10, 13
 - vinyl panels, 18
 - volatile organic compounds (VOCs), 473

-
- W**
- wall anchors, hollow, 136
 - wall and ceiling texture, 198–199
 - paint, 200–201
 - wall furring, 86–91, 240, 255–258
 - wallboard, handling of, 405–407
 - walls
 - applying First Coat on, 186
 - fastener spacing, 115
 - frame spacing, 255
 - panel application, 155–156
 - resurfacing, 228
 - warnings
 - drowning, 408
 - plaster burn, 408–409
 - water damage, of drywall, 371, 372
 - water level, 418
 - water sprayers, 431
 - waterproofing compounds, bituminous, 260
 - weather, effect on finish lime, 275
 - weather-resistant ceiling board, 127
 - wet sanding, 180
 - white silica sand, 198
 - wind uplift, 16
 - wind, 354
 - window frame, reinforcing, 255
 - window framing, 94–99
 - metal, 98–99
 - wipedown blade, 432
 - wood frame application, gypsum board, 115–117
 - wood framing, 71–75, 91–94, 127, 262
 - resilient, 91–93

wood furring erection, 91
wood strip, ROCKLATH 256
wood stud partitions, 326

wood-framed assemblies, 217
workmanship, 358–359

Z z-furring channel, 31, 32, 87, 89–91, 240

Alphabetical Index to Tables

- A** Application Guide—Setting-Type Joint Compounds, 181
ASTM Application Standards, 499
-
- B** Basecoat Plaster (Over Metal Lath), 265
Basecoat Plasters for Conventional Plaster Systems, 265
Braced Soffit Design Maximum Dimensions, 143
-
- C** Ceiling Panel Types and Manufacturing Processes, 291
Checklist for Drywall Problems, 371
Condensation in Interior Spaces, 466
Conditions for Hose Stream Test, 457
Coverage and Technical Data—Gypsum Basecoat Plasters, 243
Coverage—Adhesives for Lamination, 103
Coverage—DIAMOND Brand Basecoat, 56
Coverage—DIAMOND Veneer Finish, 56
Coverage—Finish Plasters, 247
Coverage—FIRECODE Compound, 36
Coverage—IMPERIAL Brand Basecoat and Finishes, 55
Coverage—Laminating Adhesives, 45
Coverage—SHEETROCK Brand Acoustical Sealant, 34
Current USG Building Systems and Component Products, 483
-
- D** Drywall Finishing Levels & Methods, 165
DUROCK Brand Cement Board, 148
-
- F** FIBEROCK Tile Backerboard Typical Physical Properties, 149
Finish Plasters for Conventional Plaster Systems, 271
Fire Rated Ceilings, 307
Fixture Attachment Load Table, 493
Fixture Attachment Load Data—Drywall and Veneer Plaster Construction, 137
Frame and Fastener Spacing—ROCKLATH Plaster Base, 258
Frame Spacing—Gypsum Base (Ceilings & Sidewalls), 255
Frame Spacing—Textured Gypsum Panel Ceilings, 193
-
- G** Gauging Plaster—Technical Data, 275
Grid System Types and Profiles, 289
Gypsum Board Screw Usage, 494

-
- H** Hygrometric Coefficients of Expansion (Unrestrained), 504
-
- I** Interior Framing Limiting Heights, 76
-
- L** Limitations, FIBEROCK, 149
Limiting Span—Metal Furring Members, 82
-
- M** Maximum Aggregate Quantity—Gypsum Plasters, 268
Maximum Fastener Spacing—Constructions Using Drywall, Gypsum Base and Similar Products, 111–112
Maximum Frame Spacing—Drywall Construction, 73
Maximum Frame Spacing—Metal Lath, 259
Maximum Frame Spacing—Veneer Plaster Construction, 74
Maximum Spacing—Control Joints, 173, 216
Maximum Spacing—Cross-Furring Members, 259
Maximum Spacing—Main Runner—Carrying Channels, 259
Maximum Spacing—SHEETROCK Brand Control Joints for Interior Plaster Assemblies, 238
Metric Terms & Equivalents, 495
Minimum Bending Radii of Dry Gypsum Board, 139
Minimum Bending Radii of Wetted Gypsum Board, 140
Minimum Radii of SHEETROCK Brand ¼" Flexible Gypsum Panels, 139
-
- O** Ornamental Plasters—Approximate Yield, 249
-
- P** Performance Classification Table, 451
Permeance—USG Products, 503
Plaster Product Compatibility Selector, 265
Products/UL Designations, 502
-
- S** Screw Applications, 42–43
Selector Guide for Gypsum Board Nails, 44
Selector Guide for Screws, 38–40
Set Times: USG High Strength Gypsum Accelerator To Setting-Type Joint Compounds, 176
Sizes and Packaging, FIBEROCK, 148
Sound Control Guidelines for Air Handling Systems, 312

Specifications Standards, 497
Specifications—Area Specification Wall & Shaft Wall Components, 30
Specifications—Gypsum Bases, 13
Specifications—Gypsum Panel Products, 9
Specifications—Liner and Sheathing Products, 16
Specifications—Screws, 41
Specifications—SHEETROCK Brand Joint Compounds, 51
Specifications—SHEETROCK Brand Lay-In Ceiling Tile, 18
Specifications—Structural Accessories, 241
Specifications—Typical Plaster Trim Accessories, 239
Support Area—Hangers, 259
Surface Burning Characteristics, 458

T Texture/Compound Selector, 63–66
Thermal and Hygrometric Expansion Characteristics, 445
Thermal Coefficients of Linear Expansion of Common Building Materials, 504
Thermal Resistance Coefficients of Building & Insulating Materials, 505
Thickness—Area Separation, Shaft Wall and Furring Components, 29
Typical Steel Thickness—Steel Studs and Runners, 27

U USG Ceiling Panels and Acoustical Ratings, 298
USG Ceiling Panels—Light Reflectance Ratings, 301

V Veneer Plaster Product Compatibility Selector, 219

Contact Information

To contact your local USG sales representative, visit usg.com and select "Contact USG." For product information, visit usg.com and select "Products."

Additional Copies

For additional copies of *The Gypsum Construction Handbook*, Sixth Edition, visit rsmeans.com or call (800) 334-3509.