

Minimize downtime and apply  
floor coverings within 15 hours



# Levelrock® Quik-Top™ Levelrock® Quik-Top™ Gray Floor Underlayments

- Premium poured flooring product with self-drying technology
- Can be used with a variety of finished floor applications
- No shot blasting required
- Eliminates the need for sealing prior to floor-covering installation
- Can be stained or used by itself as a finished floor with an appropriate coating system



Now, thanks to an innovative USG technology, downtime due to floor rehab and repair work can be minimized. A floor typically can be prepped, poured and floor coverings applied within one day, allowing businesses to reopen the next day.

**Product  
Performance**

**Industry-Changing Technology**

It is now possible to repair floors in one day with LEVELROCK® QUIK-TOP™ and LEVELROCK® QUIK-TOP™ Gray floor underlayments. These innovative products are ideal for any job that requires a fast turnaround, such as renovations of retail space, restaurants, casinos, office space, hospitals and airports.

**High Performance**

LEVELROCK QUIK-TOP and QUIK-TOP Gray floor underlayments exceed commercial vinyl floor-covering requirements as high performance underlayments whose exceptional surface hardness resists indentation due to high compressive strengths of 7,000–10,000 psi.<sup>1</sup>

**Easy Preparation**

LEVELROCK QUIK-TOP floor underlayments do not require shot blasting. Concrete simply needs to be clean, sound, dry and primed.

**Finishing Flexibility**

Designed specifically for commercial, institutional and rehab projects, LEVELROCK QUIK-TOP floor underlayments are suitable for a variety of floor coverings. They also can be used as a finished floor with an appropriate coating system, and can be stained prior to application of a clear coat wear surface.<sup>2</sup> LEVELROCK QUIK-TOP Gray floor underlayment provides a concrete look for industrial, commercial or loft styles when used with a clear coating.

Additionally, LEVELROCK QUIK-TOP floor underlayments speed finished floor-covering applications. Once the floor underlayment is dry, floor-covering adhesive may be applied without sealing the underlayment.

**Notes** <sup>1</sup> Compressive strengths published herein were achieved under controlled laboratory conditions. Actual field results may differ due to environmental conditions; inconsistent proportioning of field applied water and LEVELROCK floor underlayment, as well as differences in mixing/pumping equipment. <sup>2</sup> USG does not warrant the performance of the wear surface coating. Consult coating manufacturer for suitability of use, field bond test and coating warranty.

**Product Information**

See [levelrock.com](http://levelrock.com) for the most up-to-date product information.

**Trademarks**

The following trademarks used herein are owned by United States Gypsum Company or a related company: LEVELROCK, QUIK-TOP, USG, USG in stylized letters.

**Notice**

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly

limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

**Safety First!**

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

