



USG Tile and Flooring Solutions

Product Portfolio

Panel Products



Durock® Cement Board Next Gen

Thickness:
1/4", 1/2", 5/8"
Panel sizes:
32" x 5', 32" x 8'
3' x 4', 3' x 5', 3' x 6'
4' x 8'

- Lightweight, high performance cement backerboard
- For floors, walls and countertops
- Interior or exterior applications
- Superior tile bond

- Protects against moisture and mold
- Dimensionally stable
- Will not swell, soften, delaminate, decay or disintegrate



Fiberock® Underlayment

Thickness:
1/4", 3/8"
Panel Sizes:
3' x 5'
4' x 4', 4' x 8'

- Easy to install, easy to cut and lightweight.
- Recognized in TCNA Handbook and International Residential Code for use in wet areas.

- 95% certified recycled content
- Approved for use in residential and light commercial applications
- Versatile for use under tile or vinyl flooring



Fiberock® Tile Backerboard

Thickness:
1/2", 5/8"
Panel Sizes:
3' x 5'
4' x 4', 4' x 8'

- Easy to install, easy to cut and lightweight.
- Recognized in TCNA Handbook and International Residential Code for use in wet areas.
- 95% certified recycled content

- Approved for use in residential and light commercial applications
- Versatile for use under tile on floors and paint or tile on walls

Tile Membrane System



Durock™ Tile Membrane

Sizes:
3' x 100' (300 sq. ft.) roll
3' x 25' (75 sq. ft.) roll in kit
Kit includes two 1 quart pails of Durock tile membrane adhesive

- For use under tile in floor, wall and countertop applications
- High performance crack isolation solution when installed with Durock tile membrane adhesive
- Patented cementitious surface provides outstanding tile bond

- Waterproof and vapor permeable membrane
- Mold and mildew resistant
- Installs fast and easily without mechanical fasteners
- Flexible with no roll-back memory
- DurockTileMembrane.com




Durock™ Tile Membrane Adhesive

Sizes:
2 gallon pail
1 quart pail

- For use with Durock tile membrane
- Versatile application (roller or trowel)
- Solvent-free advanced polymer technology
- Very low VOC emissions

- Fast bonding
- Contains an additive for mold and mildew resistance

Floor Paper



Fiberock™ Floor Protector Paper

Size:
3' x 167' roll

- Long-term protection for finished floors
- Can be used as scribing paper

- Heavy-duty, durable
- Made with 100% recycled paper

**Self-Leveling
Floor
Underlayment**



Durock™ Multi-Use Self-Leveling Underlayment
60 lb. bag

- Ideal for wood frame, renovation and light-commercial construction
- Can be applied over wood and concrete subfloors up to 3" thick

– Compressive strengths up to 3,500 psi



Durock™ Quick-Dry Self-Leveling Underlayment
60 lb. bag

- Ideal for commercial, institutional and rehab construction
- Installs from feather edge to 3"

– Fast setting allows for floor covering application within 15 hours of application
– Compressive strengths up to 6,000 psi



Durock™ Floor Patch
15 lb. bag

- For patching subfloors prior to application of floor covering
- Apply from feather edge to 1/2" thick

– Superior spreadability
– 20-minute working time

Primer



Durock™ Primer-Sealer
Sizes:
5 gallon pail
1 gallon bottle

- Ideal for use on porous concrete subfloors, wood and gypsum underlayment
- Enhances bond between substrate and underlayment

– Reduces alkalinity of concrete surfaces with no adverse effect on flooring adhesive
– Low odor

Accessories



Durock™ Tile Backer Tape
Sizes:
2" x 50' roll
2" x 250' roll

- Alkali-resistant glass fiber tape for use with Durock cement board and FIBEROCK tile backerboard/underlayment

– Ideal for reinforcing backerboard joints and corners in interior and exterior applications



Durock™ Screws
Wood Screws: 1-1/4", 1-5/8" and 2-1/4" lengths
Steel Screws: 1-1/4" and 1-5/8" lengths

- Ideal for attaching Durock cement board, FIBEROCK Underlayment and Tile Backerboard and other backerboards

– Corrosion-resistant coating
– Wafer-head design with strip-out-prevention ribs

Visit usg.com for full product details and installation information.

Product Information

See usg.com for the most up-to-date product information.

Note

Products described here may not be available in all geographic markets. Consult your United States Gypsum Company sales office or representative for information.

Trademarks

The following trademarks used herein are owned by United States Gypsum Company or its related companies: Durock, FIBEROCK, USG, USG in stylized letters.

Notice

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

Safety First!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

**For warranty or
product information
and literature:
800 USG.4YOU
usg.com/tileandflooring**

CB487/rev. 1-12
© 2012 United States Gypsum Company
Printed in U.S.A.