

# Sheetrock™ Lay-In Ceiling Panel *ClimaPlus*™



10

Year Availability  
3270

HRC

High Recycled Content



Sheetrock Lay-In Ceiling Panel, Vinyl, with *ClimaPlus* Performance/  
Donn ZXLA Suspension System

**LEED Credits**

Recycled Content: 23% – 56%  
*ClimaPlus* No-Sag Warranty

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials <sup>1</sup>	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
	●	●	●		●	●

**Features and Benefits**

- PVC-FREE panels feature a proprietary non-vinyl face material that is free of PVC and Phthalates
- CLEAN ROOM™ panels can be used in clean room environments up to class 100
- Washable and scrubbable finish– impact and scratch resistant
- Panels meet USDA/FSIS requirements for food processing areas
- *ClimaPlus*™ 30-year lifetime no-sag system warranty

**Applications**

- Kitchens and food preparation areas
- Restrooms and utility areas
- Locker rooms
- Parking garages
- Exterior protected soffits

**Substrate**

- Gypsum panel



To order samples, go to [usg.com](http://usg.com)



White

# Sheetrock™ Lay-In Ceiling Panel *ClimaPlus™*

To order samples/literature:  
 – Web: [usg.com](http://usg.com)  
 – E-mail: [samplit@usg.com](mailto:samplit@usg.com)  
 – Fax: 888 874.2348  
 Technical Services: 800 USG.4YOU

Web Sites: [usg.com](http://usg.com)  
[usgdesignstudio.com](http://usgdesignstudio.com)  
[sustainableceilings.com](http://sustainableceilings.com)  
[seismicceilings.com](http://seismicceilings.com)

See [usg.com](http://usg.com) for the most up-to-date product information.

**30**

Year System Warranty  
 – No visible sag

UL Classified

Edge	Panel Size	Class <sup>2</sup>	Item No.	NRC <sup>3</sup>	CAC Min.	LR <sup>4</sup>	Color	Abuse-Resistant	Grid Options	Recycled Content <sup>1</sup>	Panel Cost
SHEETROCK Lay-In Ceiling Panel <i>CLIMAPLUS</i> , Vinyl	SQ 	2'x2'x1/2"	3260	–	35	.77	White		A, B, C, D	23%	\$
		2'x4'x1/2"	3270	–	40	.77	White		A, B, C, D	23%	\$
SHEETROCK Lay-In Ceiling Panel <i>CLIMAPLUS</i> , PVC-FREE <sup>7</sup>	SQ 	2'x2'x1/2"	3220	–	35	.85	White		A, B, C, D	56% 	\$
		2'x4'x1/2"	3230	–	40	.85	White		A, B, C, D	56% 	\$
SHEETROCK Lay-In Ceiling Panel <i>CLIMAPLUS</i> , CLEAN ROOM <sup>5</sup>	SQ 	2'x4'x1/2"	3200	–	40	.77	White		A, B, C, D	23%	\$\$

**Legend**

**High Recycled Content**

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

A	B	C	D
DOWN <sup>®</sup> DX <sup>®</sup> /DXL <sup>™</sup>	DOWN <sup>®</sup> DXLA <sup>™</sup>	ZXL <sup>™</sup>	DOWN CE <sup>™6</sup>

**Grid Profile Options**

**Physical Data/ Footnotes**

**Product literature**  
 Data sheet: SC1820

**ASTM E1264 classification**  
 Type XX, Pattern G

**ASTM E84 surface burning characteristics**

Class A  
 Vinyl  
 Flame spread: 25  
 Smoke developed: 50  
 PVC-Free  
 Flame spread: 25  
 Smoke developed: 50  
 CLEAN ROOM  
 Flame spread: 25  
 Smoke developed: 50

**Weight**  
 1/2" = 2.00 lb./sq. ft.

**Thermal resistance**  
 1/2" = up to R-0.45

**Maximum backloading**  
 See Warranty for details.

**Maintenance**  
 Can be cleaned easily with a damp sponge. Use mild detergent and water – do not use acetate, ammonia or high concentration of chlorine, bromide or other harsh chemicals.

**Sustainability**  
 No formaldehyde was added to any ingredient or during the manufacturing process

**U.S. Coast Guard acceptance**  
 Approved for use on merchant ships.

**Footnotes**

- For details, see LEED report generator at [usgdesignstudio.com](http://usgdesignstudio.com).
- Fire-rated items: see UL design details.
- NRC rating is .10. USG does not consider a ceiling panel to be acoustically rated if NRC is less than .50
- LR values are shown as averages.
- Field-cut edges of CLEAN ROOM panels must be sealed with white latex paint.
- Clean-room-rated applications require a suspension system with gasketed tee flanges such as DOWN CE.

7. High Scrubbability/High Washability—PVC-FREE panels have been tested to withstand 10,000 scrub/wash cycles (ASTM D2486/ASTM D4828)  
 8. No formaldehyde is added to any ingredient or during the manufacturing process for all gypsum ceiling products manufactured by USG Interiors, Inc.



Manufactured by USG Interiors, Inc.  
 550 West Adams Street  
 Chicago, IL 60661

The following are trademarks of USG Interiors, Inc. or a related company: CE, CLEAN ROOM, CLIMAPLUS, DOWN, DX, DXL, DXLA, FIRECODE, SHEETROCK, USG, ZXL.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC1820/rev. 2-11  
 © 2011, USG Interiors, Inc.  
 Printed in U.S.A.