

Millennia™ *ClimaPlus*™ High-NRC



High Recycled Content



MILLENNIA High-NRC Panels with *CLIMAPLUS* Superior Performance/
DONN FINELINE DXF Suspension System

LEED Credits

Recycled Content: 75%
CLIMAPLUS Superior Performance for Mold and Mildew

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- High NRC value without mechanical perforations
- NRC of .75 meets the demanding sound control needs of open-plan offices
- Market's fastest-installing fine-textured ceiling is an economical alternative to face-laminated panels.
- *CLIMAPLUS*™ 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a *DONN*® brand suspension system

Applications

- Libraries
- Open-plan offices
- Reception and lobby areas
- Legal
- Financial institutions

Substrate

- X-Technology mineral fiber



Fine-textured panel

To order samples, go to usg.com



White

Millennia™ ClimaPlus™ High-NRC

To order samples/literature:
 – Web: usg.com
 – E-mail: samplit@usg.com
 – Fax: 888.874.2348
 Technical Services: 800.USG.4YOU

Web Sites: usg.com
usgdesignstudio.com
sustainableceilings.com
seismicceilings.com

See usg.com for
 the most up-to-date
 product information.

30

Year System Warranty
 – No visible sag
 – Mold/mildew protection

MILLENNIA
 CLIMAPlus
 High-NRC
 Panels

UL Classified												
Edge	Panel Size	Class	Item No.	NRC	CAC Min. ³	LR ⁴	Color	Grid Options	VOC ⁵ Emissions	Anti-Mold & Mildew	Recycled Content ²	Panel Cost
SLT 	2' x2' x3/4"	Class A	76201	.75 	30	.87 	White	A	Low		75% 	\$\$
FLB 	2' x2' x3/4"	Class A	76302	.75 	30	.87 	White	B, C, D, E	Low		75% 	\$\$

Legend

Low Emissions (VOC Class)

Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

CLIMAPlus Superior Performance⁵

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold and mildew.

HRC High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Grid Profile Options

A DX®/DXL™	B CENTRICITEE™ DXT	C FINELINE® DXF	D FINELINE® 1/8 DXFF	E IDENTITEE™ DXI™

Physical Data/ Footnotes

Product literature
 Data sheet: SC1851

ASTM E1264 classification
 Type III, Form 1, Pattern E, G

ASTM E84 surface burning characteristics
 Class A

Flame spread: 25
 Smoke developed: 50

Weight
 1.06-1.09 lb./sq. ft.

Thermal resistance
 R-2.0

Maximum backloading
 See Warranty for details.

Maintenance
 Can be cleaned easily with a soft brush or vacuum.

Proprietary technology
 This product's unique combination of sag resistance and sound performance results from a proprietary technology.

Footnotes

1. Applies when USG acoustical ceilings recycling program is utilized.
2. For details, see LEED report generator at usgdesignstudio.com.
3. Adding sound masking can be as effective as using a ceiling panel with a higher CAC rating, providing increased privacy between enclosed office spaces.
4. LR values are shown as averages.
5. Panel face and back surfaces treated with a proprietary, broad-spectrum

antimicrobial standard formulation that inhibits and retards the growth of mold and mildew. For details, see *Ceiling Systems Limited Warranty Commercial Applications* (SC2102) and *ClimaPlus Ceilings Certification of Performance* (SC2451).
 6. No formaldehyde is added to any ingredient or during the manufacturing process for all mineral fiber acoustical ceiling products manufactured by USG Interiors, LLC.



Manufactured by USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The following are trademarks of USG Interiors, LLC or a related company: CENTRICITEE, CLIMAPlus, DONN, DX, DXF, DXFF, DXI, DXL, DXT, FINELINE, IDENTITEE, MILLENNIA, USG.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC1851/rev. 1-12
 © 2012 USG Interiors, LLC
 Printed in U.S.A.