



Premier Hi-Lite Twill Panels with *CLIMAPLUS* Performance/
Down DX/DXL Suspension System

LEED Credits

Recycled Content: 31%
CLIMAPLUS No-Sag Warranty

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials ¹	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
	●	●			●	●

Features and Benefits

- Washable vinyl face for easy maintenance.
- Excellent noise reduction with NRC of .60 or .75 for greater sound control in open-plan spaces.
- *CLIMAPLUS*™ 30-year system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a Down® brand suspension system.
- Lightweight fiberglass basemat makes installation fast and easy.

Applications

- Discount stores
- Grocery stores
- Mass merchandisers
- Retail stores

Substrate

- Fiberglass



Call 888 874.2450 for color samples

See individual items for color availability.



White



Flat Black 205

Premier Hi-Lite™ *ClimaPlus*™

Web Sites: usg.com
usgdesignstudio.com
sustainableceilings.com
seismicceilings.com

Technical Service 800 USG.4YOU
 Samples/Literature 888 874.2450
 Samples/Literature Fax 888 874.2348
 Customer Service 800 950.3839

See usg.com for
 the most up-to-date
 product information.

30
 Year System Warranty
 - No visible sag
 - Mold/mildew protection

**PREMIER HI-LITE
 CLIMAPLUS Twill
 Panels**

**PREMIER HI-LITE
 CLIMAPLUS Kapok
 Panels**

Edge	Panel Size	Class	Item No.	UL Classified		LR ²	Color ³	Grid Options	Anti-Mold & Mildew	Recycled Content ⁴	Panel Cost
				NRC	CAC Min.						
SQ 	2' x 2' x 5/8" Perforated	Class A	7050G	.75 	20	.76	White	A, B, C, D		31%	\$
	2' x 2' x 5/8" Unperforated	Class A	7052G	.60 	20	.76	White	A, B, C, D		31%	\$
	2' x 4' x 5/8" Perforated	Class A	7051G	.75 	20	.76	White	A, B, C, D		31%	\$
	2' x 4' x 5/8" Unperforated	Class A	7053G	.60 	20	.76	White	A, B, C, D		31%	\$
SQ 	2' x 2' x 5/8" Perforated	Class A	7054G	.75 	20	.76	White and Black	A, B, C, D		31%	\$
	2' x 2' x 5/8" Unperforated	Class A	7056G	.60 	20	.76	White and Black	A, B, C, D		31%	\$
	2' x 4' x 5/8" Perforated	Class A	7055G	.75 	20	.76	White and Black	A, B, C, D		31%	\$
	2' x 4' x 5/8" Unperforated	Class A	7057G	.60 	20	.76	White and Black	A, B, C, D		31%	\$

Legend

CLIMAPLUS Inherent Performance⁵
 Fiberglass substrate is inherently resistant to the growth of mold and mildew.

A DX®/DXL™	B DXW™	C ZXLA™	D AX™

**Grid Profile
 Options**

**Physical Data/
 Footnotes**

Product literature
 Data sheet: SC1838

ASTM E1264 classification
 Type XII, Form 1, Pattern CE
 (Perforated), Pattern E (Unperforated)

**ASTM E84 surface burning
 characteristics**
 Class A
 Flame spread: 25
 Smoke developed: 50

Weight
 .19-.33 lb./sq. ft.

Thermal resistance
 R-2.7

Maximum backloading
 See Warranty for details.

Maintenance
 Can be cleaned easily with a damp
 sponge.

Footnotes

1. Dependent on location; see Sustainability selector.
2. LR values are shown as averages.
3. See Colors selector for more information.
4. For details, see Sustainability selector.
5. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPLUS Ceilings Certification of Performance* (SC2451).



Manufactured by USG Interiors, Inc.
 550 West Adams Street
 Chicago, IL 60661

The following are trademarks of USG Interiors, Inc.
 or a related company: AX, CLIMAPLUS, Donn, DX, DXL,
 DXW, PREMIER HI-LITE, USG, ZXLA.

Safety First! Follow good safety/industrial hygiene practices
 during installation. Wear appropriate personal protective equipment.
 Read MSDS and literature before specification and installation.

SC1838/rev. 6-08
 © 2008, USG Interiors, Inc.
 Printed in U.S.A.