

TOPO™ and TRANSLUCENTS™ Ceiling Panels

Pre-Installation, Cleaning and Maintenance Instructions

TOPO™ 3-Dimensional System and TRANSLUCENTS™ Luminous Infill Panels create contemporary spaces with unique visual impact in retail, hospitality, office, education and entertainment environments. These systems consist of pre-formed and flat LEXAN® infill panels and a corresponding DONN® Brand Suspension System.

Proper preparation and cleaning can help to maintain the panels' original appearance. Before installation, remove any dirt and debris from the surrounding area.

Preparation

Remove masking paper adhesive from the panels by applying naphtha (VM&P) or kerosene with a soft cloth, then clean immediately with soap and water. Do not use gasoline. If the panel has static electricity build-up, wash according to instructions below to prevent the panel from attracting dirt and dust.

Washing

Washing will reduce static electricity in the panels, helping to prevent attraction to dust. Wash panels with a mild soap or detergent (see Compatible Cleaners below) and lukewarm water, using a clean sponge or soft cloth. Rinse well with clean water. Dry thoroughly with a chamois or moist cellulose sponge to prevent water spots. Do not scrub or use brushes.

To remove fresh paint splashes, grease or smeared glazing compounds, rub panels lightly with VM&P naphtha or isopropyl alcohol. Wash with warm water and a mild soap or detergent solution. Rinse thoroughly with clean water and dry.

Compatible Cleaners

Harsh solvents such as methyl ethyl ketone (MEK) or muriatic acid can cause surface degradation and crazing. Use only the following mild cleaning agents:

- VM&P naphtha
- Brillianize
- FREON® 11 or FREON 113
- JOY®
- PALMOLIVE® Dishwashing Liquid
- WINDEX®

Follow the manufacturer's instructions and recommendations when using these products.

Polishing Scratches

Buff and fill scratches and minor abrasions with one of the following mild polishes:

- MEGUIAR'S® Mirror Glaze Clear Plastic Detailer
- NOVUS® Plastic Polish (No. 1 or No. 2)
- PLEXUS® Plastic Cleaner Protectant and Polish
- SC JOHNSON® Paste Wax

Test the product selected on a small section of one panel, following the polish manufacturer's instructions, to determine its effectiveness for your application.

Limitations

- **Do not** use abrasive or highly alkaline cleaners.
- **Do not** scrape panels with squeegees, razor blades or other sharp instruments.
- **Do not** use benzene, gasoline, acetone, carbon tetrachloride or butyl cellosolve.
- **Do not** clean panels in extreme sunlight or at elevated temperatures.

Trademarks

The following trademarks used herein are owned by USG Interiors or a related company: DONN, TOPO, TRANSLUCENTS. FREON is a trademark of E.I. du Pont de Nemours and Company. Joy is a trademark of Proctor & Gamble Company. LEXAN is a registered trademark of General Electric Company. MEGUIAR'S is a trademark of Meguiar's, Inc. NOVUS is a trademark of Novus Plastic Polish, Ltd. PALMOLIVE is a trademark of Colgate-Palmolive Company. PLEXUS is a trademark of BTI Chemical Co., Inc. WINDEX and SC JOHNSON are trademarks of S. C. Johnson & Son, Inc.

Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date it was or reasonably should have been discovered.

Note

All products described here may not be available in all geographic markets. Consult your local sales office or representative for more information.
Safety First!
Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.

