

# CGC DUROCK™ BRAND SEALANT



## DESCRIPTION

- Easy to apply
- Long open time
- Nonflammable
- Low odour
- VOC compliant in California
- Freeze-thaw stable

## PRODUCT DATA

**Sizes and Packaging:** 298 ml (10.1 FL. OZ.) cartridge – 12 cartridges/carton  
Shipped in packaging units as shown

## AVAILABILITY

CGC Durock Sealant is distributed throughout Canada. Contact a CGC sales office or representative for additional information.

## COMPOSITION AND MATERIALS

CGC Durock Sealant is composed of calcium carbonate CAS 1317-65-3, polymer CAS proprietary, plasticizer CAS proprietary, N-beta-(aminoethyl)-gamma-aminopropyltrimethoxysilane and vinyltrimethoxysilane.

## DELIVERY AND STORAGE OF MATERIALS

All materials should be delivered and stored in their original unopened package and stored in an enclosed shelter providing protection from damage and exposure to the elements.

## APPLICATION AND CLEANUP

CGC Durock Sealant can be applied directly on clean, dry, properly prepared and attached surfaces, including: tile backerboard, ceramic tile, stone, drywall, aluminum, glass, XPS and EPS foam, wood and ABS plastic.

Remove any loose paint, dust, dirt, oil, grease and efflorescence before applying.

Skin-over time 8 minutes, tack-free time 45 minutes, cure time 24 hours at 24°C (75°F), 50% relative humidity, applied at 9.5 mm (3/8 in.) thickness.

**Cleanup:** Immediately remove sealant from unwanted areas using dry cloth or mineral spirits.

## LIMITATIONS

Do not apply sealant to contaminated or loose surfaces.

## TECHNICAL DATA

### CGC Durock™ Brand Sealant

<b>Appearance</b>	Smooth
<b>Colour</b>	White
<b>Specific gravity</b>	1.50
<b>Extrusion rate (g/minute)</b>	200
<b>Slump (in.)</b>	0
<b>Skin-over time (minute)</b>	8
<b>Tack-free time (minute)</b>	45
<b>Shore "A"</b>	50
<b>Tensile strength (psi)</b>	325
<b>Elongation (%)</b>	275
<b>Modulus (psi)</b>	300
<b>Solid (%)</b>	98
<b>VOC Content g/L</b>	15

#### PRODUCT INFORMATION

See [cgcinc.com](http://cgcinc.com) for the most up-to-date product information.

#### WARNING

DIRECT CONTACT OF UNCURED SEALANT IRRITATES EYES AND MAY IRRITATE SKIN. Use proper personal protective equipment; safety glasses to protect eyes and rubber gloves to protect hands. OVEREXPOSURE TO VAPOUR MAY IRRITATE EYES, NOSE AND THROAT. Avoid eye and skin contact. Use with adequate ventilation. Do not handle contact lenses with sealant on hands. IN CASE OF EYE CONTACT, flush eyes with water for 15 minutes. Obtain medical attention. IN CASE OF SKIN CONTACT, remove from skin and flush with water. For safe handling information consult the Material Safety Data Sheet (MSDS). Product safety information: CHEMTREC (800) 424-9300 (24 hours) or [accumetricinc.com](http://accumetricinc.com).

**KEEP OUT OF REACH OF CHILDREN.**

#### TRADEMARKS

The trademarks CGC, DUROCK, IT'S YOUR WORLD. BUILD IT., the CGC logo, the design elements and colours, and related marks are trademarks of USG Corporation or its affiliates.

#### NOTE

Products described here may not be available in all geographic markets. Consult your CGC Inc. sales office or representative for information.

#### NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

#### SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

DSS\_SEALANT\_CB666E/9-15  
© 2015 CGC Inc.  
All rights reserved.  
Printed in Canada.

800.387.2690  
[cgcinc.com](http://cgcinc.com)

Manufactured by:  
CGC Inc.  
350 Burnhamthorpe Rd. W, 5th Floor  
Mississauga, ON L5B 3J1