

CGC SHEETROCK[®] BRAND 54" GYPSUM PANEL PORTFOLIO



THE BETTER WAY TO BUILD

FOR EASIER, FASTER INSTALLATION, CHOOSE CGC SHEETROCK[®] BRAND 54" GYPSUM PANELS.

CGC Sheetrock[®] Brand 54" Gypsum Panels save time and money by using either two 54 in. panels for 9 ft. walls or one 54 in. and one 48 in. CGC Sheetrock® Brand panel for 8 ft. 6 in. CHEETROCK Same / Ultralight Start SHEETROCK Same / Ultralight Start Ultralight Start SHEETROCK Same / Ultralight Start same Ultralight Start Sta walls. And a uniform appearance means no more filler pieces to cut, faster taping and finishing, and a flatter wall under any lighting conditions.

PORTFOLIO

1/2" – 54" CGC Sheetrock[®] Brand UltraLight Panels 5/8" - 54" CGC Sheetrock[®] Brand UltraLight Panels Firecode[®] X (Type ULIX) 5/8" - 54" CGC Sheetrock[®] Brand Panels Firecode[®] X (Type SCX)

ADVANTAGES

Lightweight. Available in the lightest 12.7 mm (1/2") and 15.9 mm (5/8") gypsum panels in the industry.

Low in-place cost. Saves valuable time and money for drywall contractors by minimizing cutting, extra joints and disposal fees.

Fire protection. ULC Listed and cUL Classified for fire resistance, surface-burning characteristics and noncombustibility. For use in fire-rated partitions when installed horizontally with aligned tapered edges on 25-gauge steel studs (can be installed perpendicular to steel framing with unbacked and unstaggered joints). Complies with ASTM C1396 requirements for 15.9 mm (5/8") Type X gypsum panel.

Crack resistance. With joints reinforced by one of CGC Sheetrock® or Synko® Brand joint treatment systems, Sheetrock® Brand 54" Gypsum Panels form walls and ceilings that are exceptionally resistant to cracks caused by structural, thermal and hygrometric changes.

Sustainable. CGC Sheetrock[®] Brand Gypsum Panels achieved GREENGUARD Gold Certification and qualify as a low VOC emitting material. (meets CA 01350).

UL/ULC DESIGNS FOR STEEL- AND WOOD-FRAME APPLICATIONS

ULC W453 (1-4 hour) non-load-bearing steel

cUL U423 (1-2 hour) load-bearing steel

cUL U305 (1 hour) load-bearing wood

See the difference at cgcinc.com/sheetrock-ultralight

Manufactured by: CGC Inc. 350 Burnhamthorpe Rd. W, 5th Floor Mississauga, ON L5B 3J1

Customer Service: 800.387.2690 cgcinc.com

WB2905-CAN-ENG/03-20 © 2020 USG Corporation and/or its affiliates. All rights reserved. Printed in Canada

PRODUCT INFORMATION See cgcinc.com for the most up-to-date product information.

2020 CGC A USG COMPANY and/or its affiliates. All rights reserved. The trademarks CGC, FIRECODE, SHEETROCK, SYNKO, IT'S YOUR WORLD. BUILD IT.,

the CGC logo, the design elements and colours, and

related marks are trademarks of USG Corporation

TRADEMARKS

or its affiliates.

NOTE

Products described here may not be available in all geographic markets. The information in this document is subject to change without notice. CGC Inc. assumes no responsibility for any errors that may inadvertently appear in this document. Consult your CGC Inc. sales office or representative for information

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been disco

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read Safety Data Sheets and related literature on products before specification and/ or installation.



UltraLigi

NUCK inter