

CGC SECUROCK® BRAND ULTRALIGHT GLASS-MAT ROOF BOARD



High-performance glass-mat roof board for use in low-slope commercial roofing systems

- Lightweight core; up to 18% lighter than competitive glass-mat roof boards¹
- Ideal for use as cover board in single-ply mechanically attached systems
- Moisture and mould-resistant core and facer
- Provides protection to roof system from hail and foot traffic
- Fire-resistant for use as fire barrier and thermal barrier
- Unmatched mat-to-core tensile bond strength makes facer less likely to delaminate when cutting
- High-quality tight mat makes for easier handling and cutting

1. 12.7 mm (1/2 in.) and 15.9 mm (5/8 in.) thicknesses only.

DESCRIPTION

CGC Securock® Brand UltraLight Glass-Mat Roof Board is a high-performance roof board for use in low-slope commercial roofing systems. It enhances the durability of the entire roofing system when used as cover board in single-ply mechanically attached systems. Its specially treated core and high-performance glass-mat facer provide protection against fire, mould and moisture.

ADVANTAGES

Fire Performance: Meets Factory Mutual (FM) Class 1 and Underwriters Laboratories (UL) Class A fire ratings for unlimited slope in fire barrier applications per UL 790.

Easier to cut, handle and install: High-quality mat produces less itchiness than competitive products.

Moisture and Mould: Fiberglass face and back with treated core provides moisture and mould resistance. Scored a maximum "10" for mould resistance on ASTM D3273.

INSTALLATION

- Refer to roof system manufacturer's written instructions, local code requirements and Factory Mutual Global (FMG) and/or Underwriters Laboratories (UL) requirements for proper installation techniques.
- Use fasteners specified in accordance with above requirements. Install approved fasteners with plates into the CGC Securock® UltraLight Glass-Mat Roof Board, flush with the surface. Fasteners should be installed in strict compliance with the roof system manufacturer's installation recommendations and FMG Loss Prevention Data Sheet 1-29. A qualified architect or engineer should review and approve calculations, framing and fastener spacing for all projects.
- Locate edge joints on, and parallel to, deck ribs. Stagger end joints of adjacent lengths of CGC Securock® UltraLight Glass-Mat Roof Board.
- All board edges should be loosely abutted and never kicked in tight in typical installations.
- Roof boards should never be installed if they exhibit frost.
- For cover board applications, 6.4 mm (1/4 in.) CGC Securock UltraLight Glass-Mat roof boards should not be installed below 0°C (32°F)
- See product data table for maximum flute span when panels are applied directly over metal decking.
- For vertical parapet applications, only 12.7 mm (1/2 in.) or 15.9 mm (5/8 in.) panels should be used. Maximum framing spacing is 610 mm (24 in.) o.c.

LIMITATIONS

- CGC Securock® UltraLight Glass-Mat Roof Board is engineered to perform within a properly designed roof system. The use of CGC Securock® UltraLight Glass-Mat Roof Board as a roofing component is the responsibility of the design professional.
- Consult roofing manufacturers for specific instructions on the application of their products to CGC Securock® UltraLight Glass-Mat Roof Board.
- Weather conditions, dew, application temperature, installation techniques and moisture drive can have adverse effects on the performance of the roof system and are beyond the control of CGC Inc.

LIMITATIONS
(CONTINUED)

-
- Keep CGC Securock® UltraLight Glass-Mat Roof Board panels dry before, during and after installation. CGC Securock® UltraLight Glass-Mat Roof Board should not be installed during rains, heavy fogs and any other conditions that deposit moisture on the surface of the board. Apply only as much CGC Securock® UltraLight Glass-Mat Roof Board that can be covered by final roof membrane system in the same day. Avoid exposure to moisture from leaks or condensation.
 - Wind-uplift (vertical pull) of the roof system as installed can be affected by many factors beyond CGC Inc.'s control, including moisture migrating into the roof assembly from inside or outside the building, proper fastener spacing, the quality of installation especially for fasteners and whether the framing has been properly designed and installed to meet strength and deflection criteria specified in the contract documents. For all these reasons, CGC Inc. cannot guarantee the wind-uplift resistance (vertical pull) of any roof assembly or system containing CGC roof boards.
 - Moisture from inside the building can be as big a risk for the roof system as moisture from outside. The contractor installing the roof and the design professional should protect the roof assembly not only from excessive moisture during the construction of the building (new concrete, paint, plaster materials) but also after the building is dried in. The HVAC system must properly manage moisture generated by the occupants of the building to make sure it is vented to the outside and does not migrate into the roof system.
 - Panel spacing may be needed based on factors like roof deck's size, membrane colour, ultimate deck surface temperature and time of year the roof is installed. The designer of record should use CGC's published physical properties below to determine if spacing is needed.
 - For reroof or recover applications, existing roofing system must be dry throughout prior to application of CGC Securock® UltraLight Glass-Mat Roof Board.
 - Plastic or poly packaging applied at the plant to protect board during rail or other transit should be removed upon receipt to prevent condensation or trapping of moisture, which may cause application problems.
 - CGC Securock® UltraLight Glass-Mat Roof Board should be stored flat and off the ground with protection from the weather. If stored outdoors, a breathable waterproof covering should be used.
 - For systems not listed, please contact your local CGC Securock® roofing sales representative.
-

FIRE PERFORMANCE

- cUL Classified (Type SGMRX) as to Surface Burning Characteristics in accordance with CAN/ULC S102 (ASTM E84).
 - Flame Spread 0 and Smoke Developed 0
 - Noncombustible Core per ASTM E136-12 (CAN/ULC-S114)
 - 6.4 mm (1/4 in.), 12.7 mm (1/2 in.) and 15.9 mm (5/8 in.) Thickness — Class A unlimited slope in accordance with CAN/ULC S107 (UL790).
 - 15.9 mm (5/8 in.) Thickness — Meets requirements of Type X per ASTM C1177 and may be used in P series designs as a thermal barrier.
-

SYSTEM PERFORMANCE

- FM Approved
 - Complies with requirements of FM 4450 and FM 4470
 - Meets FM Class 1
-

STANDARDS COMPLIANCE

CGC Securock® UltraLight Glass-Mat Roof Board is manufactured to conform to ASTM C1177.

PHYSICAL PROPERTIES

	6.4 mm (1/4 in.)	12.7 mm (1/2 in.)	15.9 mm (5/8 in.)
Width, standard	1220 mm (4 ft.)	1220 mm (4 ft.)	1220 mm (4 ft.)
Length, standard	2440 mm (8 ft.)	2440 mm (8 ft.)	2440 mm (8 ft.)
Pieces per unit for 4' x 8' sheet	42	30	30
Weight, nominal kg (lbs.)/unit 4' x 8' sheet	766 (1688)	774 (1707)	992 (2187)
Weight, nominal kg/m ² (lbs./sq.ft)	5.85 (1.2)	8.3 (1.7)	10.7 (2.2)
Flexural strength, parallel, lbs. min. per ASTM C473	40	80	100
Compressive strength, MPa (psi) nominal	4.8–6.9 (700–1000)	4.8–6.9 (700–1000)	4.8–6.9 (700–1000)
Flute spannability per ASTM E661	67 mm (2-5/8 in.)	127 mm (5 in.)	200 mm (8 in.)
Permeance, perms per ASTM E96	18	18	16
R Value per ASTM C518	0.36	0.53	0.54
Coefficient of thermal expansion, inches/inch °F, per ASTM E831	8.5 x 10 ⁻⁶	8.5 x 10 ⁻⁶	8.5 x 10 ⁻⁶
Linear variation with change in moisture, inches/inch %RH, per ASTM D1037	6.3 x 10 ⁻⁶	6.3 x 10 ⁻⁶	6.3 x 10 ⁻⁶
Water absorption, % max, per ASTM C473	10	10	10
Mould resistance per ASTM D3273*	10	10	10
Bending Radius	1220 mm (4 ft.)	1830 mm (6 ft.)	2740 mm (9 ft.)

*ASTM D3273 Mould Resistance Testing: In independent lab tests conducted on CGC Securock® Brand Gypsum-Fiber Roof Board and Glass-Mat Roof Board at the time of manufacture per ASTM D3273 Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings in an Environmental Chamber, both panels scored a 10. The ASTM lab test may not accurately represent the mould performance of building materials in actual use. Given unsuitable project conditions during storage, installation or after completion, any building material can be overwhelmed by mould. To manage the growth of mould, the best and most cost-effective strategy is to protect building products from water exposure during storage and installation and after completion of the building. This can be accomplished by using good design and construction practices.

PRODUCT INFORMATION

See cgcinc.com for the most up-to-date product information.

CAUTION

Dust may cause irritation to eyes, skin, nose, throat, and upper respiratory tract. Cut and trim with a utility knife or hand saw to minimize dust levels. Power tools must be equipped with a dust collection system. Wear eye, skin, and respiratory protection if necessary. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists, call physician. Do not swallow. If swallowed, call physician. For more information call Product Safety: 800.507.8899 or see the SDS at usg.com KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks CGC, SECUROCK, IT'S YOUR WORLD, BUILD IT., the CGC logo, the design elements and colours, and related marks are trademarks of USG Corporation or its affiliates.

NOTE

Products described here may not be available in all geographic markets. The information in this document is subject to change without notice. CGC Inc. assumes no responsibility for any errors that may inadvertently appear in this document. Consult your CGC Inc. sales office or representative for information.

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read Safety Data Sheets and related literature on products before specification and/or installation.

800.387.2690
cgcinc.com

Manufactured by:
CGC Inc.
735 Fourth Line, Oakville, ON L6L 5B7

RF32-CAN-ENG/rev. 10-23
© 2018 USG Corporation
and/or its affiliates.
All rights reserved.
Printed in Canada.

