



SAFETY DATA SHEET

1. Identification

Product identifier MICORE® SB Mineral Fiber Board

Other means of identification

SDS number 41263520001

Synonyms Mineral Fiber Panel, Micore Panel

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer United States Gypsum Company

Address 550 West Adams Street
Chicago, Illinois 60661-3637

Telephone 1-800-874-4968

Website www.usg.com

Emergency phone number 1-800-507-8899

Supplier CGC Inc.

Address 350 Burnhamthorpe Road West, 5th Floor
Mississauga, Ontario L5B 3J1
A Subsidiary of USG Corporation

Telephone 1-800-387-2690

Website www.cgcinc.com

Emergency phone number 1-800-507-8899

2. Hazard identification

Physical hazards Not classified.

Health hazards Carcinogenicity (inhalation) Category 1A
Specific target organ toxicity following repeated exposure (inhalation) Category 2 (Lung)

Label elements



Signal word Danger

Hazard statement May cause cancer by inhalation. May cause damage to organs (Lung) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear protective gloves/protective clothing/eye protection/face protection.

Response IF exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Slag wool fiber		N/A	40 - 60
Perlite		93763-70-3	10 - 20
Kaolin		1332-58-7	10 - 20
Starch		9005-25-8	5 - 10
Cellulose		9004-34-6	5 - 10

Impurities	CAS number	%
Crystalline silica (Quartz)	14808-60-7	1 - 5

Composition comments

All concentrations are in percent by weight.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is <3%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

Raw materials and/or coatings in this product contain small amounts of titanium dioxide, which has been classified as possibly carcinogenic to humans by the International Agency for Research on Cancer (IARC). However, per IARC "no significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints" (1). See Section 16 for further information.

4. First-aid measures

Inhalation

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

Skin contact

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.

Eye contact

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Under normal conditions of intended use, this product is not expected to be a health risk. Dust may irritate throat and respiratory system and cause coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Not applicable.

Specific hazards arising from the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods

Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

No specific clean-up procedure noted. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Use work methods which minimise dust production. Avoid inhalation of dust and contact with skin and eyes. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	TWA	10 mg/m ³	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable fraction.
Starch (CAS 9005-25-8)	TWA	10 mg/m ³	
Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	TWA	10 mg/m ³	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable.
Perlite (CAS 93763-70-3)	TWA	3 mg/m ³	Respirable particles.
		10 mg/m ³	Total particulate.
Starch (CAS 9005-25-8)	TWA	10 mg/m ³	
Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable particles.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	TWA	3 mg/m ³	Respirable fraction.
		10 mg/m ³	Total dust.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m ³	Respirable.
Perlite (CAS 93763-70-3)	TWA	3 mg/m ³	Respirable fraction.
		10 mg/m ³	Total dust.
Starch (CAS 9005-25-8)	TWA	3 mg/m ³	Respirable fraction.
		10 mg/m ³	Total dust.
Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	TWA	10 mg/m ³	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Starch (CAS 9005-25-8)	TWA	10 mg/m3	
Impurities	Type	Value	Form

Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
---	-----	-------------	----------------------

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	TWA	10 mg/m3	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Perlite (CAS 93763-70-3)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Starch (CAS 9005-25-8)	TWA	10 mg/m3	
Impurities	Type	Value	Form

Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
---	-----	-----------	----------------------

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	TWA	10 mg/m3	Total dust.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable dust.
Perlite (CAS 93763-70-3)	TWA	10 mg/m3	Total dust.
Starch (CAS 9005-25-8)	TWA	10 mg/m3	Total dust.
Impurities	Type	Value	Form

Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
---	-----	-----------	------------------

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value	Form
Cellulose (CAS 9004-34-6)	15 minute	20 mg/m3	Fiber.
	8 hour	10 mg/m3	Fiber.
Kaolin (CAS 1332-58-7)	15 minute	4 mg/m3	Respirable fraction.
	8 hour	2 mg/m3	Respirable fraction.
Perlite (CAS 93763-70-3)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
Starch (CAS 9005-25-8)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
Impurities	Type	Value	Form

Crystalline silica (Quartz) (CAS 14808-60-7)	8 hour	0.05 mg/m3	Respirable fraction.
---	--------	------------	----------------------

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimise the risk of exposure. Cut and trim with a utility knife or hand saw to minimize dust levels. If a router is used it must have a dust collection system. Operations such as power cutting, power kerfing or using compressed air to remove dust are not recommended (2). See Section 16 for further information.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear approved safety goggles.

Skin protection**Hand protection**

It is a good industrial hygiene practice to minimise skin contact. For prolonged or repeated skin contact use suitable protective gloves.

Other	Normal work clothing (long sleeved shirts and long pants) is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	None.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Panel.
Colour	Gray/brown.
Odour	Low to no odour.
Odour threshold	Not applicable.
pH	9
Melting point/freezing point	1204.44 °C (2200 °F) (Slag wool)
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.

Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	0.34 (H ₂ O=1)

Solubility(ies)

Solubility (water)	Very low solubility in water.
---------------------------	-------------------------------

Partition coefficient (n-octanol/water)	Not applicable.
--	-----------------

Auto-ignition temperature	Not applicable.
----------------------------------	-----------------

Decomposition temperature	Not applicable.
----------------------------------	-----------------

Viscosity	Not applicable.
------------------	-----------------

Other information

Bulk density	21 lb/ft ³
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
VOC	Not applicable.

10. Stability and reactivity

Reactivity	The product is stable and non reactive under normal conditions of storage and transport.
-------------------	--

Chemical stability	Material is stable under normal conditions.
---------------------------	---

Possibility of hazardous reactions	Hazardous polymerisation does not occur.
---	--

Conditions to avoid	Contact with incompatible materials.
----------------------------	--------------------------------------

Incompatible materials	Strong oxidising agents.
-------------------------------	--------------------------

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Inhalation of dusts may cause respiratory irritation. Prolonged and repeated exposure to airborne respirable crystalline silica can cause silicosis and/or lung cancer.

Skin contact May cause irritation through mechanical abrasion.

Eye contact Direct contact with airborne particulates may cause temporary irritation.

Ingestion Ingestion may cause irritation and stomach discomfort.

Symptoms related to the physical, chemical and toxicological characteristics Under normal conditions of intended use, this material does not pose a risk to health. Dust may irritate throat and respiratory system and cause coughing.

Information on toxicological effects

Acute toxicity Not expected to be a hazard under normal conditions of intended use.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitisation

Respiratory sensitisation No data available, but none expected.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicity No data available, but none expected.

Carcinogenicity Repeated and prolonged exposures to high levels of respirable crystalline silica may cause cancer.

ACGIH Carcinogens

Crystalline silica (Quartz) (CAS 14808-60-7)

A2 Suspected human carcinogen.

Kaolin (CAS 1332-58-7)

A4 Not classifiable as a human carcinogen.

Canada - Alberta OELs: Carcinogen category

Crystalline silica (Quartz) (CAS 14808-60-7)

Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Crystalline silica (Quartz) (CAS 14808-60-7)

Suspected human carcinogen.

Kaolin (CAS 1332-58-7)

Not classifiable as a human carcinogen.

Canada - Quebec OELs: Carcinogen category

Crystalline silica (Quartz) (CAS 14808-60-7)

Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (Quartz) (CAS 14808-60-7)

1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline silica (Quartz) (CAS 14808-60-7)

Known To Be Human Carcinogen.

Reproductive toxicity No data available.

Specific target organ toxicity - single exposure No data available, but none expected.

Specific target organ toxicity - repeated exposure May damage lung tissue through repeated and prolonged exposure to high levels of respirable crystalline silica particles.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

Chronic effects Prolonged and routine inhalation of high levels of respirable crystalline silica particles can lead to the lung disease known as silicosis. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to respirable crystalline silica. Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

12. Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	Bioaccumulation is not expected.
Mobility in soil	No data available.
Other adverse effects	None expected.

13. Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

14. Transport information

TDG	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable. This product is a solid. Therefore, bulk transport is governed by IMSBC code.

15. Regulatory information

Canadian regulations	This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.
-----------------------------	--

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 09-October-2020

Revision date -

Version No. 01

Further information

Crystalline silica: Raw materials in this product may contain respirable crystalline silica as an impurity. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Industrial hygiene testing by RJ Lee Group showed that cutting with a utility knife or a router equipped with a dust collection system did not produce airborne respirable crystalline in exceedance of OSHA PELs. However, cutting with a power saw, even with a dust collection system in place, did produce some exceedances. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Slag Wool Fiber: Large morbidity and mortality studies of both European and North American mineral wool manufacturing workers have been conducted. These studies have found no significant association of non-malignant (i.e. fibrosis) or malignant (i.e., lung cancer or mesothelioma) lung disease and exposures to slag wool fibers and have not established a causal relationship between exposure and non-malignant or malignant diseases.

In 2001, the International Agency for Research on Cancer (IARC) assigned slag wool fiber to the Group 3 category ["not classifiable as to carcinogenicity to humans"].

The synthetic mineral fiber used in this product is exonerated from classification as a carcinogen in accordance with Note Q in the EU Commission Directive 97/69/EC.

Titanium dioxide: Raw materials and/or coatings in this product contain small amounts of titanium dioxide. The International Agency for Research on Cancer (IARC) has determined that titanium dioxide is possibly carcinogenic to humans (Group 2B) based on inadequate evidence in humans and sufficient evidence in experimental animals. This conclusion relates to long-term inhalation exposure to high concentrations of pigmentary (powdered) or ultrafine titanium dioxide. However, no significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints. The available human studies do not suggest an association between occupational exposure to titanium dioxide and risk for cancer.

The American Conference of Governmental Industrial Hygienists (ACGIH) has designated this chemical as not classifiable as a human carcinogen (A4).

The US National Toxicology Program (NTP) has not listed this chemical in its report on carcinogens.

NFPA Ratings:

Health: 1

Flammability: 0

Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

References

1.) International Agency for Research on Cancer (IARC). Volume 93: Carbon Black, Titanium Dioxide, and Talc; (5. Summary of data reported). IARC, 2010. Available at: <<http://monographs.iarc.fr/ENG/Monographs/vol93/mono93.pdf>>

2.) North American Insulation Manufacturer's Association (NAIMA). Working Smart with Fiber Glass, Rock Wool and Slag Wool Products. NAIMA, 2007. Available at: <<http://insulationinstitute.org/wp-content/uploads/2016/02/N059.pdf>>

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.