



SAFETY DATA SHEET

1. Identification

| | |
|---|--|
| Product identifier | CGC Sheetrock® Brand Total™ Drywall Compound |
| Other means of identification | |
| SDS number | 61001010021 |
| Synonyms | Joint Compound (Ready-Mixed), Taping Compound, Mud, Finishing Compound |
| Recommended use | Interior use. |
| Recommended restrictions | Use in accordance with manufacturer's recommendations. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Company name | CGC Inc. |
| Address | 735 Fourth Line Oakville, ON L6L 5B7 A Subsidiary of USG Corporation |
| Telephone | (English) 1-800-387-2690 (Francais) 1-800-361-1310 |
| Website | www.cgcinc.com |
| Emergency phone number | 1-800-507-8899 |

2. Hazard(s) identification

| | |
|---------------------------------|--|
| Physical hazards | Not classified. |
| Health hazards | Not classified. |
| Environmental hazards | Not classified. |
| Label elements | |
| Hazard symbol | None. |
| Signal word | None. |
| Hazard statement | None. |
| Precautionary statements | |
| Prevention | Observe good industrial hygiene practices. |
| Response | Get medical attention/advice if you feel unwell. |
| Storage | Store as indicated in Section 7. |
| Disposal | Dispose of in accordance with federal, provincial and local regulations. |
| Other hazards | None known. |
| Supplemental information | Not applicable. |

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|----------------------|-------------------|----------|
| Perlite | 93763-70-3 | < 15 |
| Kaolin | 1332-58-7 | < 10 |
| Attapulgite | 12174-11-7 | < 5 |

| | |
|-----------------------------|--|
| Composition comments | All concentrations are in percent by weight unless ingredient is a gas. Raw materials in this product contain respirable crystalline silica as an impurity. Independent, third party industrial hygiene testing of this product and its constituents suggests that under normal conditions the expected use of this product will not result in exposure to respirable crystalline silica that exceeds the OSHA PEL (which is equivalent to the Quebec OEL of 0.05 mg/m ³). However, actual exposures to respirable crystalline silica on a given jobsite must be determined by workplace hygiene testing. |
|-----------------------------|--|

4. First-aid measures

| | |
|-------------------|--|
| Inhalation | Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist. |
|-------------------|--|

| | |
|---|--|
| Skin contact | Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists. |
| Eye contact | Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance. |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | Under normal conditions of intended use, this material does not pose a risk to health. Dust may irritate throat and respiratory system and cause coughing. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. |
| General information | Ensure that medical personnel are aware of the material(s) involved. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Use fire-extinguishing media appropriate for surrounding materials. |
| Unsuitable extinguishing media | Not applicable. |
| Specific hazards arising from the chemical | Not a fire hazard. |
| Special protective equipment and precautions for firefighters | Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | Use standard firefighting procedures and consider the hazards of other involved materials. |
| Specific methods | Cool material exposed to heat with water spray and remove it if no risk is involved. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | See Section 8 of the SDS for Personal Protective Equipment. |
| Methods and materials for containment and cleaning up | Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, provincial, and federal regulations. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |
| Environmental precautions | Avoid discharge to drains, sewers, and other water systems. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Avoid inhalation of dust and contact with skin and eyes. Minimise dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques. |
| Conditions for safe storage, including any incompatibilities | Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a mouldy appearance or an unpleasant odour. Keep containers closed when not in use. Filled cartons and pails of joint compound may be stacked a maximum of 3 layers high on a pallet. Pallets may only be stacked a maximum of two high. |

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|------------------------|------|---------------------|----------------------|
| Kaolin (CAS 1332-58-7) | TWA | 2 mg/m ³ | Respirable fraction. |

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

| Components | Type | Value | Form |
|------------------------|------|---------------------|-------------|
| Kaolin (CAS 1332-58-7) | TWA | 2 mg/m ³ | Respirable. |

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

| Components | Type | Value | Form |
|------------------------|-------------|--------------|-------------|
| Kaolin (CAS 1332-58-7) | TWA | 2 mg/m3 | Respirable. |

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

| Components | Type | Value | Form |
|------------------------|-------------|--------------|----------------------|
| Kaolin (CAS 1332-58-7) | TWA | 2 mg/m3 | Respirable fraction. |

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

| Components | Type | Value | Form |
|--------------------------|-------------|--------------|----------------------|
| Kaolin (CAS 1332-58-7) | TWA | 2 mg/m3 | Respirable fraction. |
| Perlite (CAS 93763-70-3) | TWA | 10 mg/m3 | |

Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment)

| Components | Type | Value | Form |
|------------------------------|-------------|--------------|------------------|
| Attapulgite (CAS 12174-11-7) | TWA | 1 fibers/cm3 | Fiber. |
| Kaolin (CAS 1332-58-7) | TWA | 5 mg/m3 | Respirable dust. |

| | |
|--|--|
| Biological limit values | No biological exposure limits noted for the ingredient(s). |
| Appropriate engineering controls | Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimise the risk of exposure. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Wear approved safety goggles. |
| Skin protection | |
| Hand protection | It is a good industrial hygiene practice to minimise skin contact. For prolonged or repeated skin contact use suitable protective gloves. |
| Other | Normal work clothing (long sleeved shirts and long pants) is recommended. |
| Respiratory protection | If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure air supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. |
| Thermal hazards | None. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements. |

9. Physical and chemical properties

Appearance

| | |
|--|------------------|
| Physical state | Semi-solid. |
| Form | Paste. |
| Colour | Off-white. |
| Odour | Low to no odour. |
| Odour threshold | Not applicable. |
| pH | 9.5 - 9.9 |
| Melting point/freezing point | Not applicable. |
| Initial boiling point and boiling range | Not applicable. |
| Flash point | Not applicable. |
| Evaporation rate | Not applicable. |
| Flammability (solid, gas) | Not applicable. |

Upper/lower flammability or explosive limits

| | |
|--------------------------------|-----------------|
| Flammability limit - lower (%) | Not applicable. |
| Flammability limit - upper (%) | Not applicable. |
| Explosive limit - lower (%) | Not applicable. |
| Explosive limit – upper (%) | Not applicable. |

| | |
|---|------------------------------|
| Vapour pressure | Not applicable. |
| Vapour density | Not applicable. |
| Relative density | 0.9 - 1 (H ₂ O=1) |
| Solubility(ies) | |
| Solubility (water) | Soluble in water. |
| Partition coefficient (n-octanol/water) | Not applicable. |
| Auto-ignition temperature | Not applicable. |
| Decomposition temperature | Not applicable. |
| Viscosity | Not applicable. |
| Other information | |
| Bulk density | 0.9 - 1 kg/l |
| VOC (Weight %) | 4 g/l |

10. Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerisation does not occur. |
| Conditions to avoid | None known. |
| Incompatible materials | None known. |
| Hazardous decomposition products | Above 800°C (1472°F) limestone (CaCO ₃) can decompose to lime (CaO) and release carbon dioxide (CO ₂). |

11. Toxicological information

Information on likely routes of exposure

| | |
|--------------|--|
| Inhalation | Airborne dust may irritate throat and upper respiratory system causing coughing. |
| Skin contact | May cause allergic skin reactions especially in individuals with pre-existing skin disease such as eczema. (See Section 16). |
| Eye contact | Airborne dust may cause mechanical eye irritation. |
| Ingestion | May cause discomfort if swallowed. |

| | |
|--|--|
| Symptoms related to the physical, chemical and toxicological characteristics | Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. |
|--|--|

Information on toxicological effects

| | |
|----------------|--|
| Acute toxicity | Not expected to be a hazard under normal conditions of intended use. |
|----------------|--|

| Components | Species | Test results |
|------------------------|---------|-------------------|
| Kaolin (CAS 1332-58-7) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rat | > 5000 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 2 mg/l, 4 Hours |
| <i>Oral</i> | | |
| LD50 | Rat | > 5000 mg/kg |

| | |
|---|--|
| Skin corrosion/irritation | Prolonged or repeated skin contact may cause drying, cracking, or irritation. |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. |
| Respiratory or skin sensitisation | |
| Respiratory sensitisation | Not a respiratory sensitiser. |
| Skin sensitisation | The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals after repeated contact. For detailed information, see section 16. |
| Germ cell mutagenicity | Data does not suggest that this product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | This product is not expected to increase the risk of cancer. |
| ACGIH Carcinogens | |
| Kaolin (CAS 1332-58-7) | A4 Not classifiable as a human carcinogen. |
| Canada - Manitoba OELs: carcinogenicity | |
| KAOLIN, RESPIRABLE FRACTION (CAS 1332-58-7) | Not classifiable as a human carcinogen. |
| Canada - Quebec OELs: Carcinogen category | |
| Attapulgit (CAS 12174-11-7) | Detected carcinogenic effect in humans. |
| IARC Monographs. Overall Evaluation of Carcinogenicity | |
| Attapulgit (CAS 12174-11-7) | 2B Possibly carcinogenic to humans. 3 Not classifiable as to its carcinogenicity to humans. |
| Reproductive toxicity | Not expected to be a reproductive hazard. |
| Specific target organ toxicity - single exposure | No data available, but none expected. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Prolonged exposure may cause chronic effects. For detailed information, see section 16. |
| Further information | No additional adverse health effects noted. |

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | Species | Test results |
|------------------------|--------------------|---------------------|
| Kaolin (CAS 1332-58-7) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Crustacea | LC50 Daphnia magna | > 1.1 g/l, 48 Hours |

| | |
|--------------------------------------|----------------------------------|
| Persistence and degradability | No data available. |
| Bioaccumulative potential | Bioaccumulation is not expected. |
| Mobility in soil | No data available. |
| Other adverse effects | None expected. |

13. Disposal considerations

| | |
|--|---|
| Disposal instructions | Dispose of in accordance with federal, provincial and local regulations. Recycle responsibly. |
| Local disposal regulations | Dispose of in accordance with local regulations. |
| Hazardous waste code | Not regulated. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. |
| Contaminated packaging | Dispose of in accordance with local regulations. |

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

16. Other information

Issue date 02-May-2016

Revision date 07-May-2024

Version No. 02

Further information Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human exposure per ACGIH.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with eczema.

Crystalline silica: Raw materials in this product contain respirable crystalline silica as an impurity. Independent, third party industrial hygiene testing of this product and its constituents suggests that under normal conditions the expected use of this product will not result in exposure to respirable crystalline silica that exceeds the OSHA PEL (which is equivalent to the Quebec OEL of 0.05 mg/m³). However, actual exposures to respirable crystalline silica on a given jobsite must be determined by workplace hygiene testing.

Bucket NFPA Classification:

Health: 0

Flammability: 1

Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings

Health: 1

Flammability: 0

Instability: 0

NFPA ratings**List of abbreviations**

ACGIH: American Conference of Governmental Industrial Hygienists.
NFPA: National Fire Protection Association.
RTECS: Registry of Toxic Effects of Chemical Substances.

References

Registry of Toxic Effects of Chemical Substances (RTECS)
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
Torben et al. (2001). Environmental and Health Assessment of Substances in Household Detergents and Cosmetic Products.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.