CGC

SAFETY DATA SHEET

1. Identification

Product identifier CGC Synko® Brand Kal-Tex® Ceiling Texture

Other means of identification

SDS number 48001010004
Synonyms Texture
Recommended use Interior use.

Recommended restrictionsUse in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name CGC Inc.

Address 350 Burnhamthorpe Road West, 5th Floor

Mississauga, Ontario L5B 3J1 A Subsidiary of USG Corporation

Telephone1-800-387-2690Websitewww.cgcinc.comEmergency phone number1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

Precautionary statements

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of in accordance with local, provincial, and federal regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

13463-67-7	< 5
13463-67-7	

Impurities	CAS number	%	
Crystalline silica (quartz)	14808-60-7	< 0.25	

CGC Synko® Brand Kal-Tex® Ceiling Texture
932263 Version #: 01 Revision date: - Issue date: 01-February-2016

Composition comments

All concentrations are in percent by weight unless ingredient is a gas.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is < 0.25%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

4. First-aid measures

Inhalation

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.

Skin contact

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or

persists.

Eye contact

Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical

assistance.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Under normal conditions of intended use, this product is not expected to be a health risk. Dust may

irritate throat and respiratory system and cause coughing.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically.

Use fire-extinguishing media appropriate for surrounding materials.

General information Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Not applicable.

Specific hazards arising from

the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods Cool material exposed to heat with water spray and remove it if no risk is involved.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Vacuum up the spilled material. Vacuums used for this purpose should be equipped with HEPA filters. Containers must be labeled. Collect in approved containers and seal securely. For waste

disposal, see Section 13 of the SDS.

Issue date: 01-February-2016

Avoid discharge to drains, sewers, and other water systems. **Environmental precautions**

7. Handling and storage

Precautions for safe handling

Minimize dust production when mixing, sanding, or opening and closing bags. Avoid inhalation of dust. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices and use appropriate lifting techniques.

Conditions for safe storage. including any incompatibilities Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Avoid contact with acids, water, and moisture.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

932263 Version #: 01 Revision date: -

Components	Туре	Value	Form
Dust	TWA	3 mg/m3 10 mg/m3	Respirable particles. Inhalable particles.

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Impurities	Туре	Value	Form
Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	Form
Dust	TWA	3 mg/m3	Respirable particles.
		10 mg/m3	Total particulate.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Impurities	Туре	Value	Form
Crystalline silica (quartz)	TWA	0.025 mg/m3	Respirable particles.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Dust	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Impurities	Туре	Value	Form
Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Impurities	Туре	Value	Form

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Dust	TWA	3 mg/m3 10 mg/m3	Respirable particles. Inhalable
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Impurities	Туре	Value	Form
Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.

Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	Form
Dust	TWA	10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.
Impurities	Туре	Value	Form
Crystalline silica (quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering Provide sufficient ventilation for operations causing dust formation. Observe occupational

exposure limits and minimise the risk of exposure. controls

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

It is a good industrial hygiene practice to minimise skin contact. For prolonged or repeated skin Hand protection

contact use suitable protective gloves.

Normal work clothing (long sleeved shirts and long pants) is recommended. Other

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure air supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator

use.

None. Thermal hazards

Always observe good personal hygiene measures, such as washing after handling the material General hygiene and before eating, drinking, and/or smoking. Routinely wash work clothing and protective considerations

equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Solid. Physical state Powder. **Form** Off-white. Colour

Low to no odour. Odour **Odour threshold** Not applicable.

pН 7.5 - 9.9

Melting point/freezing point Not applicable. Initial boiling point and boiling

range

Not applicable.

Flash point Not applicable. Not applicable. **Evaporation rate** Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

(%)

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%) Not applicable. Explosive limit - upper

Not applicable.

(%)

Vapour pressure Not applicable. Vapour density Not applicable. Relative density 0.6 - 0.7 (H2O=1)

Solubility(ies)

Soluble in water. Solubility (water) Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable. **Decomposition temperature** Not applicable. **Viscosity** Not applicable.

Other information

Bulk density 0.6 - 0.7 kg/l

VOC (Weight %) 0 q/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerisation does not occur.

reactions Conditions to avoid

Contact with incompatible materials.

Incompatible materials Acids. Exposure to water and acids must be supervised because the reactions are vigorous and

produce large amounts of heat. Crystalline silica in contact with powerful oxidizing agents, such as fluorine, chlorine trifluoride and oxygen difluoride, may cause fires. Crystalline silica will dissolve in

hydrofluoric acid and produce a corrosive gas, silicon tetrafluoride.

Hazardous decomposition

products

Above 800°C (1472°F) limestone (CaCO3) can decompose to lime (CaO) and release carbon

dioxide (CO2).

11. Toxicological information

Information on likely routes of exposure

Inhalation Inhalation of dusts may cause respiratory irritation. Prolonged and repeated exposure to airborne

respirable crystalline silica can cause silicosis and/or lung cancer.

Under normal conditions of intended use, this product does not pose a skin hazard. Skin contact

Direct contact with airborne particulates may cause temporary irritation. Eye contact

Ingestion may cause irritation and stomach discomfort. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing.

Information on toxicological effects

Not expected to be a hazard under normal conditions of intended use. **Acute toxicity**

Species **Test results** Components

Titanium dioxide (CAS 13463-67-7)

Acute Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Not a skin irritant.

Serious eye damage/eye

Skin sensitisation

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Titanium dioxide (CAS 13463-67-7) Irritant

Respiratory sensitisation Not a respiratory sensitiser.

Data does not suggest that this product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Not a skin sensitiser.

Carcinogenicity Repeated and prolonged exposures to high levels of respirable crystalline silica may cause

cancer.

Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is

based on inadequate evidence of carcinogenicity in humans and sufficient evidence in

experimental animals.

ACGIH Carcinogens

Crystalline silica (quartz) (CAS 14808-60-7) A2 Suspected human carcinogen.

CGC Synko® Brand Kal-Tex® Ceiling Texture 932263 Version #: 01 Revision date: -Issue date: 01-February-2016

^{*} Estimates for product may be based on additional component data not shown.

Titanium dioxide (CAS 13463-67-7) A4 Not classifiable as a human carcinogen.

Canada - Alberta OELs: Carcinogen category

Crystalline silica (quartz) (CAS 14808-60-7) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

SILICA, CRYSTALLINE-.ALPHA.-QUARTZ, Suspected human carcinogen.

RESPIRABLE FRACTION (CAS 14808-60-7)

Titanium dioxide (CAS 13463-67-7) Not classifiable as a human carcinogen.

Canada - Quebec OELs: Carcinogen category

Crystalline silica (quartz) (CAS 14808-60-7) Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

No data available, but none expected.

Reproductive toxicity Not expected to be a reproductive hazard.

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

Not classified. For detailed information, see section 16.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged and routine inhalation of high levels of respirable crystalline silica particles can lead to

the lung disease known as silicosis. Some studies show excess numbers of cases of

scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and end-stage kidney disease in workers exposed to respirable crystalline silica. Pre-existing skin and respiratory conditions including dermatitis, asthma and chronic lung disease might be aggravated by exposure. Occupational exposure to respirable dust and respirable crystalline silica should be

monitored and controlled.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability Not applicable.

Bioaccumulative potential Bioaccumulation is not expected.

Mobility in soil No data available. Other adverse effects None expected.

13. Disposal considerations

Dispose of in accordance with federal, provincial and local regulations. Recycle responsibly. **Disposal instructions**

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product has been classified in accordance with the hazard criteria of the HPR and the SDS Canadian regulations

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

CGC Synko® Brand Kal-Tex® Ceiling Texture 932263 Version #: 01 Revision date: -Issue date: 01-February-2016

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

16. Other information

Issue date 01-February-2016

Revision date

Version No. 01

Further information Crystalline silica: Raw materials in this product may contain respirable crystalline silica.

Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis)

and/or lung cancer.

Titanium dioxide: In lifetime inhalation studies of experimental rats, airborne nano-sized (15-40 nanometer particle size range) particles caused lung tissue overload, chronic inflammation and subsequent tumor formation. Because of these study results, titanium dioxide was classified by IARC as a 2B (possibly carcinogenic to humans). However, other laboratory animals such as mice and hamsters did not develop lung tumors under similar testing conditions. Furthermore, results of two major human epidemiology studies among titanium dioxide workers in the US and in Europe did not demonstrate an elevated lung cancer risk, and did not suggest an association between occupational exposure to titanium dioxide and risk for cancer. The titanium dioxide contained in this product is embedded, and generation of airborne nano-sized titanium dioxide particles is not expected.

NFPA Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings Health: 1

Flammability: 0
Instability: 0

NFPA ratings



List of abbreviations ACGIH: American Conference of Governmental Industrial Hygienists.

NFPA: National Fire Protection Association.

References Registry of Toxic Effects of Chemical Substances (RTECS)

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Torben et al. (2001). Environmental and Health Assessment of Substances in Household

Detergents and Cosmetic Products.

Disclaimer This information is provided without warranty. The information is believed to be correct. This

information should be used to make an independent determination of the methods to safeguard

workers and the environment.