SAFETY DATA SHEET

1. Identification

Product identifier CGC Synko® Brand Lite Joint™ Drywall Compound

Other means of identification

SDS number 61001010016

Synonyms Joint Compound (Ready-Mixed), Taping Compound, Mud, Finishing Compound

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

CGC Inc. Company name

Address 735 Fourth Line

Oakville, ON L6L 5B7

A Subsidiary of USG Corporation

(English) 1-800-387-2690 (Francais) 1-800-361-1310 **Telephone**

Website www.cgcinc.com 1-800-507-8899 **Emergency phone number**

2. Hazard(s) identification

Physical hazards Not classified. **Health hazards** Not classified. **Environmental hazards** Not classified.

Label elements

None. Hazard symbol Signal word None. Hazard statement None.

Precautionary statements

Observe good industrial hygiene practices. Prevention Get medical attention/advice if you feel unwell. Response

Store as indicated in Section 7. Storage

Dispose of in accordance with local, provincial, and federal regulations. Disposal

Other hazards None known. Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Perlite	93763-70-3	< 10
Attapulgite	12174-11-7	< 5
Magnesium carbonate	546-93-0	< 5

Composition comments All concentrations are in percent by weight unless ingredient is a gas.

> Raw materials in this product contain respirable crystalline silica as an impurity. Independent, third party industrial hygiene testing of this product and its constituents suggests that under normal conditions the expected use of this product will not result in exposure to respirable crystalline silica that exceeds the OSHA PEL (which is equivalent to the Quebec OEL of 0.05 mg/m3). However, actual exposures to respirable crystalline silica on a given jobsite must be determined by workplace hygiene testing.

SDS Canada 932278 Version #: 02 Revision date: 23-May-2024 Issue date: 11-February-2016 1/6

4. First-aid measures

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move

injured person into fresh air and keep person calm under observation. Get medical attention if

Under normal conditions of intended use, this material does not pose a risk to health. Dust may

symptoms persist.

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or Skin contact

Eve contact Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical

irritate throat and respiratory system and cause coughing.

assistance.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Not applicable.

Specific hazards arising from

the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in

case of fire.

Fire fighting

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods

Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, provincial, and federal regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

remove residual contamination.

Avoid discharge to drains, sewers, and other water systems. **Environmental precautions**

7. Handling and storage

Precautions for safe handling Avoid inhalation of dust and contact with skin and eyes. Minimise dust generation and

accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe

good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a mouldy appearance or an unpleasant odour. Keep containers closed when not in use.

Filled cartons and pails of joint compound may be stacked a maximum of 3 layers high on a pallet. Pallets may only be stacked a maximum of two high.

2/6

8. Exposure controls/personal protection

932278 Version #: 02 Revision date: 23-May-2024

Occupational exposure limits

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Magnesium carbonate (CAS 546-93-0)	TWA	10 mg/m3	Total dust.

CGC Synko® Brand Lite Joint™ Drywall Compound SDS Canada

Issue date: 11-February-2016

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Perlite (CAS 93763-70-3)	TWA	10 mg/m3	

Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	Form
Attapulgite (CAS	TWA	1 fibers/cm3	Fiber.
12174-11-7)			
Magnesium carbonate	TWA	10 mg/m3	Total dust.
(CAS 546-93-0)			

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational

exposure limits and minimise the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

Hand protection It is a good industrial hygiene practice to minimise skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure air supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator

use.

Thermal hazards None.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Semi-solid. Physical state **Form** Paste. Colour Off-white.

Low to no odour. Odour **Odour threshold** Not applicable.

7.5 - 10pН

Melting point/freezing point Not applicable. Initial boiling point and boiling Not applicable.

range

Not applicable. Flash point **Evaporation rate** Not applicable. Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%) Not applicable.

CGC Synko® Brand Lite Joint™ Drywall Compound 932278 Version #: 02 Revision date: 23-May-2024 3/6 Issue date: 11-February-2016

Explosive limit - upper

(%)

Not applicable.

Vapour pressureNot applicable.Vapour densityNot applicable.Relative density1.1 - 1.4 (H2O=1)

Solubility(ies)

Solubility (water) Soluble in water.

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperatureNot applicable.Decomposition temperatureNot applicable.ViscosityNot applicable.

Other information

Bulk density 1.1 - 1.4 kg/l

VOC (Weight %) 4 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoid None known.

Incompatible materials None known.

Hazardous decomposition

products

Above 800°C (1472°F) limestone (CaCO3) can decompose to lime (CaO) and release carbon

dioxide (CO2).

11. Toxicological information

Information on likely routes of exposure

Inhalation Airborne dust may irritate throat and upper respiratory system causing coughing.

Skin contact May cause allergic skin reactions especially in individuals with pre-existing skin disease such as

eczema. (See Section 16).

Eye contact Airborne dust may cause mechanical eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing.

Information on toxicological effects

Acute toxicity

Not expected to be a hazard under normal conditions of intended use.

Skin corrosion/irritation

Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisationThe product contains a small amount of sensitising substance which may provoke an allergic

reaction among sensitive individuals after repeated contact.

For detailed information, see section 16.

Germ cell mutagenicity Data does not suggest that this product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not expected to increase the risk of cancer.

Canada - Quebec OELs: Carcinogen category

Attapulgite (CAS 12174-11-7)

Detected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Attapulgite (CAS 12174-11-7) 2B Possibly carcinogenic to humans.

3 Not classifiable as to its carcinogenicity to humans.

CGC Synko® Brand Lite Joint™ Drywall Compound

932278 Version #: 02 Revision date: 23-May-2024 Issue date: 11-February-2016

4 / 6

Not expected to be a reproductive hazard. Reproductive toxicity

Specific target organ toxicity -

single exposure

No data available, but none expected.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects. For detailed information, see section 16.

Further information No additional adverse health effects noted.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data available.

Bioaccumulative potential

Bioaccumulation is not expected.

No data available. Mobility in soil Other adverse effects None expected.

13. Disposal considerations

Dispose of in accordance with federal, provincial and local regulations. Recycle responsibly. **Disposal instructions**

Local disposal regulations

Dispose of in accordance with local regulations.

Hazardous waste code

Not regulated.

Not applicable.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging

Dispose of in accordance with local regulations.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

CGC Synko® Brand Lite Joint™ Drywall Compound SDS Canada 932278 Version #: 02 Revision date: 23-May-2024 5/6 Issue date: 11-February-2016

Basel Convention

Not applicable.

16. Other information

Issue date 11-February-2016 Revision date 23-May-2024

Version No.

Further information Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human

exposure per ACGIH.

eczema.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with

Crystalline silica: Raw materials in this product contain respirable crystalline silica as an impurity. Independent, third party industrial hygiene testing of this product and its constituents suggests that under normal conditions the expected use of this product will not result in exposure to respirable crystalline silica that exceeds the OSHA PEL (which is equivalent to the Quebec OEL of 0.05 mg/ m3). However, actual exposures to respirable crystalline silica on a given jobsite must be determined by workplace hygiene testing.

Bucket NFPA Classification:

Health: 0 Flammability: 1 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Health: 1 NFPA ratings

Flammability: 0 Instability: 0

NFPA ratings



List of abbreviations ACGIH: American Conference of Governmental Industrial Hygienists.

NFPA: National Fire Protection Association.

RTECS: Registry of Toxic Effects of Chemical Substances.

Registry of Toxic Effects of Chemical Substances (RTECS) References

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Torben et al. (2001). Environmental and Health Assessment of Substances in Household

Detergents and Cosmetic Products.

Disclaimer This information is provided without warranty. The information is believed to be correct. This

information should be used to make an independent determination of the methods to safeguard

workers and the environment.

SDS Canada 932278 Version #: 02 Revision date: 23-May-2024 6/6 Issue date: 11-February-2016