

# SAFETY DATA SHEET

# 1. Identification

Product identifier	HYDROCAL® FGR Gypsum Cements
Other means of identification	
SDS number	5200000017
Additional Products	HYDROCAL® FGR-95, HYDROCAL® FGR 95-LE
Recommended use	Architectural Hand or Spray Layup.
Recommended restrictions	Use in accordance with manufacturer's recommendations.
Manufacturer/Importer/Supplier/	Distributor information
Manufacturer	United States Gypsum Company
Address	550 West Adams Street
	Chicago, Illinois 60661-3637
Telephone	1-800-874-4968
Website	www.usg.com
Emergency phone number	1-800-507-8899
Supplier	CGC Inc.
Address	350 Burnhamthorpe Road West, 5th Floor
Address	Mississauga, Ontario L5B 3J1
	A Subsidiary of USG Corporation
Telephone	1-800-387-2690
Website	www.cgcinc.com
Emergency phone number	1-800-507-8899
2. Hazard identification	
Physical hazards	Not classified.
-	
Health hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	None.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	Get medical attention/advice if you feel unwell.
Storage	Store as indicated in Section 7.
Disposal	Dispose of in accordance with local, state, and federal regulations.
Other hazards	None known.
Supplemental information	None.
	u en la una die née

# 3. Composition/information on ingredients

<i>l</i> ixtures Chemical name	Common name and synonyms	CAS number	%
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1)		26499-65-0	80 - 100

**Composition comments** 

All concentrations are in percent by weight.

#### 4. First-aid measures

4. First-alu measures	
Inhalation	Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.
Skin contact	Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.
Eye contact	Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.
Ingestion	Plaster of Paris hardens and if ingested may result in stomach and intestinal blockage. Drinking gelatin solutions or large volumes of water may delay setting.
Most important symptoms/effects, acute and delayed	Under normal conditions of intended use, this product is not expected to be a health risk. Dust may irritate throat and respiratory system and cause coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved.
5. Fire-fighting measures	
Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Not applicable.
Specific hazards arising from the chemical	Not a fire hazard.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials.
Specific methods	Cool material exposed to heat with water spray and remove it if no risk is involved.
General fire hazards	No unusual fire or explosion hazards noted.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	Vacuum up the spilled material. Vacuums used for this purpose should be equipped with HEPA filters. Containers must be labeled. Collect in approved containers and seal securely. For waste disposal, see Section 13 of the SDS.
Environmental precautions	Avoid discharge to drains, sewers, and other water systems.
7. Handling and storage	
Precautions for safe handling	Minimize dust production when mixing, or opening and closing bags. Avoid inhalation of dust.

Precautions for safe handling
 Minimize dust production when mixing, or opening and closing bags. Avoid inhalation of dust.
 Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices and use appropriate lifting techniques.
 Conditions for safe storage,
 Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Avoid contact

**Conditions for safe storage,** Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Avoid contact with acids, water, and moisture.

## 8. Exposure controls/personal protection

#### **Occupational exposure limits**

US. ACGIH Threshold Limit Values Components	Туре	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	10 mg/m3	Inhalable fraction.

Components	Туре	edule 1, Table 2) Value	
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	10 mg/m3	
Canada. British Columbia ( Safety Regulation 296/97, a	DELs. (Occupational Exposure Limits is amended)	for Chemical Substances, O	ccupational Health and
Components	Туре	Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	STEL	20 mg/m3	Total dust.
	TWA	10 mg/m3	Inhalable
Canada. Manitoba OELs (R Components	eg. 217/2006, The Workplace Safety A Type	nd Health Act) Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	10 mg/m3	Inhalable fraction.
Canada. Ontario OELs. (Co Components	ntrol of Exposure to Biological or Che Type	emical Agents) Value	Form
Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	TWA	10 mg/m3	Inhalable fraction.
Canada. Quebec OELs. (Mi Components	nistry of Labor - Regulation respectin Type	g occupational health and sa Value	afety) Form
			• ·
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS	Туре	Value	Form
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	Туре	Value 5 mg/m3 10 mg/m3	Form Respirable dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE	Type TWA Ls (Occupational Health and Safety R	Value 5 mg/m3 10 mg/m3 egulations, 1996, Table 21)	Form Respirable dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS	Type TWA Ls (Occupational Health and Safety R Type	Value 5 mg/m3 10 mg/m3 egulations, 1996, Table 21) Value	Form Respirable dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0)	Type TWA Ls (Occupational Health and Safety R Type 15 minute	Value           5 mg/m3           10 mg/m3           egulations, 1996, Table 21)           Value           20 mg/m3           10 mg/m3	Form Respirable dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) logical limit values	Type TWA Ls (Occupational Health and Safety R Type 15 minute 8 hour	Value           5 mg/m3           10 mg/m3           egulations, 1996, Table 21)           Value           20 mg/m3           10 mg/m3	Form Respirable dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) ogical limit values osure guidelines propriate engineering	Type TWA Ls (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo	Value         5 mg/m3         10 mg/m3         egulations, 1996, Table 21)         Value         20 mg/m3         10 mg/m3         r the ingredient(s).         tions causing dust formation.	Form Respirable dust. Total dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Cogical limit values osure guidelines propriate engineering trols	Type TWA Ls (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo No exposure standards allocated. Provide sufficient ventilation for opera exposure limits and minimise the risk , such as personal protective equipment	Value         5 mg/m3         10 mg/m3         egulations, 1996, Table 21)         Value         20 mg/m3         10 mg/m3         r the ingredient(s).         tions causing dust formation. of exposure.	Form Respirable dust. Total dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Cogical limit values osure guidelines propriate engineering trols	Type         TWA         Ls (Occupational Health and Safety R         Type         15 minute         8 hour         No biological exposure limits noted fo         No exposure standards allocated.         Provide sufficient ventilation for operal exposure limits and minimise the risk	Value         5 mg/m3         10 mg/m3         egulations, 1996, Table 21)         Value         20 mg/m3         10 mg/m3         r the ingredient(s).         tions causing dust formation. of exposure.	Form Respirable dust. Total dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Ogical limit values osure guidelines propriate engineering trols vidual protection measures Eye/face protection Skin protection	Type         TWA         Ls (Occupational Health and Safety R         Type         15 minute         8 hour         No biological exposure limits noted fo         No exposure standards allocated.         Provide sufficient ventilation for operation exposure limits and minimise the risk         , such as personal protective equipment         Wear approved safety goggles.	Value         5 mg/m3         10 mg/m3         egulations, 1996, Table 21)         Value         20 mg/m3         10 mg/m3         r the ingredient(s).         attions causing dust formation. Gof exposure.         ent	Form Respirable dust. Total dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) ogical limit values osure guidelines propriate engineering trols vidual protection measures Eye/face protection	Type TWA Ls (Occupational Health and Safety R Type 15 minute 8 hour No biological exposure limits noted fo No exposure standards allocated. Provide sufficient ventilation for opera exposure limits and minimise the risk , such as personal protective equipment	Value         5 mg/m3         10 mg/m3         egulations, 1996, Table 21)         Value         20 mg/m3         10 mg/m3         r the ingredient(s).         ations causing dust formation. Gof exposure.         ent         e to minimise skin contact. For	Form Respirable dust. Total dust.
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) logical limit values oropriate engineering trols vidual protection measures Eye/face protection Skin protection	Type         TWA         Ls (Occupational Health and Safety R         Type         15 minute         8 hour         No biological exposure limits noted fo         No exposure standards allocated.         Provide sufficient ventilation for opera exposure limits and minimise the risk         , such as personal protective equipmed Wear approved safety goggles.         It is a good industrial hygiene practice	Value         5 mg/m3         10 mg/m3         egulations, 1996, Table 21)         Value         20 mg/m3         10 mg/m3         r the ingredient(s).         tions causing dust formation. Go exposure.         ent         e to minimise skin contact. For	Form Respirable dust. Total dust. Dbserve occupational prolonged or repeated skir
Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) Canada. Saskatchewan OE Components Plaster of Paris (Calcium Sulfate Hemihydrate CAS 10034-76-1) (CAS 26499-65-0) logical limit values osure guidelines propriate engineering trols vidual protection measures Eye/face protection Skin protection Hand protection	Type         TWA         Ls (Occupational Health and Safety R         Type         15 minute         8 hour         No biological exposure limits noted fo         No exposure standards allocated.         Provide sufficient ventilation for opera         exposure limits and minimise the risk         , such as personal protective equipmed         Wear approved safety goggles.         It is a good industrial hygiene practice         contact use suitable protective gloves	Value         5 mg/m3         10 mg/m3         egulations, 1996, Table 21)         Value         20 mg/m3         10 mg/m3         r the ingredient(s).         ations causing dust formation. Gof exposure.         ent         at to minimise skin contact. For         nirts and long pants) is recommendation beloeptable level (in countries when	Form Respirable dust. Total dust. Dbserve occupational prolonged or repeated skin nended. w recommended exposure

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

### 9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Powder.
Colour	White to off-white.
Odour	Low to no odour.
Odour threshold	Not applicable.
pН	6 - 8
Melting point/freezing point	Not applicable. Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower ( %)	Not applicable.
Explosive limit – upper (%)	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	2.96 (H2O=1)
Solubility(ies)	
Solubility (water)	0.15 - 0.4 g/100 g (H2O)
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	1450 °C (2642 °F)
Viscosity	Not applicable.
Other information	
Bulk density	55 - 70 lb/ft³
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Particle size	Varies.
VOC	Not applicable.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Conditions to avoid	When mixed with water this product can become very hot. Encasing or making moulds of any body part can cause serious burns that may require surgical removal of affected tissue and even amputation of encased body part.
Incompatible materials	Acids.

# 11. Toxicological information

#### Information on likely routes of exposure

Inhalation	Airborne dust may irritate throat and upper respiratory system causing coughing.
Skin contact	Under normal conditions of intended use, this product does not pose a skin hazard.
Eye contact	Direct contact with airborne particulates may cause temporary irritation.
Ingestion	Ingestion may cause irritation and stomach discomfort.
Symptoms related to the physical, chemical and toxicological characteristics	Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing.
Information on toxicological effe	ects
Acute toxicity	Not expected to be a hazard under normal conditions of intended use.
Skin corrosion/irritation	Not a skin irritant.

Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitisation	
<b>Respiratory sensitisation</b>	Not expected to cause respiratory sensitization based on non-skin sensitization history.
Skin sensitisation	Not a skin sensitiser. Plaster of Paris has displayed little sensitization potential.
Germ cell mutagenicity	No evidence of mutagenicty found in Ames bacterial tests.
Carcinogenicity	Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Not expected to be a reproductive hazard.
Specific target organ toxicity - single exposure	No data available, but none expected.
Specific target organ toxicity - repeated exposure	No data available, but none expected.
Aspiration hazard	Not an aspiration hazard.

No other specific acute or chronic health impact noted.

Chronic effects

#### 12. Ecological information

Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
Plaster of Paris (Calcium Su	lfate Hemihydi	ate CAS 10034-76-1) (CAS	26499-65-0)
Aquatic			
Fish	LC50	Fathead minnow (Pime	phales promelas) > 1970 mg/l, 96 hours
Persistence and degradability	Calcium su	Ifate dissolves in water forn	ning calcium and sulfate ions.
Bioaccumulative potential	Bioaccumu	lation is not expected.	
Mobility in soil	No data av	ailable.	
Other adverse effects	None expe	cted.	

#### 13. Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

## 14. Transport information

#### TDG

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to** Annex II of MARPOL 73/78 and

the IBC Code

## 15. Regulatory information

#### **Canadian regulations**

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Not regulated. Export Control List (CEPA 1	999. Schedule 3)	
Not listed.		
Greenhouse Gases		
Not listed.		
Precursor Control Regulatio	ons	
Not regulated.		
ernational regulations		
Stockholm Convention		
Not applicable.		
Rotterdam Convention		
Not applicable.		
Kyoto Protocol		
Not applicable. Montreal Protocol		
Not applicable.		
<b>Basel Convention</b>		
Not applicable.		
ernational Inventories		
Country(s) or region	Inventory name	On inventory (yes/r
Australia	Australian Inventory of Chemical Substances (AICS)	
Canada	Domestic Substances List (DSL)	
Canada	Non-Domestic Substances List (NDSL)	
China	Inventory of Existing Chemical Substances in China (IECSC)	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	
Europe	European List of Notified Chemical Substances (ELINCS)	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	
Korea	Existing Chemicals List (ECL)	
New Zealand	New Zealand Inventory	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	
	Taiwan Chemical Substance Inventory (TCSI)	
Taiwan		

# 16. Other information

Issue date	21-April-2020
Revision date	-
HYDROCAL® FGR Gypsum Cements	

Version No.	01
Further information	Plaster of Paris: Is classified as a hazardous substance but is generally considered a safe material for routine use. When plaster of Paris is used responsibly it is not considered as a dangerous material. However, when mixed with water this product can become very hot. DO NOT attempt to make a cast enclosing any part of the body. Encasing any body part can cause serious burns and even amputation of the encased body part.
	NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0
	Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe
Disclaimer	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.