Version number: 04



SAFETY DATA SHEET

SECTION 1. Identification of the hazardous chemical substance or mixture and of the supplier or manufacturer

Name of the hazardous Redimix® All Purpose Joint Compound

chemical substance or mixture

Other means of identification Common name(s),

Joint Compound (Ready-Mixed), Taping Compound, Mud, Finishing Compound

synonym(s)

SDS number 61000110001

Recommended use of the hazardous chemical substance or mixture, and restrictions of use

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Suppliers details

Manufacturer USG México S.A. de C.V.

Address Av. Vasco de Quiroga #4800, piso 5, oficina 501

Santa Fe, Cuajimalpa (de Morelos, CP) 05348

Ciudad de México

Telephone +(52 55) 5261 6300

Website www.usg.com
Emergency phone number 01 800 8740737

SECTION 2. Hazard identification

Classification of the substance or mixture

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

Elements of labeling, including precautionary statements and warning pictograms

Hazard symbolsNone.Signal wordNone.Hazard statementNone.

Precautionary statement

PreventionObserve good industrial hygiene practices.ResponseGet medical attention/advice if you feel unwell.

Storage Store as indicated in Section 7.

Disposal Dispose of in accordance with local, state, and federal regulations.

Other hazards which do not

result in classification

None known.

Supplemental information None.

SECTION 3. Composition/information on ingredients

Mixtures

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
Limestone		1317-65-3	> 65
Attapulgite		12174-11-7	< 5
1,3,5-tris(2-hydroxyethyl)hexah ydro-1,3,5-triazine		4719-04-4	< 0.25

SDS Mexico

Version number: 04

Composition comments

All concentrations are in percent by weight.

Industrial hygiene studies by USG Corporation and governmental agencies did not detect airborne respirable crystalline silica above US OSHA permissible exposure limits (PELs) during activities associated with the normal use of this product, though in some cases total dust PELs were exceeded. However, job site air monitoring should be conducted to determine actual exposure when PELs may be exceeded.

SECTION 4. First-aid measures

Description of necessary first-aid measures

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move Inhalation

injured person into fresh air and keep person calm under observation. Get medical attention if

Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing. May cause allergic skin disorders in sensitive individuals.

symptoms persist.

Skin contact Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or

persists.

Eye contact Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical

assistance.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved.

Use fire-extinguishing media appropriate for surrounding materials.

SECTION 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

General information

media

Specific hazards arising from

the chemical

firefighters

Special protective actions for

Not a fire hazard.

Not applicable.

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in

Use standard firefighting procedures and consider the hazards of other involved materials.

case of fire

Fire fighting

equipment/instructions

General fire hazards This product is not flammable.

Specific methods Cool material exposed to heat with water spray and remove it if no risk is involved.

SECTION 6. Measures that must be taken in the event of accidental spillage or an accidental leak

Personal precautionary measures, protective equipment and emergency procedure

For non-emergency

personnel

Wear appropriate personal protective equipment.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the

SDS.

Environmental precautions

Methods and materials for containing and cleaning up

spills or releases

Avoid discharge to drains, sewers, and other water systems.

Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, state, and federal regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

SECTION 7. Handling and storage

Precautions for safe handling

Avoid inhalation of dust and contact with skin and eyes. Minimize dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.

SDS Mexico Redimix® All Purpose Joint Compound

Issue date: 11-December-2014

Issue date: 11-December-2014 Revision date: 06-January-2023 Supersedes date: 27-October-2020 Version number: 04

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

Filled 4.5 gallon pails of joint compound may be stacked a maximum of 3 layers high on a standard 48 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

Filled cartons of joint compound may be stacked a maximum of 3 layers high on a standard 42 x 42 or 42 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

SECTION 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits No exposure limits noted for ingredient(s).

Biological limit values No biological exposure limits noted for the ingredient(s).

Control banding approach Follow standard monitoring procedures.

Appropriate engineering

controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment (PPE)

Wear approved safety goggles. Eye/face protection

Skin protection

Hand protection It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards No protection is ordinarily required under normal conditions of use.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

SECTION 9. Physical and chemical properties

Appearance

Physical state Semi-solid. **Form** Paste

White to off-white. Color Odor Low to no odor. Not applicable. Odor threshold 7.5 - 9.9pН Melting point/freezing point Not applicable.

Initial boiling point and boiling

range

212 °F (100 °C)

Flash point Not applicable. **Evaporation rate** Not applicable. Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%) Not applicable. Not applicable. Explosive limit - upper (%) Vapor pressure Not applicable. Vapor density Not applicable. 1.4 - 1.8 (H2O=1) Relative density

Redimix® All Purpose Joint Compound 923272 Version #: 04

SDS Mexico Revision date: 06-January-2023 Issue date: 11-December-2014

Issue date: 11-December-2014 Revision date: 06-January-2023 Supersedes date: 27-October-2020

Version number: 04

Soluble in water. Solubility(ies) Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable. **Decomposition temperature** Not applicable. **Viscosity** Not applicable.

Other information

Bulk density 12 - 15 lb/gal

VOC 2.0 g/l (Calculated by EPA Method 24)

SECTION 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions that must be

avoided

None known.

Incompatible materials None known.

Hazardous decomposition Above 1472°F (800°C) limestone (CaCO3) can decompose to lime (CaO) and release carbon

dioxide (CO2). products

SECTION 11. Toxicological information

Information about likely routes of entry

Inhalation Airborne dust may irritate throat and upper respiratory system causing coughing.

May cause allergic skin reactions especially in individuals with pre-existing skin disease such as Skin contact

eczema. (See Section 16).

Eye contact Airborne dust may cause mechanical eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing.

Delayed and immediate effects and also chronic effects from short and long term exposure

Numerical measures of toxicity (such as acute toxicity estimates)

Acute toxicity Not expected to be a hazard under normal conditions of intended use. Prolonged or repeated skin contact may cause drying, cracking, or irritation. Skin corrosion/irritation

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization The product contains a small amount of sensitizing substance which may provoke an allergic

reaction among sensitive individuals after repeated contact.

For detailed information, see section 16.

Germ cell mutagenicity Data does not suggest that this product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not expected to increase the risk of cancer.

Reproductive toxicity Not expected to be a reproductive hazard. No data available, but none expected. Specific target organ toxicity -

Specific target organ toxicity -

repeated exposure

single exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

No other specific acute or chronic health impact noted. Other information

Redimix® All Purpose Joint Compound

SDS Mexico 923272 Version #: 04 Revision date: 06-January-2023 Issue date: 11-December-2014

Issue date: 11-December-2014 Revision date: 06-January-2023 Supersedes date: 27-October-2020

Version number: 04

SECTION 12. Ecotoxicological information

Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data available.

Bioaccumulative potential Bioaccumulation is not expected.

Mobility in soilNo data available.Other adverse effectsNone expected.

SECTION 13. Disposal considerations

Disposal methods

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

Waste from residues / unused products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

SECTION 14. Transport information

SCT

Not regulated as dangerous goods.

DOT

Not regulated as dangerous goods.

ADR

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

ADN

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and

the IBC Code

SECTION 15. Regulatory information

Safety, health and environmental regulations specific for the hazard This safety data sheet was prepared in accordance with the Official Mexican Standard

(NOM-018-STPS-2015).

chemical substance or mixture

in question

Mexico. Hazard identification guidance list (NOM-018-STPS)

Limestone (CAS 1317-65-3) Listed.

Mexico. Substances subject to reporting for the pollutant release and transfer registry (PRTR)

Not listed.

International regulations

Montreal Protocol

Not applicable.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Redimix® All Purpose Joint Compound SDS Mexico

Issue date: 11-December-2014

923272 Version #: 04 Revision date: 06-January-2023

Issue date: 11-December-2014 Revision date: 06-January-2023 Supersedes date: 27-October-2020

Version number: 04

Basel Convention

Not applicable.

International Inventories

Country(s) or region Inventory name

On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

. .

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16. Other included information relevant to the preparation and updating of safety data sheets

Revision date

06-January-2023

List of abbreviations

GHS: Globally Harmonized System of Classification and Labeling of Chemicals. SCT: Secretariat of Communications and Transportation (NOM-002-SCT/2011).

DOT: Department of Transportation (49 CFR 172.101).

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

IATA: International Air Transport Association.

IMDG Code: International Maritime Dangerous Goods Code.

MARPOL: International Convention for the Prevention of Pollution from Ships.

NFPA: National Fire Protection Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

References

NOM-047-SSA1-2011 – Workplace Biological Exposure Indices (BEIs) to Chemical Substances

Workplace Threshold Quantities of Hazardous Chemicals

NOM-028-STPS-2012 - Work-Safety Management System for Processes and Critical Equipment

Handling Hazardous Chemical Substances

NOM-018-STPS-2000 - Workplace Hazardous Chemical Substances Communication and

Identification Standard

NOM-010-STPS-2014 (second revision) - Occupational Exposure Limits - becomes effective on

April 28, 2016

Further information

Vinyl acetic monomer, formaldehyde and acetaldehyde: Trace amounts of vinyl acetate monomer and formaldehyde may be found in this product.

Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human exposure per ACGIH.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with

eczema.

Crystalline silica: Raw materials in this product may contain respirable crystalline silica. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



Issue date: 11-December-2014 Revision date: 06-January-2023 Supersedes date: 27-October-2020 Version number: 04

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.