

NOTES:


- Minimum depth of bellow to be equal to the thickness of the Securock ExoAir 430 Panel
- Exact depth of bellow to be determined by anticipated movement
- Overlap 1" of ExoAir Duo using Dymonic 100 when splicing in a proper shingle effect

See securockexoair.com for the most up-to-date product information

This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional

The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.

Rev	Date	Description	By
-	-	-	-

 <p>PERFORMANCE BUILT IN www.securockexoair.com</p>	United States Gypsum Company 550 West Adams Street Chicago, IL 60661 USG Technical & Customer Support: 800.USG.4YOU (874-4968)	Tremco Commercial Sealants & Waterproofing 3735 Green Road Beachwood, OH 44122 Tremco Technical Support: 866.209.2404	SECUROCK® ExoAir® 430 Panel Project: XXXX Detail: Expansion Joint - ExoAir Duo	File Name: 12904 Date: 7/9/2015	Rev # 00
	Drawn by: MI	Approved by: XX	Scale: NTS	Date: 7/9/2015	