

DESIGNER PATTERNS

HIGH-DURABILITY CAST PANELS

USG Sandrift™ R808

TO ORDER SAMPLES, GO TO USG.COM

USG CHEYENNE™ AND USG SANDRIFT™ AVAILABLE COLORS*



Manila
555



Parchment
556



Sandstone
554

USG Arctic™/USG Frost™

USG Sandrift™

USG Cheyenne™/USG Glacier™

FEATURES AND BENEFITS

- ClimaPlus™ panels offer a 30-year limited warranty against sag, mold and mildew.
- Absorb and block sound for balanced acoustics.
- Unique, naturally formed textures.
- Color goes all the way through panel to mask nicks and scratches.

SUBSTRATE

- Cast mineral fiber

PRODUCT SPECIFICATIONS

Pattern	Item No.	Edge	Panel Size	Pcs./ Carton	Sq. Ft./ Carton	Ctns./ Pallet	Fire Rating	Sound Control			Technical Information					
								NRC	CAC	LR	R-Value	VOC	Mold, Mildew & Sag Resistance	Abuse Resistant	Recycled Content	USG Commercial Equivalent
USG ARCTIC™	R414	SLB 	2'x2'x3/4" Paper-Back	8	32	28	Class A 	0.70 	36 	0.84 	1.7	Zero 			72% 	USG Frost™ 414
USG CHEYENNE™	156	SL 	2'x2'x3/4" Paper-Back	8	32	28	Class A	0.65	35	0.70	1.7	Zero	—		72%	USG Glacier™ Basic 707
USG CHEYENNE™ MANILA¹	555	SL 	2'x2'x3/4" Paper-Back	8	32	28	Class A	0.65	35	0.70	1.7	Zero	—		72%	USG Glacier™ Basic 707 Manila
USG CHEYENNE™ PARCHMENT¹	556	SL 	2'x2'x3/4" Paper-Back	8	32	28	Class A	0.65	35	0.70	1.7	Zero	—		72%	USG Glacier™ Basic 707 Parchment
USG CHEYENNE™ SANDSTONE¹	554	SL 	2'x2'x3/4" Paper-Back	8	32	28	Class A	0.65	35	0.70	1.7	Zero	—		72%	USG Glacier™ Basic 707 Sandstone
USG FROST™	419²	FLB 	2'x2'x3/4" Paper-Back	8	32	28	Class A	0.70	38/40 ²	0.84	1.7	Zero			72%	USG Frost™ 419
	489²	FLB 	2'x2'x7/8" Paper-Back	8	32	24	Class A	0.80	38/40 ²	0.89	1.7	Zero			73%	USG Frost™ 489
	491	FLB 	2'x2'x3/4" Paper-Back	8	32	28	Class A	0.75	36	0.89	1.7	Zero			72%	USG Frost™ 491
USG GLACIER™	708	FL 	2'x2'x3/4"	8	32	28	Class A	0.65	35	0.70	1.7	Zero	—		72%	USG Glacier™ Basic 708
USG SANDRIFT™	R808	SL 	2'x2'x3/4"	8	32	28	Class A	0.70	38	0.83	1.7	Zero			72%	USG Sandrift™ 808
	809	FL 	2'x2'x3/4" Paper-Back	8	32	28	Class A	0.70	38	0.83	1.7	Zero			72%	USG Sandrift™ 809
USG SANDRIFT™ MANILA¹	R808	SL 	2'x2'x3/4"	8	32	28	Class A	0.70	38	0.83	1.7	Zero			72%	USG Sandrift™ 808 Manila
USG SANDRIFT™ PARCHMENT¹	R808	SL 	2'x2'x3/4"	8	32	28	Class A	0.70	38	0.83	1.7	Zero			72%	USG Sandrift™ 808 Parchment
USG SANDRIFT™ SANDSTONE¹	R808	SL 	2'x2'x3/4"	8	32	28	Class A	0.70	38	0.83	1.7	Zero			72%	USG Sandrift™ 808 Sandstone

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at productguide.ulenvironment.com

ClimaPlus™ Warranty Performance
Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.



This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete list of all USG ceiling panels on biopreferred.gov website.



GREENGUARD Gold Certification offers stricter certification criteria, considers safety factors to account for sensitive individuals (such as children and the elderly), and ensures a product is acceptable for use in environments such as schools and healthcare facilities. It is referenced by both The Collaborative for High Performance Schools (CHPS) and the Leadership in Energy and Environmental Design (LEED) Building Rating System.

FOOTNOTES

ASTM E84 surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Maintenance
Can be cleaned easily with a soft brush or vacuum.

- Notes**
- USG Cheyenne™ and USG Sandrift™ Color Codes:
– Manila - 246
– Parchment - 103
– Sandstone - 090
 - 419 and 489 achieve 40 CAC when installed with USG Donn® Brand Fineline® or Fineline® 1/8 suspension system.