

# USG DONN® BRAND FINELINE® 1/8 DXFF™ ACOUSTICAL SUSPENSION SYSTEM

USG Donn® Brand Fineline®  
1/8" DXFF™ Acoustical Suspension  
System/USG Eclipse™ Acoustical  
Panels with ClimaPlus™ Performance

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)

#### STANDARD COLOR



Flat White  
050

#### ADVANTAGE COLOR



Coordinating  
Matte White  
3756

#### POWDER-COATED FINISH



Powder  
White 3767


#### FEATURES AND BENEFITS

- Narrow-profile, slotted grid system with 1/8" reveal provides streamlined appearance.
- Reveal accommodates partition attachments and pendant-mounted light fixtures.
- Mitered intersections offer a clean, tailored appearance.
- Complies with all national code requirements.
- Optional integrated air diffuser.
- Custom colors available.
- ICC-ES evaluated for seismic installations (ESR-1222).
- Standard components available in Imperial and Metric sizes.

#### APPLICATIONS

- All interior general-use areas

#### PROFILE



#### EDGE DETAIL



USG Donn® Brand  
Fineline®



USG Donn® Brand  
Fineline® Bevel

# USG DONN® BRAND FINELINE® 1/8 DXFF™ ACOUSTICAL SUSPENSION SYSTEM


ORDER SAMPLES/LITERATURE  
USG: [samplitt@usg.com](mailto:samplitt@usg.com)  
fax: 888 874-2348 | [usg.com](http://usg.com)  
CGC: contact Sales Representative

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
[usgdesignstudio.com](http://usgdesignstudio.com)  
[cgcdesignstudio.com](http://cgcdesignstudio.com)


TECHNICAL SERVICES  
800 USG.4YOU (874-4968)



## 9/16" TEE SYSTEM® Main Tee³



## Cross Tee



ASTM Class	Length	Height	Item No. <sup>3</sup>	Fire Rating	Color <sup>2</sup>	Seismic Design Category		Rated Load <sup>1</sup>			
						IBC	ICC-ES Evaluated Installation	4' Hanger Spacing	5' Hanger Spacing	6' Hanger Spacing	
Intermediate Duty	10'	1-25/32" 45 mm	DXFF2930 	Class A 	Flat White	A-C		7/8" Molding ACM7 Clip	12 lb./LF	6.5 lb./LF	3.6 lb./LF
	12'	1-25/32" 45 mm	DXFF2924 DXFF2948 								
	3600 mm	45 mm	MEDXFF3600 								
Heavy Duty	12'	1-25/32" 42 mm	DXFFH2924 	Class A	Flat White	A-F	7/8" Molding ACM7 Clip	16 lb./LF	8.3 lb./LF	4.9 lb./LF	
	3600 mm	45 mm	MEDXFFH3600 								
	1'	1-25/32"	DXFF129 	Class A	Flat White						
	2'	1-25/32"	DXFF229 								
	30"	1-25/32"	DXFF30 								
	4'	1-25/32"	DXFF429 DXFF429N <sup>4</sup> DXFF429S <sup>5</sup> 								
	5'	1-25/32"	DXFF529 DXFF529N <sup>4,7</sup> 								
	1200 mm	45 mm	MEDXFF1200 MEDXFF1200N <sup>4,7</sup> MEDXFF1200S <sup>5</sup> 								
	600 mm	45 mm	MEDXFF600 								

### High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

## MOLDING®



Wall Angle	Length	Item No.	Color <sup>2</sup>	Wall Angle	Length	Item No.	Color <sup>2</sup>
	12' 3600 mm	M9 	Flat White	Shadowline 	12' 3600 mm	MS174	Flat White

## PHYSICAL DATA/ FOOTNOTES

### Product literature and samples

Data sheet: AC3033  
Sample: 270308

### Material

Min. G30 hot-dipped galvanized steel tee. Baked on polyester paint or powder-coated finish.

### Installation

Install according to ASTM C636, ASTM E580, CISCA and USG requirements. Alternate installation methods may be used when approved by the authority having jurisdiction.

### LA Research Report - RR 25764

Refer to [usg.com](http://usg.com) for most current version.

### Online tools

[usgdesignstudio.com](http://usgdesignstudio.com) or [cgcdesignstudio.com](http://cgcdesignstudio.com)

### ICC Evaluation Service, LLC Report Compliance

For areas under ICC jurisdiction, see ICC-ES Evaluation Report ESR-1222 for allowable values and conditions of use. Reports are subject to reexamination, revision and possible cancellation. Refer to [usg.com](http://usg.com) for most current version.

### ASTM Load Compliance

Classified as Light, Intermediate or Heavy Duty when tested in accordance with ASTM C635.

### Air diffusers

Request AC272.

### Notes

- Load test data shows uniform load in lb./LF based on simple span tests in accordance with ASTM C635 deflection limit on L/360.
- Custom color available.
- Cross-tee notches available in 24" and 30" modules. Standard is 24" o.c.
- N = Notch at midpoint.
- Midpoint notch on one side only to accommodate light fixtures.
- Panels must be field-cut to size at the perimeter.
- Notched 30" o.c.
- Metric sizes listed available with standard lead times. Other metric sizes available by RTQ.

### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

### AC3033/rev. 8-17

© 2017 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CLIMAPLUS, DONN, DXFF, ECLIPSE, FINELINE, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

