

USG DUROCK™ BRAND INTERIOR AND EXTERIOR TAPES

For joint reinforcement of USG Durock® Brand Cement Board, USG Fiberock® Brand Underlayment and Tile Backerboard, and USG Durock™ Brand Glass-Mat Tile Backerboard.

- Alkali-resistant glass-fiber construction
- Reinforces joints and corners of cement board in exterior substrate applications and interior tile or thin-brick applications
- Sizes for interior (2" wide) and exterior (4" wide) joint reinforcement

DESCRIPTION

USG Durock™ Brand Interior and Exterior Tapes are specially designed to reinforce the joints and corners of USG tile backerboard panels. The 2" USG Durock™ Interior Tape is used to reinforce corners and joints of USG tile backerboard panels. USG Durock™ Exterior Tape is 4" wide, and it is the required product for completely covering and reinforcing corners and joints of USG Durock® Cement Board when used as an exterior substrate. USG Durock™ Interior and Exterior Tapes are made of alkali-resistant glass-fiber mesh to provide a strong, long-lasting joint.

DIRECTIONS - INTERIOR

APPLICATIONS OF TILE AND THIN BRICK FINISHES

For USG Durock® Cement Board. Following application of USG Durock® Cement Board, prefill joints between panels of USG Durock® Cement Board with tile-setting mortar or adhesive. Center USG Durock™ Interior Tape over all joints and corners and embed in mortar or adhesive. Do not overlap pieces of the tape. Level the joints. For small areas where the USG Durock® Cement Board will not be tiled, such as a board extending beyond the tiled area and abutting another surface, treat joints as follows; seal USG Durock® Cement Board with Type 1 ceramic tile adhesive (mix four parts adhesive with one part water). Embed USG Sheetrock® Brand Joint Tape over joints and treat fasteners with USG Sheetrock® Brand Durabond® 45 or 90 Setting-Type Joint Compound applied in a conventional manner. Flat trowel USG Sheetrock® Brand Durabond Setting-Type Joint Compound over board to cover fasteners and fill voids to a smooth surface. Finish joints with at least two coats of USG Sheetrock® Brand Ready-Mixed Joint Compound. Do not apply ready-mixed or setting-type joint compound over unsealed board.

For USG Fiberock® Brand Tile Backerboard in tiled areas. Embed USG Durock™ Interior Tape in latex-modified mortar or latex-based Type I mastic over the joint. Use the same material as specified for tile setting.

For finishing USG Fiberock® Brand Underlayment joints. Prefill all underlayment joints with tile-setting mortar or adhesive. Immediately embed USG Durock™ Interior Tape over the joints and strike joints flush. Additional fill coats may be required. Sand uneven panel joints.

For USG Durock™ Brand Glass-Mat Tile Backerboard in tiled areas. Prefill joints between panels of USG Durock® Glass-Mat Tile Backerboard with tile-setting mortar or adhesive. Center USG Durock™ Interior Tape over all joints and corners and embed in mortar or adhesive. Do not overlap pieces of the tape. Level the joints. For small areas where the USG Durock® Glass-Mat Tile Backerboard will not be tiled, such as a board extending beyond the tiled area and abutting another surface, treat joints as follows; seal USG Durock® Glass-Mat Tile Backerboard with Type 1 ceramic tile adhesive (mix four parts adhesive with one part water). Embed USG Sheetrock® Brand Joint Tape over joints and treat fasteners with USG Sheetrock® Brand Durabond® 45 or 90 Setting-Type Joint Compound applied in a conventional manner. Flat trowel USG Sheetrock® Brand Durabond Setting-Type Joint Compound over board to cover fasteners and fill voids to a smooth surface. Finish joints with at least two coats of USG Sheetrock® Brand Ready-Mixed Joint Compound. Do not apply ready-mixed or setting-type joint compound over unsealed board.

DIRECTIONS - EXTERIOR
APPLICATIONS OF TILE AND THIN BRICK FINISHES

APPLICATION OF TEXTURE FINISHES

PRODUCT DATA

SUBMITTAL APPROVALS

Following application of USG Durock® Cement Board, prefill joints with latex-modified portland cement mortar. Center USG Durock™ Exterior Tape over all joints and corners and embed in mortar. Do not overlap pieces of the tape. Level the joints.

Following application of USG Durock® Cement Board, prefill joints with a suitable basecoat. Center USG Durock™ Exterior Tape over all joints and embed in basecoat. Do not overlap pieces of the tape. Level the joints.

USG Durock™ Interior and Exterior Tapes are made from alkali-resistant glass-fiber mesh.

Sizes and Packaging: USG Durock™ Interior Tape: Rolls, 2" x 50' and 2" x 250'.
USG Durock™ Exterior Tape: Rolls, 4" x 150'.

Shelf Life: Up to 12 months under protected storage conditions. Rotate stock.

Availability and Cost: USG Durock™ Interior and Exterior Tapes are distributed throughout the United States. Contact a USG sales office or salesperson for additional information.

Job Name	
Contractor	Date

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

TRADEMARKS

The trademarks USG, DURABOND, DUROCK, FIBEROCK, SHEETROCK, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTE

Products described here may not be available in all geographic markets. Consult your USG Company sales office or representative for information.

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

800 USG.4YOU
800 (874-4968)
usg.com

Manufactured by or for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

CB448-USA-ENG/rev. 7-20
© 2020 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

