

# Declare.™



## Ensemble™ Acoustical Drywall Ceiling United States Gypsum Company

**Final Assembly:** Walworth, Wisconsin, USA

**Life Expectancy:** 30+ Years

**End of Life Options:** Salvageable/Reusable in its  
Entirety (100%)

### Ingredients:

**USG Sheetrock® Brand Ensemble™ Panels:** Calcium Sulfate Dihydrate (FGD Gypsum and Mined Gypsum), Cellulose, Fiber Glass, Starch, Aluminum Hydroxide, Adhesive, Proprietary (0.05-0.2%)<sup>1</sup>, Dextrose, Metaphosphoric Acid (H3P3O9), Trisodium Salt; **USG Ensemble™ Spray-Applied Finish:** Water, Calcium Carbonate, 2-Propenoic Acid, Butyl Ester, Polymer with Ethenyl Acetate, Fiber Glass, Titanium Dioxide, Calcined Kaolin, Proprietary (0.17-0.34%)<sup>1</sup>, Propanoic Acid, 2-Methyl-, Monoester with 2,2,4-Trimethyl-1,3-Pentanediol, 1,3,5-Triazine-1,3,5(2H,4H,6H)-Triethanol; **USG Ensemble™ High-NRC Backer Panels:** Mineral Wool Fiber, Styrene-Based Polymer, Starch, Stucco; **USG Fiberock® Brand End-Joint Backer Panel:** Calcium Sulfate Dihydrate (FGD Gypsum and Mined Gypsum), Cellulose; **USG Sheetrock® Brand Ensemble™ Ceiling Compound:** Water, Calcium Carbonate, Adhesive, Attapulgite, Proprietary (0.02-0.04%)<sup>1</sup>, Propanoic Acid, 2-Methyl-, Monoester with 2,2,4-Trimethyl-1,3-Pentanediol, 1,3,5-Triazine-1,3,5(2H,4H,6H)-Triethanol; **Fasteners:** Steel; **USG Sheetrock® Brand Paper Joint Tape:** Cellulose

<sup>1</sup>LBC Temp Exception I10-E4 Proprietary Ingredients <1%

### Living Building Challenge Criteria:

USG-1048

VOC Content: 0 g/L

**Declaration Status**

EXP: 01 JUL 2020

VOC Emissions: N/A

LBC Red List Free

LBC Compliant

Declared

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ [declareproducts.com](http://declareproducts.com)