

Declare.



Ensemble® Acoustical Drywall Ceiling United States Gypsum Company

Final Assembly: Walworth, WI

Life Expectancy: 30+ Year(s)

End of Life Options: Salvageable/Reusable in its Entirety,
Landfill (100%)

Ingredients:

USG Sheetrock® Brand Ensemble™ Panels: Calcium sulfate dihydrate; Cellulose; Mineral wool; Adhesive; Starch; Polyvinyl acetate; Aluminum hydroxide; Dextrose; Metaphosphoric acid (H3P3O9), trisodium salt; **USG Ensemble™ High-NRC Backer Panels:** Mineral wool fiber; Styrene-based polymer; Starch; Stucco; **USG Ensemble™ Spray-Applied Finish:** Water; Calcium Carbonate; Titanium dioxide; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Glass, oxide, chemicals; Calcined kaolin; Polyvinyl acetate; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Cellulose; 1,3,5-Triazine-1,3,5-(2H,4H,6H)-triethanol; **USG Sheetrock® Brand Ensemble™ Ceiling Compound:** Calcium Carbonate; Water; Attapulgite; Polyvinyl acetate; Adhesive; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; 1,3,5-Triazine-1,3,5-(2H,4H,6H)-triethanol; **Fasteners:** Steel; **USG Sheetrock® Brand Paper Joint Tape:** Cellulose

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: 12.8 g/L
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

USG-0048

EXP. 01 SEP 2024

Original Issue Date: 2018