



USG Halcyon™ ECO United States Gypsum Company

Final Assembly: Greenville, Mississippi, USA

Life Expectancy: 30+ Year(s)

End of Life Options: Landfill

Ingredients:

Basemat: Fiberglass; Dextrose; D-Fructose; Aluminum sulfate octadecahydrate; 1-Propanamine, 3-(triethoxysilyl)-; **Coating :** Nepheline syenite; Calcium Carbonate; Kaolin Clay; Calcined kaolin; 2-Propenoic acid, polymer with chloroethene, ethene, ethenyl acetate, 2-propenamide and sodium ethenesulfonate; Proprietary; Fiberglass; Titanium dioxide; Polysiloxane; Calcium carbonate; Diphosphoric acid, tetrapotassium salt; Phosphorus oxide (P2O5); Amorphous silica; Aluminum hydroxide; Cellulose, 2-hydroxypropyl methyl ether; Salt of polycarboxylic acid; Ethyl acrylate; Zirconium oxide (ZrO2); 1-Propanol, 2-amino-2-methyl-; **Laminate :** Fiberglass; Aluminum hydroxide; **Adhesive:** Acetic acid ethenyl ester, polymer with ethene; Proprietary (0.02-0.04%)¹

¹LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-------------------------------|
| ☐ LBC Red List Free | % Disclosed: 99.96% at 100ppm |
| ☒ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

USG-0067
EXP. 01 OCT 2021
Original Issue Date: 2020