

# USG RADAR™ BASIC ACOUSTICAL PANELS

USG Radar™ Basic Acoustical  
Panels with USG Donn® Brand DX®  
Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- Nondirectional pattern with a fresh, clean appearance offers fast, efficient installation.
- Economical, all-purpose ceiling pattern offered in many sizes.
- Optional Firecode® product designed to meet life-safety codes.
- USDA Certified Biobased Product.<sup>8</sup>

## APPLICATIONS

- Schools
- Corridors
- Offices
- Retail stores

## SUBSTRATE

- Wet-formed mineral fiber

Lightly Textured Panel

USG RADAR™ BASIC ACOUSTICAL PANELS

ORDER SAMPLES/LITERATURE  
USG: usg.com or samplitt@usg.com  
CGC: contact Sales Representative

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com

TECHNICAL SERVICES  
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
ULCOM/GG  
UL 2818



2110, 2120, 2310, 2742



HIGH RECYCLED  
CONTENT



UL Classified

Edge	Panel Size Imperial Metric (mm)	Fire Rating <sup>2</sup>	Item No. Imperial Metric (mm)	NRC	CAC Min.	LR <sup>3</sup>	Color <sup>5</sup>	Grid Options	VOC Emissions	Recycled Content <sup>1</sup>	Panel Cost
SQ 	2'x2'x5/8" 600x600x15	Class A	2110 ME2110	0.55	33	0.83	White	A,C	Low	24-25%	\$
	2'x2'x5/8"		2115	0.55	35	0.83	White	B	Low	48- 49%	\$
	2'x4'x5/8" 600x1200x15	Class A	2310 ME2310	0.55	35	0.83	White	A,C	Low	24-25%	\$
	2'x4'x5/8"		2315	0.55	35	0.83	White	B	Low	48- 49%	\$
	2'x5'x5/8"	Class A	2619	0.55	35	0.83	White	A,C	Low	24-25%	\$
	20"x60"x5/8" 500x1500x15	Class A	2617 ME2617	0.55	35	0.83	White	A,C	Low	24-25%	\$
	30"x60"x3/4"	Class A	2618	0.60	35	0.83	White	A,C	Low	24-25%	\$
SLT 	2'x2'x5/8" 600x600x15	Class A	2120 ME2120	0.55	33	0.83	White	D	Low	24-25%	\$
	2'x2'x5/8"		2125	0.55	35	0.83	White	E	Low	48-59%	\$
	2'x4'x5/8"	Class A	2320	0.55	35	0.83	White	D	Low	24-25%	\$
	20"x60"x5/8"	Class A	2627	0.55	35	0.83	White	D	Low	24-25%	\$
FLB 	2'x2'x5/8"	Class A	2130	0.55	33	0.83	White	F,G,H,I	Low	24-25%	\$
BESK 	12"x12"x5/8"	Class A	2990	0.50	40	0.83	White	J	Low	44%	\$\$\$
SLT 	2'x4'x3/4"	Class A	2742	0.55	35	0.83	White	D	Low	26-27%	\$

PATTERNS

Illusion™ Two/24



The look of 2'x2' panels



Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.



High Recycled Content

USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.



Firecode®

GRID PROFILE OPTIONS

A USG DX®	B USG DXL™	C USG DXW™	D USG DX®	E USG DXL™	F USG Centricitee™ DXT™	G USG Fineline® DXF™	H USG Fineline® 1/8 DXFF™	I USG Identitee® DXI™	J USG DX® Concealed

PHYSICAL DATA/  
FOOTNOTES

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2288/rev. 8-23  
© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Product literature  
Data sheet: SC2288

ASTM E1264 classification

ASTM E1264-22 Type III, Form 2, Pattern C & E and C, E, K  
ASTM E1264-23 Type A, Form A1.2, Pattern C & E and C, E, & K

ASTM E84 and CAN/ULC S102  
surface-burning characteristics

Class A  
Flame spread: 25 or less  
Smoke developed: 50 or less

UL Type  
FR-83

Weight  
0.61-1.15 lb./sq. ft.

Online tools

usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance

R-1.4 (Class A, 5/8" panels and tile)  
R-1.7 (Class A, 3/4" panels)  
R-1.4 (Class A, 15 mm panels)  
R-1.6 (Firecode®, 5/8" panels)

Maximum backloading

See USG 30-Year Limited System Warranty  
Commercial Applications (SC2102).

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Metric sizes available

Contact sales for minimum quantities and lead times.

Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- Firecode® products are approved for use in fire-resistance rated UL designs, where the designs allow for the UL Type Designation.
- LR values are shown as averages.
- Not UL Classified for acoustics.
- No Flat Black or 'Deeptones' are available on any reveal edge or USG Radar™ Firecode® panel.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

Manufactured by  
USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, DONN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, FIRECODE, IDENTITEE, RADAR, IT'S YOUR WORLD, BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

