

RED TOP® Brand Finish Plaster

| | |
|--------------------|---|
| Preparation | Make sure basecoat is properly prepared, clean and rough and open for the finish. To avoid blistering, apply to set and partially dry (damp) basecoat. If basecoat has dried, mist the surface with water to dampen before applying finish. |
| Mixing | RED TOP® Brand Finish Plaster a pre-mix finish coat product that requires only the addition of water. Use a 16-gal. or 30-gal. (60.6 to 113.6 L) smooth-sided container and a cage-type mixer paddle driven by a 1/2" electric drill with a no-load rating of 900-1,000 rpm to produce the rapid, high-shear action required to assure proper dispersion of ingredients. Mix only as much as will be applied in one hour. Water must be clean, fresh, suitable for domestic consumption and free of minerals and organic substances that can affect set. Add plaster to water in the proportions described on the package, mixing as powder is added. |
| Application | Trowel apply to basecoat. Scratch in thoroughly, then immediately double-back to a thickness of not more than 1/16". Final trowel to a smooth, dense surface ready for decoration. |
| Cleanup | Clean mixing tools and containers immediately with water after use and before material has set. Any remaining material on containers and tools may alter the setting time and performance of subsequent batches and will be extremely difficult to remove after more time has passed. |

Trademarks

The following trademarks used herein are owned by United States Gypsum or a related company: RED TOP.

Note

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than their intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

