

Red Top® Finish Plaster



For finishing conventional and veneer plaster interior surfaces

- Factory-prepared for trouble-free mixing
- Excellent smoothness and troweling characteristics
- Consistent lime/gauging ratio

Description

RED TOP® brand finish plaster is a mill-mixed, gauging plaster/lime finish that requires only the addition of water. It has stabilized set and excellent troweling characteristics. The formulation is designed for use over conventional sanded gypsum basecoats and over IMPERIAL® brand and DIAMOND® brand veneer basecoats. It is not to be used over lightweight aggregate gypsum basecoats.

Directions	Preparation	Make sure basecoat is properly prepared, clean and rough and open for the finish. To avoid blistering, apply to set and partially dry (damp) basecoat. If basecoat has dried, mist the surface with water to dampen before applying finish.
	Mixing	RED TOP finish plaster a pre-mixed finish coat product that requires only the addition of water. Use a 16 gal. or 30 gal. (60.6 or 113.6 L) smooth-sided container and a cage-type mixer paddle driven by a 1/2" electric drill with a no-load rating of 900-1,000 rpm to produce the rapid, high-shear action required to properly disperse ingredients. Mix only as much as will be applied in one hour. Water must be clean, fresh, suitable for domestic consumption and free of minerals and organic substances that can affect set. Add plaster to water in the proportions described on the package, mixing as powder is added. If a faster or slower set time is desired, follow recommendations for use of accelerators and retarders in USG literature PM6 and PM7.
	Application	Trowel to basecoat. Scratch in thoroughly, then immediately double-back to a thickness of not more than 1/16". Final-trowel to a smooth, dense surface ready for decoration.
	Cleanup and Storage	Clean mixing tools and containers immediately with water after use and before material has set. Any material remaining in containers and on tools will become extremely difficult to remove and may alter the setting time and performance of subsequent batches.

Product Data	<p>Coverage: RED TOP finish plaster covers 3,500 ft.²/ton (358 m²/t[metric]) of mixed product.</p> <p>Storage: Store material inside, in a dry location and away from heavy-traffic areas. Stack bags on planks or platforms away from damp floors and walls.</p> <p>Shelf Life: 6 months under good storage conditions. To assure consistent performance, rotate stock so as to use oldest first and keep stock consistently fresh.</p> <p>Availability and Cost: RED TOP finish plaster—regular set 55 to 75—is distributed throughout the United States.</p> <p>Packaging: Packed in 50 lb. bags.</p>
---------------------	---

Submittal Approvals:

Job Name	
Contractor	Date

WARNING!

When mixed with water, this material hardens and becomes very hot - sometimes quickly. DO NOT attempt to make a cast enclosing any part of the body using this material. Failure to follow these instructions can cause severe burns that may require surgical removal of affected tissue or amputation of limb. Dust may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Avoid irritation by reducing exposure to dust.

Use in a well-ventilated area or provide sufficient local ventilation. Do not ingest. If dusty, wear a NIOSH/MSHA-approved dust respirator. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists, call physician. Wash with soap and water after use. If ingested, call physician. Product information and MSDS: (800) 507-8899 or usg.com.

KEEP OUT OF REACH OF CHILDREN.

Trademarks

The following trademarks used herein are owned by United States Gypsum or a related company: DIAMOND, IMPERIAL, RED TOP, USG, USG in stylized letters.

Note

Products described here may not be available in all geographic markets. Consult your United States Gypsum Company sales office or representative for information.

Notice

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

Safety First!

Follow good safety and industrial hygiene practices during handling and installation of products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.

