

SHEETROCK® Brand Gypsum Panels Flexible

Application

- Position ends and edges of all gypsum panels over framing members, except when joints are at right angles to framing members as in perpendicular application
- Apply SHEETROCK Brand Flexible Gypsum Panels first to the ceiling and then to the walls. Extend ceiling board into corners and make firm contact with top plate. Cut panels neatly and provide support at cutouts and openings. To minimize end joints, use panels of maximum practical lengths. Fit ends and edges closely, but do not force together.
- SHEETROCK Brand Flexible Gypsum Panels are normally installed in a double-layer application. Center face layers over joints of base layers. Secure base panels to studs with fasteners at 16" o.c., with a minimum of four screws for each stud. For the face layer, space fasteners 12" o.c. with a minimum of five screws per panel width in each stud. Use 1" fasteners for base layer and 1-5/8" screws for face layer.
- When applying gypsum panels to outside radius of frame, attach panel to last stud on either tangent wing wall, then screw-attach panel to studs as you carefully work panel around frame. Those panels being applied to inside of arc must be supported at each end by one person, with each person supporting and pulling in on the panel ends with one hand and using other hand to carefully push the panel in at the center. Fasten panels to studs beginning with center stud and work outward. For panels longer than 8 ft., an additional person may be required to support the center of the panel.

Trademarks

The following trademarks used herein are owned by United States Gypsum or a related company: SHEETROCK.

Note

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than their intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from the date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

