

SHEETROCK™ Sand Finish Paint Additive



Produces a decorative sand texture

- For quick, easy creation of attractive textured walls and ceilings.
- Works in all paints and varnishes.
- Amount added can be varied to customize texture.

Description

SHEETROCK™ Sand Finish Paint Additive is an extremely fine volcanic mineral compound added to paint or varnish to produce a decorative sand texture finish on walls and ceilings. It can also be used to create a non-skid surface around pools and on decks, steps, and ramps. SHEETROCK Sand Finish Paint Additive can be used with any paint or varnish, oil- or latex-based. It remains uniformly distributed throughout the paint, never settling to the bottom.

The addition of 8 oz. (0.22 kg) of additive to one gal. (3.78 L) of paint or varnish reduces normal coverage by approximately 25%.

Directions	Preparation	Surface must be structurally sound, dry, clean, and free of scaly paint, wallpaper, wax, dust, and dirt.
	Mixing	Add approximately 8 oz. (0.22 kg) of additive to one gal. (3.78 L) of latex- or oil-based paint to create a medium texture finish on walls, ceilings, or wood surfaces. If a heavier or lighter texture is desired, more or less additive may be used. When using dark paint colors, mix 2-3 hours before painting, and allow to stand. Note: When attempting a heavier-than-average finish, test a small area before starting the job. The use of too much additive may cause cracking when paint is dry.
	Application	Apply paint or varnish according to manufacturer's directions, using brush or roller. If desired, a sponge, whisk broom, or other tool may be used on wet paint to further modify the texture.
	Cleanup	Clean all brushes, rollers, and equipment immediately, referring to the instructions provided by the paint or varnish manufacturer.

Product Data	Packaging	8 oz. (0.23 kg) plastic tub and 30 oz. (0.85 kg) box.
---------------------	------------------	---

Submittal Approvals	Job Name	
	Contractor	Date

WARNING

Spraying mist or dust created from product may cause eye, skin, nose, throat, or respiratory irritation. Avoid inhalation of mist or dust. Wear a NIOSH/MSHA-approved respirator when dusty or misty or if spray applying. Use proper ventilation to reduce mist/dust exposure. Prolonged and repeated exposure to respirable mica may cause lung disease. Wear eye protection. If eye contact occurs, immediately flush thoroughly with water for 15 minutes. If irritation persists, call physician. Wear long-sleeved work clothing to prevent skin irritation. Wash thoroughly with soap and water after use. Do not ingest. If ingested, call physician. Product safety information: (800) 507-8899.

KEEP OUT OF REACH OF CHILDREN.

Trademarks

The following trademark used herein is owned by United States Gypsum Company: SHEETROCK.

Note

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

Safety First!

Follow good safety and industrial hygiene practices during handling and installing of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.