

SHEETROCK® Brand Wall and Ceiling Spray Texture

UNAGGREGATED



For a variety of light, appealing textures in interiors

- For most interior wall and ceiling surfaces.
- Superior open time for hand-tooled knockdown finishes.
- Excellent surface relief (standout).
- Low shrinkage formula.

Spatter	Spatter/Knockdown	Orange Peel
		

Description SHEETROCK® Brand Wall and Ceiling Spray Texture is a top-performance product available unaggregated. Ideal where moderate to bold texture patterns are desired. Designed for spray application over gypsum panels and most other interior wall and ceiling surfaces. Formulated to create attractive texture patterns such as spatter, spatter/knockdown, and orange peel designs. Dries to a firm, soft-tone white surface. Should be overpainted when dry. Not washable unpainted.

Advantages

- Safe and easy to mix and use.** Mixes easily with cold water. Variety of textures obtained with simple equipment.
- For most interior surfaces.** Ideal for use on gypsum drywall, plaster, concrete.
- Superior open time for hand-tooled knockdown finishes.** Remains wet at the surface long enough so that the user can control the finishing process, resulting in a uniform pattern.
- Excellent surface relief (standout).** Pronounced texture designs forgive and conceal minor surface imperfections.
- Low shrinkage property.** Provides lower shrinkage than texturing with joint compound.

Limitations

1. Application below grade or in high-humidity areas is not recommended.
2. Heavy water-based textures may result in sagging of gypsum board ceilings under these conditions: high heat and humidity, improper ventilation, and/or board application to framing, and insufficient board thickness for span between supports. When using water-based textures, refer to the following table:

Board Thickness		Application Method (Long edge relative to frame)	Maximum Frame Spacing o.c.	
inch	mm		inches	mm
3/8	9.5	Not Recommended	—	—
1/2	12.7	Perpendicular Only	16*	406
5/8	15.9	Perpendicular Only	24	610

Note: Double layer laminated. 3/4" or greater total thickness—24" o.c.

*1/2" SHEETROCK® Brand Interior Gypsum Ceiling Board provides the strength and sag resistance of 5/8" standard board without the added thickness.

Directions

Surface Preparation Substrate must be sound, dry, clean, and free of oil, grease, mildew, efflorescence, and other foreign materials and/or contaminants. Product, air, and surface temperatures must be maintained at a minimum of 55 °F (13 °C) throughout the finishing process when using joint compound, primer, and texture products.

New Drywall—Treat joints and nailheads with an appropriate USG Joint Treatment System.

New Concrete/Plaster—Age at least 60 days before texturing. Remove form oils and efflorescence and grind down form lines. Fill cracks and holes, and level concrete surfaces with SHEETROCK® Brand Setting-Type (DURABOND®) or Lightweight Setting-Type (EASY SAND™) Joint Compound or Cover Coat® Compound and let dry.

Substrate Priming Application of a prime coat is necessary to equalize surface porosity. After prepared surfaces have thoroughly dried, apply a prime coat of SHEETROCK® Brand First Coat flat latex paint or a good quality interior latex flat wall paint with high solids content. Prime coat should be applied undiluted and allowed to dry before decorating.

Mixing

Use a clean vessel equipped with power agitator. For initial mix, stir powder into recommended amount of water, agitating during powder addition. Allow to soak for at least 15 min.—longer in cold water. Remix until a creamy, lump-free mix is obtained. Adjust spray consistency by adding small amounts of powder or water. Overthinning can create an undesirable finish or “soft wall” or chalky condition. Overdilution can also entrain excessive air and foam.

Application

Using suitable spray equipment, apply by machine to create the desired effect. The application rate will vary from 10 ft.²/lb. (2 m²/kg) to 40 ft.²/lb. (8.2 m²/kg) depending on texture pattern. Maintain 55 °F (13 °C) minimal air, product, and surface temperature during application and until surface is dry. Avoid drafts while applying, but provide ventilation after application to aid drying. Do not use unvented gas or oil heaters. May be painted after overnight drying. Unpainted surface is not washable or scrubbable. Match spray equipment to job size and time requirements. For rapid application and high production, use either a piston pump (7:1 or larger) or a rotor stator pump matched to a compressor of adequate size. Preferred texture patterns can be obtained using a Binks 18D spray gun (with #57 or 58 fluid nozzle with R27 or R30 fan cap) or Binks 7E2 spray gun (with #46 fluid nozzle with #190, 191, 290, 291, or 292 fan cap). Fan caps with a rectangular orifice reduce overspray and waste and will provide greater spray control. Good results can also be obtained using a short pole gun with a 3/8” nozzle orifice. Small jobs can be completed using a Hopper Gun or Goldblatt Pattern Pistol with separate compressor.

Product Data

Color: White; overpainting recommended on walls. Not washable unpainted.

Filler: Calcium carbonate or calcium sulfate.

Dilution (water): Refer to directions on product bag.

Density (dry bulk): 43.0-48.0 lb./ft.³ (689-769 kg/m³).

pH: 7.0-8.0.

Tinting: Not recommended. Usually overpainted.

Drying Time: Dries to touch in 1 to 2 hr. (75 °F/50% R.H. conditions). Let dry before painting.

Coverage: Up to 40 ft.²/lb. (8.2 m²/kg). Coverage will vary depending on the texture pattern.

Storage: Close opened bags as tightly as possible and store in dry place.

Shelf Life: 6-12 mos. under protected storage conditions.

Packaging: 40 and 50 lb. bags (18.1 kg and 22.7 kg).

Submittal Approvals:

Job Name	
Contractor	Date

WARNING

Spraying mist or dust created from product may cause eye, skin, nose, throat, or respiratory irritation. Avoid inhalation of mist or dust. Wear a NIOSH/MSHA-approved respirator when dusty or misty or if spray applying. Use proper ventilation to reduce mist/dust exposure. Wear eye protection. If eye contact occurs, immediately flush thoroughly with water for 15 minutes. If irritation persists, call physician. Wear long-sleeved work clothing to prevent skin irritation. Wash thoroughly with soap and water after use. Do not ingest. If ingested, call physician. Product safety information: (800) 507-8899.
KEEP OUT OF REACH OF CHILDREN.

Trademarks:

The following trademarks used herein are owned by United States Gypsum or a related company: COVER COAT, DURABOND, EASY SAND, SHEETROCK.

Note:

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installing of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.