

# TREM Grip®

TREM Grip's quick tack sealant is a sealant you can count on for a variety of applications on a number of substrates, limiting extra steps and allowing rapid installation.

## Description

TREM Grip® is a one component, non-sag, elastic sealant based on hybrid polymers best suited for in-plant applications on Securock® ExoAir® 430.

## Key Benefits

- Single component elastomeric sealant (medium modulus)
- Offers great elasticity and rapid bond development
- Solvent free formulation, low odor and extremely low [VOC](#)
- Resistant to UV, weather and aging
- Indoor/outdoor use on a variety of substrates

## Usage/Purpose

TREM Grip has been developed to bond materials to a variety of substrates where an adhesive with extremely high initial green strength is required. Examples of applications include, but are not limited to:

- Drainage board for backfill applications
- Air Barrier Applications
- Insulation to Air Barriers and Below Grade Membranes

## Health & Safety Precautions

Safety [data sheet](#) must be read and understood before use. Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment.

## Color

Grey

## Packaging

600 ml sausage (15 per carton)

## Please Note

Not suitable for bonding polyethylene, polypropylene, Teflon® or nylon. Not recommended for sheet laminate. Do not use as a structural glazing adhesive. Not recommended for prolonged exposure to water. Contact with bituminous or tar containing surfaces may lead to discoloration. Staining on natural stone may occur. If two nonporous substrates are adhered, the maximum width should not exceed 15mm.

## Necessary Tools

TREM Grip is easy to apply with conventional caulking equipment.

Property	Test Method	Results
Tensile	ASTM D412	390 psi
Elongation	ASTM D412	420%
Tear Strength	ASTM D624	76 psi
Hardness- Shore A	ASTM C661	60
Skin Time	ASTM C679 (8.4)	10-14 minutes
Tack Free Time	ASTM C679	16-18 minutes
Movement Capabilities	ASTM C719	In Progress (35%)
Lap Shear	ASTM C961	280 psi
Flame Spread	ASTM E84	0
Smoke Development	ASTM E84	0
Fire Resistance of Assembly	NFPA 285	Passes