

USG 500 LANDPLASTER

BALTIMORE, MD

DESCRIPTION

- USG 500 Landplaster is manufactured from high purity, natural gypsum rock, resulting in a product that is uniformly high in analysis and solubility.
- USG 500 Landplaster is a multisized product, delivering the benefits of consistent flow, even coverage during application, and continuing release of calcium and sulfur across the important growth stage of your crop. Calcium and sulfur—where you need it, when you need it.
- USG 500 Landplaster has been developed to provide high levels of performance that save time and return a value to both the dealer and farmer. When you weigh your agriculture purchasing decision, please consider the benefits of USG 500 Landplaster—one man spreader operations, fewer trips to the field, less time in the field, and fewer truck deliveries from the source. All these benefits add up to less of your time spent on gypsum applications and more time to earn a profit on other projects. USG 500 Landplaster will help buy you time, not just better yields.
- USG 500 Landplaster has been certified as organic by the Organic Materials Review Institute (OMRI®).

GUARANTEED ANALYSIS

Calcium Sulfate Dihydrate Equivalent (Gypsum, CaSO ₄ • 2H ₂ O)	90.0%
Calcium Sulfate Equivalent (CaSO ₄)	71.2%
Calcium (Ca)	21.0%
Sulfur (S)	16.8%
pH	7.3

APPROXIMATE SIZING

% Passing — 4 Mesh	98.4%
% Passing — 8 Mesh	67.0%
% Passing — 16 Mesh	26.8%
% Passing — 30 Mesh	7.4%
% Passing — 50 Mesh	4.5%
% Passing — 100 Mesh	2.7%
% Passing — 200 Mesh	0.9%
% Passing — 325 Mesh	0.4%

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

CAUTION

Dust from mixing may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If on skin: Wash with plenty of water. If swallowed or irritation persists, call physician. For more information call Product Safety: 800-507-8899 or see the SDS at usg.com

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates. OMRI LISTED is a registered trademark of OMRI.

NOTE

The information in this document is subject to change without notice. USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document. Consult your USG Company sales office or representative for information.

NOTICE

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

BULK DENSITY

82 lbs. per cubic foot (loose) / approx. 94 lbs. per cubic foot (packed)



800 USG.4YOU
800 (874.4968)
usg.com

Manufactured for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG1978-USA-ENG/rev. 10-17
© 2017 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.