

USG ASPEN™ BASIC ACOUSTICAL PANELS

USG Aspen™ Basic Acoustical Panels/
USG Donn® Brand DX® Acoustical
Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Random, naturally sculptured appearance offers an upscale look without the upscale cost.
- Sizes and performance meet most design criteria.
- Suitable for general applications.
- USDA Certified Biobased Product.⁴

APPLICATIONS

- Schools
- General Offices
- Retail Stores

SUBSTRATE

- Wet-formed Mineral Fiber

Medium-Textured Panel

USG ASPEN™ BASIC ACOUSTICAL PANELS

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818



USG ASPEN™
BASIC PANELS

USG ASPEN™
BASIC ILLUSION™
TWO/24 PANELS

FACE-CUT PATTERNS

GRID PROFILE OPTIONS

PHYSICAL DATA/
FOOTNOTES

UL Classified											
Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Recycled Content ¹	Panel Cost
	2'x2'x3/4"	Class A	650	0.55	35	0.87	White	A	Low	58%	\$\$
	2'x4'x3/4"	Class A	651	0.55	35	0.87	White	A	Low	58%	\$\$
	2'x4'x3/4"	Class A	652	0.55	35	0.87	White	A	Low	58%	\$\$

USG Aspen™ Basic Illusion™ Two/24




The look of 2'x2' panels

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available at spot.ul.com.

A
USG DX®



Product literature
Data sheet: SC1809

ASTM E1264 classification

USG Aspen™ Basic:
ASTM E1264-22 Type III, Form 2, Pattern CDFI
ASTM E1264-23 Type A, Form A1.2, Pattern CDFI

USG Aspen™ Basic Illusion™:
ASTM E1264-22 Type III, Form 2, Pattern CDFIK
ASTM E1264-23 Type A, Form A1.2, Pattern CDFIK

ASTM E84 and CAN/ULC S102
surface-burning characteristics
Class A

Flame spread: 25 or less
Smoke developed: 50 or less

Online tools
usgdesignstudio.com, cgcdesignstudio.com
or usg.ecomedes.com

Thermal resistance
R-1.7 (3/4" panels)

Weight
0.92 lb./sq. ft. (Class A)
0.92 lb./sq. ft. (Illusion)

Maximum backloading
See USG 30-Year Limited System Warranty
Commercial Applications (SC2102).

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Metric sizes available
Contact sales for minimum quantities and lead times.

Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- Panels have a 15/16" routing.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.
- SLT & ILT Illusion™ edges have a different reveal depth from SLT or FLB edge details. Please reference the System Interface, located in the SC2000, before installing.

Notice
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1809/rev. 7-24
© 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, ASPEN, DONN, DX, ILLUSION, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

