

USG ORION™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Orion™ Acoustical Panels
with ClimaPlus™ Performance/
USG Donn® Brand DX®
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Excellent noise reduction.
- High light-reflective finish (LR-0.87) reduces light fixtures and energy use.
- Nondirectional, monolithic visual reduces installation time and waste.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Wide range of acoustical performance.
- USG Orion™ Acoustical Panels are part of the Ecoblueprint™ portfolio — meeting today's sustainability standards. For sustainability documentation go to USG.com or CGCInc.com.

APPLICATIONS

- Offices
- Conference rooms
- Healthcare (HIPAA requirements)
- Classrooms
- Corridors
- Reception/lobby areas
- Dining rooms

SUBSTRATE

- Wet-formed mineral fiber

Fine-Textured Panel

USG ORION™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
 USG: samplitt@usg.com
 phone: 866 528-7089 | usg.com
 CGC: contact Sales Representative

FOR MOST UP-TO-DATE
 TECHNICAL INFORMATION
 AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com

TECHNICAL SERVICES
 800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
 FOR LOW CHEMICAL
 EMISSIONS:
 UL/COM/GG
 UL2818



• No Visible Sag
 • Mold/Mildew Protection



UL Classified

Edge	Panel Size	Fire Rating	Item No.	UL Classified			Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹	
				NRC	CAC	LR ²					Total RC	Panel Cost
USG ORION™ 60 SQ	2'x2'x1/2"	Class A	62156	0.60	23	0.87	White	A,B,C	Low		71%	\$
	2'x4'x1/2"	Class A	62157	0.60	23	0.87	White	A,B	Low		71%	\$
USG ORION™ 75	SQ	2'x2'x5/8"	62150	0.75	24	0.87	White	A,B,C	Low		69%	\$\$
		2'x4'x5/8"	62151	0.75	24	0.87	White	A,B	Low		69%	\$\$
	SLT	2'x2'x5/8"	62152	0.75	24	0.87	White	D	Low		69%	\$\$
		2'x4'x5/8"	62153	0.75	24	0.87	White	D	Low		69%	\$\$
	FLB	2'x2'x5/8"	62154	0.75	24	0.87	White	E,F,G,H	Low		69%	\$\$
		2'x4'x5/8"	62155	0.75	24	0.87	White	E,F,G,H	Low		69%	\$\$
USG ORION™ 85	SQ	2'x2'x5/8"	62162	0.85	24	0.87	White	A,B,C	Low		71%	\$\$
		2'x4'x5/8"	62163	0.85	24	0.87	White	A,B	Low		71%	\$\$
	SLT	2'x2'x5/8"	62164	0.85	24	0.87	White	D	Low		71%	\$\$
		2'x4'x5/8"	62165	0.85	24	0.87	White	D	Low		71%	\$\$
	FLB	2'x2'x5/8"	62166	0.85	24	0.87	White	E,F,G,H	Low		71%	\$\$
		2'x4'x5/8"	62167	0.85	24	0.87	White	E,F,G,H	Low		71%	\$\$

Low Emissions

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C ⁴ USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Fineline® DXF™	G USG Fineline® 1/8 DXFF™	H USG Identitee® DXI™

PHYSICAL DATA/ FOOTNOTES

Product literature
 Data sheet: SC2648

ASTM E1264 classification
 Mineral Fiber: Type IV, Form 1 and 2, Pattern E,G

ASTM E84 and CAN/ULC S102 surface-burning characteristics
 Class A
 Flame spread: 25 or less
 Smoke developed: 50 or less

Weight
 0.71 lb./sq. ft. 1/2" Mineral Fiber
 0.63 lb./sq. ft. 5/8" Mineral Fiber

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Thermal resistance
 R-1.8

Maximum backloading
 See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

Maintenance
 Can be cleaned easily with a soft brush or vacuum. To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface.

Metric sizes available
 Contact sales for minimum quantities and lead times.

Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial additive that inhibits and retards the growth of mold, mildew and bacteria. For details, see *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).
- Maximum 2'x2' with SQ edge panels.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2648/rev. 8-21

© 2021 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, FINELINE, IDENTITEE, ORION, IT'S YOUR WORLD, BUILD IT, the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

