



**USG CEILINGS PLUS<sup>®</sup>  
COLORTEX™ BARZ<sup>®</sup>**  
ACOUSTIC PANEL SOLUTIONS

**INSTALLATION GUIDE**



# Introduction

Enter **COLORTEX™ BARZ®** - Innovative ceiling designs brought to you by **USG Ceilings Plus®**. In this manual we'll show you how to perform the installation the right way, the first time. Go ahead, install with a smile..

The purpose of this installation manual is to provide you with general steps and procedures on how to properly and safely install **COLORTEX™ BARZ®** ceiling systems as well as how to address various field conditions.

Please read this entire manual and familiarize yourself with all procedures before you begin. If you have been supplied with project drawings specific to your order, make sure you have a thorough understanding of those. Any details within those documents will supersede this manual. Work area must be clear of debris and obstacles to ensure a safe and fast installation.

**Please work safely!**


# Table of Contents

<b>Preparation</b>	
Component Identification	1
Tools	2
Blank Grid	3
<b>General Installation</b>	
Install Hanger Wire & Main Tees	4
Install Cross Tees	5
Level Grid System	6
Install Colortex™ Baffles	7
Adjust Baffle Spacing	8
Installation Completed	9
Field Cutting Colortex™ Baffles	10
Field Cutting Colortex™ Baffles	11
Install Wall & Ceiling Channels	12
Mounting Colortex™ Baffles	13
Applying Lock-Screws	14
Colortex™ Baffles Completed	15
Mounting Colortex™ Baffles - SERIES	16
SERIES Installation Completed	17
<b>Colortex Barz + Brilliance Installation</b>	
Prepare plenum, install junction boxes, system drivers, as required. (ELECTRICIAN)	19
Level and install main ceiling grid as required (INSTALLER)	20
Baffle installation and electrical connections	21
Baffle installation using cable method	22
<b>Notices</b>	
Safety, Installation, Limitation, Liability	23
<b>Maintenance</b>	
Adjust & Clean	24
<b>Support</b>	
Contacts	24
<b>Notes</b>	


# Preparation

## Component Identification

### Typical Supplied Components



### Available Accessories




# Preparation

## Tools

### Standard Tools



Safety Goggles



Hard Hat



White Cotton Gloves




Tape Measure




Square



Lineman Wire Cutters




Hanger Wire



Laser Level


### Field Modification Tools




Utility Knife




Electric Screwdriver




Electric Shears



Working Gloves



Metal Straight-Edge



Left

Right


Center

Snips

# Grid Planning




## Blank Grid

Crosses @ 4'⌀, Dashed Lines @ 2'⌀




# General Installation

## Install Hanger Wire & Main Tees





Install per ASTM C636 and ASTM E580 specifications. Select the correct fastener based on your field conditions, i.e. shot-in pin, anchor bolts, screw/clip, etc.

Install additional bracing required for project's seismic codes. Lateral bracing wires/compression posts. For lateral bracing, counter-splayed wires or diagonal bracing are required for each direction.



# General Installation


## Install Cross Tees




Install Cross-Tees between Main Tees with 30" maximum  $\varnothing$  spacing. Follow installation drawing layout.

# General Installation

## Level Grid System




Use laser level to ensure whole grid is leveled to a 1/8" maximum variance.





# General Installation


## Install Colortex™ Baffles



(A) Lift Baffles up into position with Swivel-Clips making contact with Main Tees.




(B) Rotate Swivel-Clips clockwise to lock them onto Main Tees. Clips can still be slid along Main Tee for fine tuning spacing (see next page).





# General Installation

## Adjust Baffle Spacing





(C) Slide Swivel-Clips along Main Tee's length to adjust spacing between baffles.

Hole for Lock-Screw




(D) To lock Baffles into position, apply Self-Tapping Screws to Main Tees and Swivel-Clips as shown.




# General Installation

## Installation Completed




(E) Adjust/position remaining Baffles as necessary.




FULLY INSTALLED COLORTEX™ BARZ® CEILING SYSTEM

# General Installation

## Field Cutting Colortex™ Baffles





(C) Align and position Enc-Cap, then secure in place via Screws as shown below.



# General Installation


## Field Cutting Colortex™ Baffles

Swivel-Clips may be re-positioned after a Field-Cut operation to conform to any grid layout.




# Direct Mount Installation

## Install Wall & Ceiling Channels




(A) Locate wall and/or ceiling studs, measure, and mark location for channel placements.




# Direct Mount Installation

## Mounting Colortex™ Baffles




(A) Install Wall Baffles as shown.



# Direct Mount Installation


## Applying Lock-Screws



Apply Lock-Screw at end of Baffles as shown. Ensure that Lock-Screw's head is set past Baffle's End-Cap surface. Lock-Screws must penetrate Baffle's internal Hat-Channel and anchor to wall/ceiling.

# Completed Installation


Colortex™ Baffles Completed




FULLY INSTALLED COLORTEX™ BARZ® CEILING & WALL SYSTEM

# Direct Mount Installation

## Mounting Colortex™ Baffles - SERIES




(A) For a SERIES installation, first mount Hook-Channels in the order shown above. The REVEAL for HOOK-CHANNELS must be calculated with BAFFLES'S final 1/4" reveal in mind.



(B) Install Ceiling Baffles in order shown.



(C) Lock-Screw must be applied to EACH Baffle PRIOR to mounting NEXT Baffle.

Completed Installation  
SERIES Installation Completed




FULLY INSTALLED COLORTEX™ BARZ® CEILING SERIAL ARRAY

# Colortex Barz + Brilliance Installation





# Colortex Barz + Brilliance Installation

Prepare plenum, install junction boxes, system drivers, as required. (ELECTRICIAN)




# Colortex Barz + Brilliance Installation

Level and install main ceiling grid as required (INSTALLER)



# Colortex Barz + Brilliance Installation

## Baffle installation and electrical connections




**STEP 1**

Colortex Barz + Brilliance baffles are installed onto grid per installation drawings.



**STEP 3**

After Colortex Barz + Brilliance baffles installed, Electrical sub-contractor shall make all cable connections and ensure operation of lights.



**STEP 2**

Adjust Colortex Barz + Brilliance baffle spacing to desired spacing and ensure swivel clips are firmly locked onto grid.




**FINAL ASSEMBLY**


# Colortex Barz + Brilliance Installation

## Baffle installation using cable method


### CABLE METHOD OF INSTALLATION




**STEP 1**  
Use appropriate hardware for substrate (provided by others)



**STEP 2**  
Adjust cable length thru hook as necessary. Trim any excess length leaving only approximately 2" length for future adjustments.



**STEP 3**  
Hook cable assembly into baffle bracket.



**FINAL ASSEMBLY**

## Notices

### Safety, Installation, Limitation, Liability

#### SAFETY

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation. Be cautious with exposed sharp edges when handling ceiling system components.

#### INSTALLATION

Prior to installation, make sure your project complies with any seismic & non-seismic requirements. Must be installed in compliance with ASTM C636, ASTM E580, utilizing standard industry practices and adopting applicable code requirements. Alternative assemblies and installation methods may be utilized when approved by the authority having jurisdiction. USG Ceiling Plus recommends checking with the authority having jurisdiction prior to designing and installing a suspended ceiling system.

#### LIMITATION

Some commercially acceptable color variation may occur between lots and between different size products of the same color.

#### LIABILITY

We shall not be liable for any incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered. This product is covered under the standard warranty for USG Ceilings Plus products. For terms and conditions please visit [www.usg.com](http://www.usg.com)

## Maintenance

### Adjust & Clean

- A.** Colortex™ Barz® baffles are meant for indoor applications only.
- B.** Adjust ceiling components to provide a consistent finish and appearance in conformity with established tolerances and requirements.
- C.** Make sure to have clean hands at all times when handling/touching Colortex™ panels.
- D.** To remove dust, use a vacuum. An angled nozzle end works best.
- E.** If a spill occurs on the material immediately dab area with a clean, damp cloth. Soap and water may also be used if necessary.
- F.** If further cleaning is required, a polyester carpet and fabric cleaner can also be used. Always test on an inconspicuous area first.
- G.** Never expose Colortex™ material to temperatures above 240° F.
- H.** Remove and replace work that cannot be successfully cleaned and repaired to permanently eliminate evidence of damage, including dented and bent units.

---

## Support

### Contacts

**Contact your sales rep for any additional support.**



