



USG DUROCK™ BRAND ADVANCED SKIM COAT™ FLOOR PATCH

- Premium, versatile, trowelable calcium aluminate skim coat and floor patch
- Fast setting—floor coverings may be installed in as little as 15 minutes
- Innovative formulation offers significant yield advantage vs. competitive products
- May be re-tempered multiple times prior to set without addition of water
- No priming necessary over most surfaces
- Featheredge to 1/2 in. (13 mm) thick in large areas; any thickness in small well-defined areas such as thresholds and concave-shaped depressions in substrates
- May be used as an embossing leveler

USG DUROCK™ BRAND ADVANCED SKIM COAT™ FLOOR PATCH

At USG, we know how important it is to get the floor right. Rework is expensive, and delays are costly. That's where USG Performance Flooring comes in. We offer the most innovative floor preparation products and systems, ensuring you get the right floor the first time.

DESCRIPTION

USG Durock™ Brand Advanced Skim Coat™ Floor Patch is a versatile calcium aluminate floor patch and skim coat for interior use over wood, concrete and gypsum subfloors.¹ Its versatility allows USG Durock™ Advanced Skim Coat Floor Patch to be used over most interior floors, including ceramic and quarry tile, terrazzo, wood, metal and interior concrete, as well as properly prepared residues of cutback and other non-water-soluble adhesives on concrete and epoxy coatings. Simply mix USG Durock™ Advanced Skim Coat Floor Patch with water and apply with a trowel—no need for priming or a latex additive for most applications. USG Durock™ Advanced Skim Coat™ Floor Patch can be used as an embossing leveler over most floor coverings when mixed with water.² To enhance bond to epoxy coatings or for high performance applications, use in conjunction with USG Durock™ Matrix™ Bond Enhancer.

Notes

- Existing gypsum underlayments must be solid with no cracks and dust free. First test surface hardness by scratching existing underlayment with a coin. If surface can be gouged, do not use USG Durock™ Advanced Skim Coat Floor Patch and see *USG Rehabilitation Guidelines for Damaged Gypsum Underlayments* (CB822). Gypsum surfaces must be sealed with USG Durock™ Brand Primer-Sealer prior to application of USG Durock™ Advanced Skim Coat™ Floor Patch.
- For maximum bond when embossing, use in conjunction with USG Durock™ Brand Matrix™ Bond Enhancer.

APPLICATIONS

For interior use over concrete, gypsum, metal and wood subfloors and most interior floors, including sheet goods, VCT, ceramic and quarry tile, and terrazzo, as well as properly prepared residues of cutback and other non-water-soluble adhesives on concrete and epoxy coatings.

EXTENDED WARRANTY

An extended warranty may apply when using USG Durock™ Advanced Skim Coat Floor Patch in a system application. Please contact USG for further details.

PRODUCT DATA

Mixing Ratio	9 lb. (4.0 kg) bag USG Durock™ Advanced Skim Coat Floor Patch requires up to 2.25 quarts (2.1 L) of water (three parts USG Durock™ Advanced Skim Coat Floor Patch to one-part water by volume)
Approximate Coverage	Up to 76 sq. ft. (7.1 m ²) at 1/16 in. (2 mm) thickness Up to 38 sq. ft. (3.5 m ²) per bag when applied at 1/8 in. (3 mm) thickness Up to 19 sq. ft. (1.7 m ²) per bag when applied at 1/4 in. (6 mm) thickness
Approximate Working Time	10–15 minutes
Approximate Time to Flooring	In as little as 15 minutes or when USG Durock™ Advanced Skim Coat Floor Patch can be worked on without damaging the surface. Drying time is dependent on job site temperature and humidity conditions as well as application thickness.
Thickness Range	Featheredge to 1/2 in. (13 mm) thick in large areas; any thickness in small well-defined areas such as thresholds and concave-shaped depressions in substrates.
Packaging	9 lb. (4.0 kg) multiwall paper bags.

Note: Physical characteristics published herein were achieved under controlled laboratory conditions. Actual field results may differ due to environmental conditions, inconsistent proportioning of field-applied water and USG Durock™ Advanced Skim Coat Floor Patch, as well as differences in mixing equipment.

For more information, see *USG Durock™ Brand Advanced Skim Coat™ Floor Patch Submittal* (CB805) at usgperformanceflooring.com.

CB819-USA-ENG/rev. 11-19
© 2019 USG Corporation and/or its affiliates.
All rights reserved.
Printed in U.S.A.

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

800.USG.4YOU
800 (874-4968)
usgperformanceflooring.com
usg.com

PRODUCT INFORMATION

See usgperformanceflooring.com for the most up-to-date product information.

DANGER!

Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause respiratory irritation. May cause cancer by inhalation of respirable crystalline silica. Do not handle

until all safety precautions have been read and understood. Avoid breathing dust. Use only in a well-ventilated area, wear a NIOSH/MSHA approved respirator. Wear protective gloves/protective clothing/eye protection. If swallowed, inhaled, or skin irritation occurs get medical attention. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses and continue rinsing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Dispose of in accordance with local, state, and federal regulations. For more information call Product Safety: 800 507-8899 or see the SDS at usg.com.
KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, ADVANCED SKIM COAT, DUROCK, MATRIX, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTE

The information in this document is subject to change without notice. USG Corp. and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Consult

your USG sales office or representative for information.

NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to the replacement of defective goods or a refund of the purchase price, at USG's option, and does not include costs of labor, floor-covering materials, or any other costs associated with material replacement. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.