



USG DUROCK™ BRAND FLOOR PREP PRODUCTS

BEST SELLERS LIST

- USG Durock™ UltraCap® Self-Leveling Underlayment
- USG Durock™ Quik-Top™ Self-Leveling Underlayment
- USG Durock™ Advanced Skim Coat™ Floor Patch
- USG Durock™ RH-100™ Moisture Vapor Reducer
- USG Durock™ X2 Primer-Sealer

usg.com/floorprep

USG DUROCK™ BRAND FLOOR PREP PRODUCTS

At USG, we know how important it is to get the floor right. Rework is expensive and delays are costly. That's where USG Performance Flooring comes in. We offer the most innovative products and systems, ensuring you get the right floor the first time.



EQUIVALENT PRODUCT CATEGORY	APPLICATION	FEATURES AND BENEFITS ¹
USG DUROCK™ BRAND ULTRACAP® SELF-LEVELING UNDERLAYMENT		
<ul style="list-style-type: none"> Portland cement self-levelers 	<ul style="list-style-type: none"> Interior use over concrete and wood² subfloors 	<ul style="list-style-type: none"> Portland cement Extended working time 5,000 psi (35.4 MPa) Wear surface with an appropriate coating Featheredge to 2" (5 cm), 5" (13 cm) thickness when extended Value priced Low VOC emissions
USG DUROCK™ BRAND QUIK-TOP™ SELF-LEVELING UNDERLAYMENT (GRAY/WHITE)		
<ul style="list-style-type: none"> High-performance self-levelers 	<ul style="list-style-type: none"> Interior applications over concrete, wood and gypsum subfloors and over well-bonded existing floor coverings on concrete, including ceramic tile, vinyl composition tile (VCT), cement terrazzo and thin cutback adhesive when a fast turnaround is required 	<ul style="list-style-type: none"> Proprietary engineered cement UL Classified for use in fire-rated assemblies Low-prep³ (prime and pour) 10-year limited system warranty available⁴ 7,000-10,000 psi (48.3-68.9 MPa) Non-shrinking and self-sealing Featheredge to 3" (8 cm) thickness Install floor coverings in as little as 15 hours Can be stained or polished Wear surface with an appropriate coating system Low VOC emissions
USG DUROCK™ BRAND ADVANCED SKIM COAT™ FLOOR PATCH		
<ul style="list-style-type: none"> High-performance patches 	<ul style="list-style-type: none"> Patch and skim coat over most interior subfloors, including wood, concrete, gypsum, metal and tile 	<ul style="list-style-type: none"> Calcium aluminate cement Fast setting—floor coverings may be installed in as little as 15 minutes Innovative formulation offers significant yield advantage vs. competitive products No priming necessary over most surfaces 10-year limited system warranty available⁵ Featheredge to 1/2 in. (12.7 mm) thick in large areas; any thickness in small well-defined areas such as thresholds and concave-shaped depressions in substrates Easy mixing and smooth finish over various substrates May be used as an embossing leveler⁶
USG DUROCK™ BRAND RH-100™ MOISTURE VAPOR REDUCER		
<ul style="list-style-type: none"> Moisture mitigation systems 	<ul style="list-style-type: none"> Over concrete, tolerates up to 100% RH and 14 pH 	<ul style="list-style-type: none"> Two-part epoxy system Can be installed five days after concrete placement Great penetration and spreading characteristics Fast cure—becomes tack-free in as little as four hours, depending on conditions Low odor Low VOC emissions
USG DUROCK™ BRAND X2 PRIMER-SEALER		
<ul style="list-style-type: none"> High-performance primers and sealers 	<ul style="list-style-type: none"> Single coat primer over concrete and wood and surface sealer over USG Durock™ Brand gypsum-based self-leveler 	<ul style="list-style-type: none"> Proprietary polymer formula 10-year limited system warranty available⁵ Multi-purpose single-coat primer for USG Levelrock® and USG Durock™ Brand self-leveling underlayments USG Levelrock® and USG Durock™ Brand gypsum-based underlayment sealer Low VOC emissions

Notes:

- See corresponding product submittal sheets for details and installation instructions at usg.com
- Installation of wire lath is required over wood subfloors.
- No mechanical preparation of the substrate is required for most applications.
- A 10-year limited system warranty applies when using this product sealed with USG Durock™ Brand X2 Primer-Sealer and a XL Brands® manufactured adhesive. Please contact USG for further details.
- A 10-year limited system warranty applies when using this product in conjunction with an XL Brands® manufactured adhesive. Please contact USG for further details.
- For maximum bond when embossing, use in conjunction with USG Durock™ Brand Matrix™ Bond Enhancer.

CB790-USA-ENG/rev. 2-17
 © 2017 USG Corporation and/or its affiliates.
 All rights reserved.
 Printed in the USA

Manufactured by or for
United States Gypsum Company
 550 West Adams Street
 Chicago, IL 60661

800 USG.4YOU
 800 (874-4968)
 usg.com/floorprep

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

TRADEMARKS

The trademarks USG, ADVANCED SKIM COAT, DUROCK, LEVELROCK, MATRIX, QUIK-TOP, RH-100, ULTRACAP, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

XL Brands is a registered trademark of XL Brands, LLC.

NOTICE We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

NOTE The information in this document is subject to change without notice. USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document. Consult your USG Company sales office or representative for information.

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read Safety Data Sheets and related literature on products before specification and/or installation.

