

USG
Performance
Flooring
Solutions



USG DUROCK™ BRAND QUIK-COVER™ SELF-LEVELING UNDERLAYMENT

- Fast-track solution for commercial and institutional repair and renovation
- Allows for application of most floor coverings in as little as 1 hour; wood in 12 hours
- Featheredge to 1 in. (25.4 mm) thick
- No mechanical preparation required for most applications
- Fast and easy to mix

USG 
IT'S YOUR WORLD. BUILD IT.®

USG DUROCK™ BRAND QUIK-COVER™

SELF-LEVELING UNDERLAYMENT

New construction, major renovation or minor repairs – USG has a solution for every flooring demand. USG Durock™ Fast Track Products offer quick return to service – saving you time and money.

DESCRIPTION

USG Durock™ Brand Quik-Cover™ Self-Leveling Underlayment is a proprietary calcium aluminate product with quick-drying technology designed by USG for interior use in commercial, institutional and rehab construction. USG Durock™ Quik-Cover Self-Leveling Underlayment is the ideal product for fast-track renovation when the space needs to return to use as quickly as possible. USG Durock™ Quik-Cover Self-Leveling Underlayment allows floor coverings to be installed in as little as one hour after underlayment application. USG Durock™ Quik-Cover Self-Leveling Underlayment requires minimal subfloor preparation and provides a smooth, hard surface that resists indentation.

USG Durock™ Quik-Cover Self-Leveling Underlayment is suitable for a variety of floor coverings and exceeds commercial resilient floor-covering requirements for underlayments with compressive strengths exceeding 5,000 psi (34.5 MPa). Higher compressive strengths minimize floor damage from other trades and reduces the need for repair patching.

When used with an appropriate clear coating system, USG Durock™ Quik-Cover Self-Leveling Underlayment can be used as a finished floor and provides a concrete look. For detailed instructions including application restrictions and how to prepare the subfloor, see the *USG Durock™ Brand Quik-Cover™ Self-Leveling Underlayment* submittal sheet (CB844) at usg.com.

APPLICATIONS

Concrete slabs, pre-stressed concrete and concrete planks.

PRODUCT DATA

Thickness Range	Featheredge-1 in. (25.4 mm)
Approximate Compressive Strength ASTM C109 (Modified)¹	5,000 psi ² (34.5 MPa)
Approximate Flow Time at 70 °F (21 °C)	20 minutes
Approximate Coverage Rate	25 sq. ft. (2.3 m ²) per bag at 1/4 in. (6.3 mm) thickness
Approximate Final Set ASTM C191	40-60 minutes ²
Approximate Walkable	60-90 minutes
Time to Floor Covering	60-90 minutes; wood in 12 hours
Approximate Dry Density	120-126 lbs./cu. ft. ² (1920-2018 kg/m ³)
Packaging	50 lb. (22.7 kg) multiwall paper bags

Notes

1. ASTM C109 modified refers to air drying as opposed to damp curing.
2. Results published herein were achieved under controlled laboratory conditions. Actual field results may differ due to environmental conditions, inconsistent proportioning of field-applied water and USG Durock™ Quik-Cover Self-Leveling Underlayment, as well as differences in mixing/pumping equipment.

CB5022-USA-ENG/7-17

© 2017 USG Corporation and/or its affiliates.
All rights reserved.
Printed in U.S.A.

Manufactured by or for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

800.USG.4YOU
800 (874-4968)
usg.com
usgdesignstudio.com

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

DANGER

Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction. May cause cancer by inhalation of respirable crystalline silica. Do not handle until all safety precautions have

been read and understood. Avoid breathing dust. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear protective gloves/protective clothing/eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses and continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If swallowed, inhaled, or skin irritation occurs get medical attention. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Dispose of in accordance with local, state, and federal regulations. For more information call Product Safety: 800-507-8899 or see the SDS at usg.com

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, DUROCK, QUIK-COVER, IT'S YOUR WORLD, BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTE

The information in this document is subject to change without notice. USG Corp. assumes no responsibility for any errors that

may inadvertently appear in this document. Consult your USG Company sales office or representative for information.

NOTICE

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read Submittal Sheet CB844, SDS and literature at usg.com before specification and installation.