

USG ECLIPSE™/ECLIPSE™ HIGH-NRC ACOUSTICAL PANELS


CLIMAPLUS™ PERFORMANCE

USG Eclipse™ Acoustical Panels
with ClimaPlus™ Performance, and
USG Donn® Brand Identitee® DXI™
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM

See individual items for color availability.

STANDARD COLORS



ADVANTAGE COLORS



FEATURES AND BENEFITS

- Elegant, fine-textured visual.
- Excellent noise reduction (up to NRC-0.75).
- Balanced Acoustics. High-NRC and High-CAC.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- USG Eclipse™ Acoustical Panels is part of the Ecoblueprint™ portfolio — meeting today's sustainability standards. For sustainability documentation go to USG.com or CGCInc.com.

APPLICATIONS

- Offices
- Conference areas
- Healthcare (HIPAA requirements)
- Retail stores

SUBSTRATE

- Wet-formed mineral fiber

Fine-Textured Panel

USG ECLIPSE™/ECLIPSE™ HIGH-NRC ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL**
usgdesignstudio.com
cgcdesignstudio.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818



USG ECLIPSE™ PANELS

USG ECLIPSE™ HIGH-NRC PANELS

Edge	Panel Size	Fire Rating	Item No.	UL Classified			Color ⁴	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹	Panel Cost
				NRC	CAC	LR ²						
SQ	2'x2'x3/4"	Class A	76575	0.70	35	0.86	White	A, B, C	Low		79%	\$
	2'x4'x3/4"	Class A	78575	0.70	35	0.86	White	A, B	Low		79%	\$
SLT	2'x2'x3/4"	Class A	76775	0.70	35	0.86	White/ Colors	D	Low		79%	\$
	600x600x19	Class A	ME76775	0.70	35	0.86	White	D	Low		79%	\$
FL	2'x4'x3/4"	Class A	78775	0.70	35	0.86	White	D	Low		79%	\$
	2'x2'x3/4"	Class A	76975	0.70	35	0.86	White/ Colors	E, F, G, H	Low		79%	\$
SQ	600x600x19	Class A	ME76975	0.70	35	0.86	White	E, F, G, H	Low		79%	\$
	2'x4'x3/4"	Class A	78975	0.70	35	0.86	White	E, F, G, H	Low		79%	\$
SLT	2'x2'x7/8"	Class A	76520	0.75	35	0.86	White	A, B, C	Low		80%	\$
	2'x4'x7/8"	Class A	76521	0.75	35	0.86	White	A, B	Low		80%	\$
FL	2'x2'x7/8"	Class A	76522	0.75	35	0.86	White	D	Low		80%	\$
	2'x4'x7/8"	Class A	76523	0.75	35	0.86	White	D	Low		80%	\$
SQ	2'x2'x7/8"	Class A	76524	0.75	35	0.86	White	E, F, G, H	Low		80%	\$
	2'x4'x7/8"	Class A	76525	0.75	35	0.86	White	E, F, G, H	Low		80%	\$

Low Emissions

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C ⁵ USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Finline® DXF™	G USG Finline® 1/8 DXFF™	H USG Identitee® DXI™

PHYSICAL DATA

Product literature
Data sheet: SC1812

ASTM E1264 classification

ASTM E1264-22 Type III, Form 1, Pattern E & I
ASTM E1264-23 Type A, Form A1.1, Pattern G & K

ASTM E84 and CAN/ULC S102 surface-burning characteristics

Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Imperial weight
1.10-1.19 lb./sq. ft. (Class A panels)

Metric weight
5.07 kg/m2 (Class A panels)

Thermal resistance
R-2.0 (Class A)

Maximum backloading
See USG 30-Year Limited System Warranty
Commercial Applications (SC2102).

Online tools
usgdesignstudio.com or cgcdesignstudio.com

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Metric sizes available
Contact sales for minimum quantities and lead times.

Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- See Colors selector for more information. Metric: white only.
- Maximum 2'x2' with SQ edge panels.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1812/rev. 8-23

© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXLF, DXLT, DXT, DXW, ECLIPSE, FINELINE, IDENTITEE, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

