

USG LEVELROCK™ BRAND CRACK SUPPRESSION MAT

Polymeric-reinforcement crack suppression mat

- Can be used over a variety of subfloors
- May contribute towards LEED® credits
- Installed by USG Levelrock® authorized applicators

DESCRIPTION

USG Levelrock™ Brand Crack Suppression Mat (CSM) is a 3/8 in.-thick random filament, non-geometrically-patterned mat used during the renovation of old buildings. Designed for interior use directly over concrete, plywood or OSB subfloors, USG Levelrock CSM is a Class A fire-rated product.

USG Levelrock CSM is made from 40% post-consumer recycled polypropylene and may contribute towards LEED MR credits for Recycled content and LEED MR Regional credits. Contact USG for further information.

LIMITATIONS

1. Do not use in exterior applications.
2. Do not install where continuous exposure to moisture is a possibility.
3. Structure shall be designed so that deflection does not exceed L/240 from combined dead and live loads and L/360 from live loads. Certain floor coverings such as marble, limestone, travertine and wood may have more restrictive deflection limits. Consult the appropriate floor-covering manufacturer.
4. For wood subfloors, do not install on plywood/OSB subfloors lacking tongue and groove edges without back-blocking.

INSTALLATION

USG Levelrock crack suppression mat can be used over concrete, plywood or OSB subfloors. For plywood or OSB subfloors, the edges must be tongue and groove or the use of back blocking is required. The subfloor must be clean and free of construction debris and dirt. The building temperature should be maintained at a 50 °F minimum.

Protect USG Levelrock underlayment floors poured over USG Levelrock CSM from heavy trade traffic loads (i.e. loaded drywall carts, heavy tool cabinets, etc.) with plywood.

For further details on installation requirements, specifications and the most up-to-date product information, please see IG1763 *USG Levelrock Applicator Best Practices Manual* or visit usg.com, pourlevelrock.com and usgdesignstudio.com.

PRODUCT DATA

	USG Levelrock™ Brand Crack Suppression Mat
Thickness (inches)	3/8" (0.375")
Width (inches)	39.5"
Roll Length (feet)	100'
Coverage Per Roll (ft²)	330
Weight (ounces/yard²)	13.5
Weight Per Roll (lbs)	24
Roll Diameter (inches)	19.0
Rolls Per Pallet	8

STORAGE

All material shall be delivered and stored on the job in their original unopened packaging. Do not expose material to sunlight. The material must be stored in an enclosed shelter providing protection from damage and exposure to the elements. Remove damaged or deteriorated material from the premises.

SUBMITTAL APPROVALS

Job Name	
Contractor	Date

PRODUCT INFORMATION

See usg.com or pourlevelrock.com for the most up-to-date product information.

LEED INFORMATION

For the most up-to-date information on LEED rating systems, project certification and the U.S. Green Building Council, please visit usgbc.org.

CAUTION

Dust may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. Remove contact lenses and continue rinsing. If on skin: Wash with plenty of water. If irritation persists, call physician. For more information call Product Safety: 800-507-8899 or see the SDS at usg.com

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, LEVELROCK, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates.
LEED is a registered trademark of U.S. Green Building Council.

NOTICE

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

800 USG.4YOU
800 (874.4968)
usg.com
pourlevelrock.com
usgdesignstudio.com

Manufactured for
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG1917/rev 1-16
© 2016 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

USG
IT'S YOUR WORLD. BUILD IT.®